




ASTRONERGY



ASTRO N7

CHSM66RN(DG)/F-BH
Bifacial Series


630~650W



Warranty

15 15-year Product Warranty

30 30-year Linear Power Warranty
(Only to the front-side of modules)



n-type TOPCon

Newly upgraded cell technology, ultra-high product energy efficiency



Better Temperature Coefficient

$\leq -0.29\%/^{\circ}\text{C}$, adapting for high temperature



Low Voc Design

Increasing modules per string, lower BOS cost



Bifacial Power Generation

Maximizing bifaciality, boosting backside power output



ISO 9001:2015:ISO Quality Management System
ISO 14001:2015:ISO Environment Management System
ISO 45001:Occupational Health and Safety



Tier 1
BloombergNEF



630~650W

POWER RANGE

0~+3%


POWER SORTING

24.1%MAX MODULE
EFFICIENCY**≤ 1.0%**FIRST YEAR
POWER DEGRADATION**≤ 0.4%**YEAR 2-30
POWER DEGRADATION

Mechanical Specifications

Outer dimensions (L x W x H)	2382 x 1134 x 30 mm
Cell type	n-type mono-crystalline
No. of cells	132 (6*22)
Frame technology	Aluminum, silver anodized
Front / Back glass	2.0+2.0 mm
Cable length (Including connector)	Portrait: (+)350 mm, (-)250 mm; Customized length
Cable diameter (IEC/UL)	4 mm ² / 12 AWG
① Maximum mechanical test load	5400 Pa (front) / 2400 Pa (back)
Connector type (IEC/UL)	PV-HCB40 (Chint New Energy) or PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy (Stäubli)
Module weight	31.65 kg
Packing unit	36 pcs / box
Weight of packing unit (for 40'HQ container)	1190 kg
Modules per 40' HQ container	720 pcs (Subject to sales contract)

① Refer to Astronergy crystalline installation manual or contact technical department.
Maximum Mechanical Test Load=1.5×Maximum Mechanical Design Load.



Electrical Specifications CHSM66RN(DG)/F-BH-XXX(XXX=630~650)

STC: Irradiance 1000W/m², Cell Temperature 25° C, AM=1.5

Rated output (P _{mpp} / Wp)	630	635	640	645	650
Rated voltage (V _{mpp} / V)	41.82	41.86	41.99	42.11	42.24
Rated current (I _{mpp} / A)	15.07	15.17	15.24	15.32	15.39
Open circuit voltage (V _{oc} / V)	49.34	49.42	49.57	49.72	49.87
Short circuit current (I _{sc} / A)	16.27	16.35	16.42	16.50	16.58
Module efficiency	23.3%	23.5%	23.7%	23.9%	24.1%

Tolerance: P_{mpp} ±3%, V_{oc} ±3% and I_{sc} ±4%.**BNPI & BSI:** Bifaciality(P_{mpp}/I_{sc}): 80±5 %, Bifaciality(V_{oc}): 98±5 %

Rated output (P _{mpp} / Wp)	694.6	702.3	707.8	713.4	718.9
Rated voltage (V _{mpp} / V)	41.83	41.87	42.00	42.13	42.25
Rated current (I _{mpp} / A)	16.60	16.77	16.85	16.93	17.01
Open circuit voltage (V _{oc} / V)	49.35	49.43	49.58	49.73	49.88
Short circuit current (I _{sc} / A)	17.99	18.13	18.21	18.30	18.38
I _{sc} [aBSI (BSI)]	20.09	20.31	20.40	20.50	20.59

BNPI: Irradiance: front 1000W/m², rear 135W/m², Cell Temperature 25° C, AM=1.5aBSI (BSI): Irradiance: front 1000W/m², rear 300W/m²

Electrical characteristics with 10% Bifacial Gains

Rated output (P _{mpp} / Wp)	693.00	698.50	704.00	709.50	715.00
Rated voltage (V _{mpp} / V)	41.82	41.86	41.99	42.11	42.24
Rated current (I _{mpp} / A)	16.58	16.69	16.77	16.85	16.93
Open circuit voltage (V _{oc} / V)	49.34	49.42	49.57	49.72	49.87
Short circuit current (I _{sc} / A)	17.90	17.98	18.07	18.15	18.23




Temperature Ratings (STC)

Temperature coefficient (P _{mpp})	-0.29%/°C
Temperature coefficient (I _{sc})	+0.043%/°C
Temperature coefficient (V _{oc})	-0.25%/°C
Fire performance:	Class A / Class C

Operating Parameters

Operating Temperature	-40°C ~+85°C
No. of diodes	3
Junction box IP rating	IP 68
Max. series fuse rating	35 A
Max. system voltage (IEC/UL)	1500V _{DC}
Module [T98] max[°C]: 70	

Curve



Made in China, Made in Turkey.

© Chint New Energy Technology Co., Ltd. Reserves the right of final interpretation. please contact our company to use the latest version for contract.

<http://www.astronergy.com.au>

202507