



AZ-ARD

The AZ-ARD-series low pressure two-position damper was developed for economical control of supply air in the HVAC System. The solid aluminum shaft provides a sturdy platform to attach the blade and damper actuator. The damper actuator with built-in coil spring is designed for years of care-free operation. Foam tape provides a positive seal for the blade. Long-life nylon bushings insure a quiet, low friction operation of the damper. Heavy-duty galvanized steel cylinder provides strength to keep the damper round. One crimped end and one straight end allows for flexible installation. 30-Second operation to full close position.




- FAIL-SAFE SPRING OPEN DESIGN
- SIMPLE, 2-WIRE CONNECTIONS
- AVAILABLE SIZES: 5", 6", 7", 8", 9", 10", 12", 14", 16"
- HEAVY-DUTY ACTUATOR
- POWER CLOSE/SPRING OPEN
- 5 YEAR FACTORY WARRANTY

SPECIFICATIONS

POWER	24VAC, 9 VA typical (12 VA Max)
ACTUATOR	Synchronous A/C type Heavy-Duty Metal Gearing 30-second Operation Direct Drive Shaft Coupling Backlash Protection Power Close/Spring Open
WIRING	2 – Wire Connection for Wire Nuts Standard 18-3 Thermostat Wire 24VAC, Common

PART NUMBER	D CYLINDER DIAMTER (INCHES)	L CYLINDER LENGTH (INCHES)
FAD06	6	12
FAD07	7	12
FAD08	8	12
FAD09	9	12
FAD10	10	12
FAD12	12	12
FAD14	14	14
FAD16	16	16



ALL RIGHTS RESERVED TO D-VAC SALES INC.
 200B VERDI STREET, FARMINGDALE NY 11735
SALES@DVACHVAC.COM
 516-256-3131

