

The AZ-EZ4F controller features a state-of-the-art microprocessor for reliable control of two (2) zones from a single forced-air HVAC system. The panel includes a bright, backlit LCD display with full text for system status monitoring and diagnosis. In addition, each thermostat and equipment terminal has its own color-coded LED allowing for easy monitoring of thermostat and equipment calls. The included supply air temperature sensor allows for constant monitoring of supply air temperature in the plenum. XCI's exclusive Electronic Limit Control[™] (ELC) technology protects the system's compressor and heat exchanger from potential issues associated with freeze-up and over heating. Intelligent Smart-Staging[™] handles equipment staging based on time and temperature, allowing the use of single-stage thermostats. Exclusive Economy Mode provides comfort and efficiency control. Supports up to 3-Stage Heating and 2-Stage Cooling equipment.

 \triangleright

- \triangleright Full-Featured 2-Zone Controller
- \geq Electronic Limit Control
- Intelligent SmartStaging
- ≻ **On-Board Fresh Air & Economizer** \geq Control ≻
- Bright, Backlit LCD Display
- Return Ari or Fresh Air Temperature Monitoring Available

EZ INSTALLATION

- Mounts with Two Screws
- **Quick-Connect Screwless Terminals**
- Innovating Enclosure Design with Multiple Wiring and Mounting Options

EZ CONFIGURATION

- Simple Step-By-Step System Setup
- Controller Guides You Thru Each Step
- Backlit LCD Display is EZ to see
- No Dipswitches No Confusion No Guessing

EZ TROUBLESHOOTING

- **Display Indicates Full System Status**
- Color-Coded LED Indicators for Each Thermostat Call & Equipment Call
- Two-Color LED Indicators show Damper Position
- **Red LED Indicates Blown Fuse**

- Supply Air & Return Air Sensor Included
- Plastic Enclosure and Spare Fuse Included
- AZ's Exclusive Start-up Equipment Test Mode
- Stand-Alone or 2-Zone Expansion Module
- LED Indicates Blown Fuse
- **Dependable Field-Proven Platform**

EZ CUSTOMER FEATURES

- Customer Never Needs to Use the Control Panel
- Selectable Zone-1 Priority for More Customer Control
- Enable Emergency Heat from Zone 1 Thermostat
- Constant Supply Air Monitoring from ELC[™] Ensures Customer Safetv
- Zone Specific Ventilation Energize Fan from Any Thermostat

EZ OPERATION

- Mix & Match Standard Gas/Electric and Heat Pump Thermostats
- Intelligent Staging[™] Based on Supply Air Temperature
- Automatic Changeover for Maximum Comfort
- Microprocessor Manages All Complex Decisions
- Adjustable Staging Time and Temperature for Maximum Comfort

ALL RIGHTS RESERVED TO D-VAC SALES INC. 200B VERDI STREET, FARMINGDALE NY 11735 SALES@DVACHVAC.COM 516-256-3131



HVAC Manufacturer's Representive







AZ-EZ4F

ZONE CONTROLLER

	EZ4F	8VA Max (24VAC @ 300mA)			
POWER		Separate transformer design for controller, thermostats and dampers (Field Suppl	lied)		
		Separate RC & RH terminals for separate equipment transformers, if needed	Í Í		
	System Power	8VA + Thermostats (3VA) + Dampers (3 to 10VA) = Total Transformer Size			
	Requirements				
ă.	Protection	Integrated 5x20mm 300ma Slo-Blo Fuse - One replacement also included			
					- în - I
					U.
		10 AMP @ 24VAC Contact Rating			
		RH - 24VAC HOT from Heating Transformer on Equipment (RED Led)			
OUTPUTS		RC - 24VAC HOT from Cooling Transformer on Equipment (RED Led)			
	Equipment	C - 24VAC COMMON from Transformer on Equipment (NO Led)	10.625″		
		Y1 - 1st Stage Compressor (YELLOW Led)			
5		Y2 - 2nd Stage Compressor (YELLOW Led)			- P
ō		G - Fan (GREEN Led)			
		W1/EH - 1st Stage Heat OR Emergency Heat (RED Led)			
		W2 O/B - Reversing Valve OR 2nd Stage Heat (ORANGE Led)			
ŝ		10 AMP @ 24VAC Contact Rating	—		
5		Power Close/Spring Open Dampers (10VA)			- 1 ⁰
ουτρυτε	Dampers	Power Open/Power Close Dampers (3VA)			
0	Dampero			• Å 💻	
S			— ↓ I		
		LABEL - DESCRIPTION (LED COLOR)			
		R - 24VAC HOT (RED)		5.6875″	
		C - Common (NONE)			
INPUTS		Y - Compressor (YELLOW)		+	
Z	Thermostat	G - Fan (GREEN)			
		W - Heart OR Emergency Heat (RED)			
		O/B - Reversing Valve (ORANGE)			
		EC - Economy Input (GREEN) ← Zone ONE Only			
Ş		10K Type II Thermistor			
5	Temperature	SA Sensor - 4" Supply Air Temperature Sensor - Stainless Steel Probe w/10ft.			
INPUTS		Cable and Plug (Provided with each SmartZone Controller)			
_					
		SPECIAL FEATURES			
FEATURES	Equipment	A/C - Gas Heat		10.625"	
	Capabilities	A/C - Electric Heat			
		Electric Heat Pump - Electric Auxiliary Heat			
		3 Heat/2 Cool			
	Controller	Intelligent Staging			
	Capabilities	Zone 1 Thermostat Staging Capable			
		Electronic Limit Control			
		Adjustable High and Low Limit Set points			
Ξ		Adjustable Time and Temperature Aux Heat Staging			
		Works with Most 5-Wire Thermostats with Common Terminal		*	
		On-Board Supply Air Temperature Monitoring			<>
		Back-lit LCD Display		_	1.625"
		LED Indicators for Thermostat and Equipment Calls		5.6875"	
		Exclusive Technician Run-Test Mode	·		
		5-Year Warranty			
		LED Indicator for Blown Fuse	1.625″	-	-
			↓		

ALL RIGHTS RESERVED TO D-VAC SALES INC. 200B VERDI STREET, FARMINGDALE NY 11735 <u>SALES@DVACHVAC.COM</u> 516-256-3131



HVAC Manufacturer's Representive