



SP SPORT MAXX 050+

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R18	40	225/40ZR18 92Y XL	236	635	8
R18	45	225/45ZR18 95Y XL	236	657	7.5
R18	50	235/50ZR18 101W XL	258	691	7.5
R17	45	215/45ZR17 91Y XL	225	624	7
R17	50	205/50ZR17 93Y XL	226	636	6.5
R17	50	215/50ZR17 95W XL	237	649	7

DIREZZA DZ102

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R18	35	215/35R18 84W XL	214	607	7.5
R18	40	205/40R18 86W XL	214	621	7.5
R18	40	215/40R18 89W XL	207	628	7.5
R18	40	225/40R18 88W	230	635	8
R18	40	235/40R18 91W	239	644	8.5
R18	40	245/40R18 97W XL	241	652	8.5
R18	45	225/45R18 91W	222	657	7.5
R18	50	225/50R18 95W	228	682	7
R18	50	235/50R18 97V	241	693	7.5
R18	55	225/55R18 98V	233	704	7
R18	60	235/60R18 103H	236	739	7
R17	40	205/40R17 84W XL	213	596	7.5
R17	40	215/40R17 87W XL	216	601	7.5
R17	45	205/45R17 84W	207	614	7
R17	45	215/45R17 87W	209	626	7
R17	45	225/45R17 94W XL	221	633	7.5
R17	45	245/45R17 95W	239	651	8
R17	50	205/50R17 93W XL	209	637	6.5
R17	50	215/50R17 91V	222	648	7
R16	50	195/50R16 84V	198	602	6
R16	55	205/55R16 91V	212	633	6.5

SP SPORT LM705

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R19	30	275/30ZR19 96W XL	282	649	9.5
R19	35	225/35ZR19 88W XL	232	642	8
R19	35	235/35ZR19 91W XL	244	648	8.5
R19	55	235/55R19 101V	248	745	7.5
R18	35	265/35ZR18 97W XL	275	646	9.5
R18	50	235/50R18 97W	248	698	7.5

R18	55	235/55R18 100V	248	719	7.5
R18	60	225/60R18 100V	230	731	6.5
R18	60	255/60R18 112V XL	263	769	7.5
R17	45	205/45R17 88W XL	206	617	7
R17	45	215/45R17 91W XL	215	629	7
R17	50	215/50R17 95V XL	228	651	7
R17	50	225/50R17 98V XL	235	663	7
R17	55	215/55R17 94V	228	672	7
R17	55	225/55R17 101W XL	235	684	7
R17	60	215/60R17 96H	223	694	6.5
R17	60	225/60R17 99H	230	706	6.5
R16	45	195/45R16 80W	196	585	6.5
R16	50	195/50R16 84V	202	605	6
R16	55	185/55R16 83V	195	612	6
R16	55	195/55R16 87V	201	622	6
R16	55	205/55R16 91V	216	636	6.5
R16	55	225/55R16 99W XL	235	658	7
R16	60	195/60R16 89H	202	644	6
R16	60	205/60R16 92H	210	656	6
R16	60	215/60R16 95H	223	668	6.5
R16	65	205/65R16 95H	210	676	6
R16	65	215/65R16 98H	223	692	6.5
R15	55	185/55R15 82V	195	587	6
R15	55	195/55R15 85V	202	597	6
R15	60	185/60R15 84H	190	607	5.5
R15	60	195/60R15 88H	202	619	6
R15	65	185/65R15 88H	190	625	5.5
R15	65	195/65R15 91H	202	639	6
R15	65	205/65R15 94H	210	651	6
R15	70	205/70R15 96H	217	669	6
R15	70	215/70R15 98H	221	683	6.5
R14	70	185/70R14 88H	189	616	5.5
R14	70	195/70R14 91H	201	630	6
R14	70	205/70R14 94H	209	644	6

ENASAVE EC300+

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R17	55	205/55R17 91V	210	660	6.5
R17	60	215/60R17 96H	221	690	6.5
R17	60	205/60R17 94H	206	678	6
R16	50	195/50R16 84V	201	602	6
R16	55	195/55R16 87V	201	620	6
R16	55	185/55R16 83H	194	610	6
R16	55	205/55R16 91V	214	632	6.5
R16	60	185/60R16 86H	187	630	5.5
R16	60	215/60R16 95H	220	660	6.5
R16	60	195/60R16 89H	201	640	6
R16	65	205/65R16 95H	209	672	6
R16	65	195/65R16 92H	201	661	6

R16	65	215/65R16 98S	221	686	6.5
R15	55	185/55R15 82H	194	585	6
R15	60	185/60R15 84H	189	603	5.5
R15	65	195/65R15 91H	201	635	6
R15	65	185/65R15 88S	189	621	5.5
R15	65	185/65R15 88H	189	621	5.5
R15	65	205/65R15 94H	209	647	6
R14	70	185/70R14 88S	189	616	5.5

ENASAVE EC350+

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R16	60	195/60R16 89H	200	642	6
R15	65	185/65R15 88H	189	622	5.5

SP TOURING R1

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R16	60	185/60R16 86T	189	628	5.5
R16	60	205/60R16 92T	209	652	6
R15	60	175/60R15 81S	177	591	5
R15	60	185/60R15 84T	189	603	5.5
R15	60	195/60R15 88T	201	615	6
R15	60	205/60R15 91T	209	627	6
R15	65	175/65R15 84S	177	609	5
R15	65	185/65R15 88S	189	621	5.5
R15	65	195/65R15 91T	201	635	6
R15	65	205/65R15 94T	209	647	6
R15	65	215/65R15 96T	221	661	6.5
R14	60	185/60R14 82T	189	578	5.5
R14	65	165/65R14 79S	170	570	5
R14	65	175/65R14 82S	177	584	5
R14	65	185/65R14 86T	189	596	5.5
R14	65	195/65R14 89S	201	610	6
R14	70	185/70R14 88S	189	616	5.5
R14	70	195/70R14 91T	201	630	6
R14	80	185/80R14 91S	188	652	5
R13	65	165/65R13 77S	170	544	5
R13	70	175/70R13 82S	177	576	5
R13	70	185/70R13 86S	189	590	5.5
R13	80	165/80R13 83S	167	597	4.5
R12	70	175/70R12 80S	177	551	5

GRANDTREK AT5

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R18	55	235/55R18 100H BLT	243	715	7.5
R18	60	265/60R18 110H BLT	273	775	8
R17	60	235/60R17 102H BLT	240	713	7
R17	65	225/65R17 102H BLT	230	725	6.5

R17	65	235/65R17 108H BLT	241	736	7
R17	65	265/65R17 112S BLT	271	780	8
R17	65	285/65R17 116T BLT	292	802	8.5
R17	70	265/70R17 115S WLT	278	800	8
R16	60	235/60R16 100H BLT	241	688	7
R16	70	215/70R16 100T BLT	224	711	6.5
R16	70	225/70R16 103T WLT	233	721	6.5
R16	70	245/70R16 111T WLT	252	748	7
R16	70	255/70R16 111T WLT	256	762	7.5
R16	70	265/70R16 112T WLT	274	779	8
R16	75	225/75R16 108S WLT	227	742	6
R16	75	245/75R16 111S WLT	255	772	7
R16	75	265/75R16 116S WLT	268	804	7.5
R16	75	285/75R16 122/119Q OWL	294	833	8
R15	-	30X9.50R15LT 104S	240	750	7.5
R15	-	31X10.50R15LT 109S	271	772	8.5
R15	70	235/70R15 107S XL WLT	245	708	7
R15	70	205/70R15 96T WLT	209	671	6
R15	70	265/70R15 112T OWL	268	804	7.5

GRANDTREK ST30

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R19	55	225/55R19 99H	237	733	7
R18	60	225/60R18 100H	228	727	6.5
R17	65	225/65R17 102H	228	724	6.5
R17	65	225/65R17 102T	228	724	6.5

GRANDTREK ST20

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R16	60	235/60R16 100H	240	688	7
R16	65	215/65R16 98S	221	686	6.5
R16	65	215/65R16 98H	221	686	6.5

GRANDTREK AT20

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R17	65	265/65R17 112S	272	776	8
R16	70	255/70R16 111H	260	764	7.5
R16	70	225/70R16 102S	228	722	6.5
R16	70	265/70R16 112S	272	778	8

GRANDTREK AT22

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R17	65	275/65R17 115H	279	790	8
R15	75	235/75R15 109S	235	733	6.5

GRANDTREK AT25

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R18	60	265/60R18 110H (PT)	272	775	8
R18	60	265/60R18 110H	272	775	8
R17	65	265/65R17 112S	272	776	8

GRANDTREK MT2 (WIDE)

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R17	65	265/65R17 112Q	272	776	8
R16	75	LT265/75R16 112/109Q	267	804	7.5
R15	75	235/75R15 105Q	240	737	6.5

GRANDTREK MT2 (NARROW)

Rim	Aspek Ratio	Ukuran	h Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R15	-	30X9.50R15LT 104Q	240	756	7.5
R15	-	31X10.50R15LT 109Q	268	775	8.5
R14	-	27X8.50R14LT 95Q	218	680	7

SP10

Rim	Aspek Ratio	Ukuran	h Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R15	65	185/65R15 88S	189	621	5.5
R14	70	185/70R14 88S	189	616	5.5
R12	-	155SR12 76S	155	555	4.5

SP LT 5

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R15	-	195R15C 106/104R 8PR	198	689	5.5
R14	-	185R14C 8PR	188	653	5.5
R14	-	195R14C 8PR	198	670	5.5
R13	-	175R13C 8PR	178	612	5
R13	-	165R13C 8PR	167	599	4.5

HI-MAX

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R13	80	165/80R13 82S	165	594	4.5
R12	70	175/70R12 80S	177	551	5

SP VAN 01

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R16	65	235/65R16C 115/113R 10PR	239	711	7
R16	75	225/75R16C 121/120R 10PR	229	741	6
R15	70	225/70R15C 112/110R 8PR	228	698	6.5

SP LT 4

Rim	Aspek Ratio	Ukuran	Ukuran Ban Terpompa (mm)		Lebar Pelek(inch)
			Lebar	Diameter	
R13	80	165R13C	165	599	4.5