

BI-FOLD DOOR TB



Transmittance

$U_w \geq 0.97$ (W/m²K)

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing **45 mm**

Minimum glazing **25 mm**

Sightlines

Frame 73 mm
Sash 73 mm

Profile Thickness

Door 1.8 mm

Polyamide strip length

Frame 20 mm

Sash 30 mm

Maximum dimensions / Sash

Width (L) = 1,200 mm

Height (H) = 3,000 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 120 kg

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability

(UNE-EN 12207): Class 4

Water tightness

(UNE-EN 12208): Class 9A

Wind resistance

(UNE-EN 12210): Class A3

* Reference test 2.70 x 2.53 m. 3 Sashes.

Security test: PAS24 ☒

Passed

* Reference test 3 Sashes. Configuration 330. 2,701 x 2,517 mm

Test verified by

ALUMINIOS CORTIZO S.A.U.

Extrusion alloy

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewva Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Inward opening: From 1 to 14 Sashes

Outward opening: From 1 to 14 Sashes, possibility of corner sash at 90° without a mullion

