



**Putzmeister**



**VSP**

Vehicle Mounted Thom-Katt® Pump

## Driven to perform

Now added to our Vehicle-Series product line with the VSP 50 Vehicle Mounted Thom-Katt® Pump. It doesn't require a CDL to operate, which means more versatility for your staff.

It delivers the same high-level performance and output as the reliable Thom-Katt® TK 50 on a rugged flatbed-style chassis. The VSP 50 is well suited for pumping grout, block fill, and shotcrete applications due to its ø6" (150mm) concrete cylinders.

## Standard features

- Large side decks with folding side panels
- Entry steps to both deck sides
- Large side-mounted aluminum toolbox
- 150 gal (568L) water tank
- Water pump
- Variable volume (0 to full) pump output
- Double hydraulic circuit with accumulator
- Proximity sensors in hydraulic cylinders
- Hard-chromed concrete cylinders
- Long lasting fabric-reinforced piston cups
- Proven reliable S-Valve with splined shaft
- Twin shifting ball and socket cylinders
- Centralized hopper-mounted grease system
- Hydraulic remixer/agitator
- Fully enclosed weatherproof control panel with color display of pump information
- Multi-Function remote control with 100 ft (30m) cable
- High quality paint finish

## VSP 50 Specifications

Dimensions		
Fill height	46.3'	(1,175mm)
Deck height	44.5"	(1,130mm)
Deck length	12.5'	(3.81m)
Height	80.3'	(2,040mm)
Width	96.5"	(2,450mm)
Length	29'	(8.8m)

Capacities		
Hopper	9.5 ft³	270L
Hydraulic tank	45 gal	170L
Water tank	150 gal	570L

Performance		
Output Vol	54 yd³/hr	41m³/hr
Output Press	1,450 psi	79 bar
Strokes/min	43	

Major Parts		
Hy-cyl		80 x 45 H mm
Del-cyl		150 x 1000mm
S-tube		S1512
Outlet		5" HD

Chassis		
Mfr		Ram 5500 Regular Cab 4x4
Engine		6.7L Cummins Diesel
Power	325 hp	242kW
Torque	750 lb-ft	1,016Nm
Transmission		Automatic 6-speed
Fuel tank	45 gal	170L
WB	204"	5,180mm
CA	120"	3,050mm
Max GVWR	19,500 lb	8,845kg
Max GAWR Front	7,250 lb	3,288kg
Max GAWR Rear	13,500 lb	6,123kg



## Driven to perform

Now added to our Vehicle-Series product line with the VSP 60HP Vehicle Mounted Thom-Katt® Pump. It doesn't require a CDL to operate, which means more versatility for your staff.

It delivers the same high-level performance and output as the reliable Thom-Katt® TK 60HP on a rugged flatbed-style chassis. The VSP 60HP is well suited for pumping grout, block fill, and shotcrete applications due to its ø6" (150mm) concrete cylinders.

## Standard features

- Large side decks with folding side panels
- Entry steps to both deck sides
- Large side-mounted aluminum toolbox
- 150 gal (568L) water tank
- Water pump
- Variable volume (0 to full) pump output
- Double hydraulic circuit with accumulator
- Proximity sensors in hydraulic cylinders
- Hard-chromed concrete cylinders
- Long lasting fabric-reinforced piston cups
- Proven reliable S-Valve with splined shaft
- Twin shifting ball and socket cylinders
- Centralized hopper-mounted grease system
- Hydraulic mixer/agitator
- Fully enclosed weatherproof control panel with color display of pump information
- Multi-Function remote control with 100 ft (30m) cable
- High quality paint finish

## VSP 60HP Specifications

Dimensions		
Fill height	46.3'	(1,175mm)
Deck height	44.5"	(1,130mm)
Deck length	12.5'	(3.81m)
Height	80.3'	(2,040mm)
Width	96.5"	(2,450mm)
Length	29'	(8.8m)

Capacities		
Hopper	9.5 ft³	270L
Hydraulic tank	45 gal	170L
Water tank	150 gal	570L

Performance		
Output Vol	56 yd³/hr	43m³/hr
Output Press	1,450 psi	100 bar
Strokes/min	44	

Major Parts		
Hy-cyl		110 x 63 R mm
Del-cyl		150 x 1000mm
S-tube		S1512
Outlet		5" HD

Chassis		
Mfr		Ram 5500 Regular Cab 4x4
Engine		6.7L Cummins Diesel
Power	325 hp	242kW
Torque	750 lb-ft	1,016Nm
Transmission		Automatic 6-speed
Fuel tank	45 gal	170L
WB	204"	5,180mm
CA	120"	3,050mm
Max GVWR	19,500 lb	8,845kg
Max GAWR Front	7,250 lb	3,288kg
Max GAWR Rear	13,500 lb	6,123kg



## Driven to perform

Now added to our Vehicle-Series product line with the VSP 70 Vehicle Mounted Thom-Katt® Pump. It doesn't require a CDL to operate, which means more versatility for your staff.

It delivers the same high-level performance and output as the reliable Thom-Katt® TK 60HP on a rugged flatbed-style chassis. The VSP 60HP is well suited for pumping grout, block fill, and shotcrete applications due to its ø6" (150mm) concrete cylinders.



## VSP 70 Specifications

Dimensions		
Fill height	46.3"	(1,175mm)
Deck height	44.5"	(1,130mm)
Deck length	11.3'	(3.45m)
Height	80.3"	(2,040mm)
Width	96.5"	(2,450mm)
Length	27.6'	(8.4m)

Capacities		
Hopper	9.5 ft³	270L
Hydraulic tank	45 gal	170L
Water tank	150 gal	570L

Performance		
Output Vol	74 yd³/hr	57m³/hr
Output Press	1,130 psi	78 bar
Strokes/min	43	43

Major Parts		
Hy-cyl		110 x 63 R mm
Del-cyl		180 x 1000mm
S-tube		S1812
Outlet		5" HD

Chassis		
Mfr		Ram 5500 Regular Cab 4x4
Engine		6.7L Cummins Diesel
Power	325 hp	242kW
Torque	750 lb-ft	1,016Nm
Transmission		Automatic 6-speed
Fuel tank	22 gal	83L
WB	204"	5,180mm
CA	120"	3,050mm
Max GVWR	19,500 lb	8,845kg
Max GAWR Front	7,250 lb	3,288kg
Max GAWR Rear	13,500 lb	6,123kg

**DU98662@msn.com**



Putzmeister America, Inc.  
 1733 90th Street  
 Sturtevant, WI 53177 USA

Phone (262) 886-3200  
 Toll-free (800) 884-7210  
 Fax (262) 884-6338

Authorized Distributor © Putzmeister America, Inc. 2020. Printed in the USA. CT  
 4824 US Photos and drawings are for illustrative purposes only.

[www.PutzmeisterAmerica.com](http://www.PutzmeisterAmerica.com) [pmr@putmeister.com](mailto:pmr@putmeister.com)