



# **FAS 4 - 11KW**

The FAS product range includes air cooled, single stage silenced and packages screw compressors in the power range of 4 - 11kW. These compressors are designed for industrial application and 24x7 continuous duty. All models are driven by highly efficient IE3 efficiency class electric motors.

As an option, FAS compressors are available with pre-assembled accessories like

Air receiver Refrigeration Dryer Pre & post down stream filters



#### **EXCELLENT QUALITY**

High quality components in combination with decades of experience in building air ends ensure durability with constantly high efficiency.





## INTEGRATED OIL SEPARATOR IN THE OIL TANK

The large oil tank is equipped with all necessary connections and safety installations and therefore ensures the highest operational safety. The internal high efficiency oil separator guarantees excellent compressed air quality with a remaining oil content of  $< 3mg/m^3$ .

Through an inspection glass the oil level can be controlled at all times. Service can be conducted quickly and safely – the inlet neck as well as the oil drain valve can be easily accessed.

### HIGH PERFORMANCE SUCTION FILTER

In all models a high performance suction filter is installed. Sucked particles are filtered in two stages: first by centrifugal forces and second by a high efficiency filter element.

## **ELECTRIC MOTOR**

The driving motor conforms to energy efficiency class IE3, protection class IP55, insulation class F and is thus most suited for rugged, continuous duty industrial application, with highest efficiency.

## HIGH EFFICIENCY COOLING

The cooling system for both air and oil is designed in a way that the compressor can efficiently operate even at high ambient temperature of 45°C.

# **CONFIGURATION TABLE**

Machine Model	FAS-4 — 11B Base Mounted	FAS-4 – 11T Tank Mounted	FAS-4 – 11A UltraPack	FAS-4 – 11D Skid mounted with Dryer
Air compressor unit	✓	✓	$\checkmark$	✓
Refrigerated air dryer			✓	✓
Pre-filter			✓	$\checkmark$
Post-filter			✓	✓
Air receiver		✓	$\checkmark$	



# **TECHNICAL DATA**

Machine Model		FAS-4	FAS-6	FAS-8	FAS-11	FAS-11(HE)	
Cooling Type		Air-cooled					
	7 kg/cm² (g)	19	28	39	62	76	
Working pressure/Free Air	8 kg/cm² (g)	18	26	36	58	67	
Delivery CFM	10 kg/cm <sup>2</sup> (g)	14	23	34	53	59	
	12 kg/cm² (g)	12	18	29	49	54	
	14 kg/cm² (g)	11	15	25	42	48	
	16 kg/cm² (g)	9	13	21	35	40	
	Power (kW)	4	5.5	7.5	11	11	
	Starting method	Star-Delta Star-Delta					
	Voltage/ Frequency (V/Hz)	400V, 50Hz					
Electric Motor	Protection Level	IP 55					
	Insulation Class	F Class					
	Motor Efficiency	IE3					
Drive		Belt Driven					
Noise (dBA)		65 +/- 3 68 +/- 3					
Oil Carryover (ppm)		≤3					
Discharge temperature (after cooler) (°C)		≤ Ambient temperature+15°C					
Lubricant Capaticy (L)		6			8		
Outlet (inch)		G1/2 G3/4					

Machine Model - Base Mounted		FAS-4B	FAS-6B	FAS-8B	FAS-11B	FAS-11 (HE)B
	Length (mm)	660		800	880	
External Dimension	Width (mm)	600		800	830	
	Height (mm)	890		995	1075	
Weight (kg)		230	240	280	300	350

Machine Model - Tank Mounted		FAS-4T	FAS-6T	FAS-8T	FAS-11T	FAS-11 (HE)T+
Tank Volume (L)			500L			
External Dimension	Length (mm)	1650		1650	1650	2174
	Width (mm)	800		900	900	900
	Height (mm)	1533		1638	1716	1716
Weight (kg)		340	405	390	410	520

Machine Model - Ultra Pack		FAS-4A	FAS-6A	FAS-8A	FAS-11A	FAS-11 (HE)A+
Tank Volume (L)			500L			
External Dimension	Length (mm)	1650		1650	1650	2174
	Width (mm)	800		900	900	900
	Height (mm)	1533		1638	1716	1716
Weight (kg)		378	405	445	465	575

The data & performance were recorded in accordance with latest ISO 1217 standard.

The sound level was measured in accordance with PNEUROP/CAGI standard.

Tank mounted & Ultrapack models are also available with 500L tank, details on request.

Due to continous engineering improvements, above features are subject to change without prior notice.





Compressors! No compromises.

Email: info@firstair.in www.india.firstaircompressor.com

FS Compressors India Pvt. Ltd. Plot No. S-3, Phase-II, Chakan MIDC, Village, Sawardari, Khed, Maharashtra 410501

# **Distributor**

eaflet firstAir FN 03/17