

3300®

PROFESSIONAL GRADE POLYURETHANE SEALANT

Advanced Formula Engineered with Professional Contractors & Manufactured by an Industry Leader

Every Geocel brand of product is a reflection of who we are and embodies the high level of performance and quality on which builders have come to depend.

As an industry leader with over 40 years of innovation, knowledge, and experience, we understand the job site needs. That is why our focus is delivering total solutions with global access in a product that you can count on long after the sale.

So when choosing the right sealant for the job, look to the brand that is backed by the quality, performance, expertise, and after-the-sale support you deserve. Look to Geocel.

Product Attributes

- Easy to tool
- Withstands adverse weather conditions
- Meets ASTM C 920, TT-S-00230C
- Remains flexible – will not crack
- Primerless adhesion on most substrates
- Paintable, non-corrosive
- Contains no TDI (toluene diisocyanate)
- Moisture cure, minimal shrinkage

Adheres to

- Aluminum • Asphalt Shingles • Built-up Roofing (BUR) • Building Paper (lath, roof)
- Coated Steel (Kynar 500® based finishes**) • Concrete (poured, block)
- Fiberglass • Galvanized Steel • Masonry (Brick)
- Sheet Metal (HVAC) • Vinyl • Wood



C O M P A R E

	3300® Sealant	Sonneborn NP-1
Paintable	Yes	Yes
Tack Free	3 Hours	Skins overnight or within 24 Hours
Gap Filling (width)	1/2"	1/2"
Cold Weather Application	-20° F	Can be applied below freezing temps. only if substrates are completely dry, clean, & free of moisture. Warm product for 24 hours before using.
Cure (days)	1	Approx. 7
Elongation	880%	800%
Meets ASTM C 920	Yes	Yes
Competitive data taken from manufacturer's technical data sheet, SDS, & website		

* Toluene Diisocyanate (TDI) is used as a chemical in the production of polyurethane products. It is extremely toxic with acute and chronic exposures. 3300 Sealant **DOES NOT** contain TDI.
** Kynar 500® is a registered trademark of Arkema Inc., and is used under license.

Geocel
Setting the Standard®

Geocel Products Group, A Business Unit of The Sherwin-Williams Company
Cleveland, OH 44115 | Ph. (800) 348-7615 | Fx. (800) 348-7009 | www.GeocelUSA.com

1115 703302