



Electrical Characteristics		
AMPS	(A)	N/A
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+80
IN	(kA)	20
15 impulses 8/20µs		
Installation		
Accessories		Screws
Product DimensionL	mm	59.0000
Product DimensionH	mm	85.0000
Product DimensionW	mm	50.0000
Product DimensionL	In	2.3200
Product DimensionH	In	3.3400
Product DimensionW	In	1.9600
Miscellaneous		
Individual Pack		Yes
Storage TemperatureMin	°C	-40.0000
Storage TemperatureMax	°C	85.0000
Storage TemperatureMin	°F	-40.0000
Storage TemperatureMax	°F	85.0000
Mechanical Characteristics		
CONNECTION METHOD		36" #12 AWG LEADS
MATERIAL		Aluminum cast
NEMA RATING (IP RATING)		6
FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required
REAL-TIME DIAGNOSTICS		LED and audible alarm
DIMENSIONS		See diagram
WEIGHT		2.5 lbs.
Standards		
UL STANDARD		UL1449 5th Edition
UL FILE NUMBER		E326289
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Part number		
899002		