

323ST STAND ON COMPACT LOADER

ENGINE

| | |
|---------------------------------------|---|
| ENGINE TYPE | Dual cylinder(90° V type) 4 stroke forced air cooling |
| MODEL NAME | HONDA GX690 |
| DISPLACEMENT | 688 (ml) |
| ENGINE POWER - SAE J1995 GROSS | 23 HP |
| RATED POWER | 3600 rpm |
| MAXIMUM NET TORQUE | 38.6(n·m) 2500 rpm |

DIMENSIONS

| | |
|---|---|
| OVERALL LENGTH-TRANSPORT (W/STD BUCKET PARALLEL TO GROUND) | 94.5" (2400 mm) |
| OVERALL LENGTH (W/O BUCKET) | 67" (1700 mm) |
| OVERALL HEIGHT | 60.2" (1530 mm) |
| OVERALL WIDTH W/STD BUCKET(S/T) | S: 39.3" (1000 mm) T: 35.0" (890 mm) |
| OPERATING WEIGHT (W/O OPERATOR) LBS | 2426 lbs (1,100 kg) |
| RATED OPERATING CAPACITY (35%) | 883 lb (400 kg) ROC |
| WHEELBASE | 28.5" (720 mm) |
| HINGE PIN HEIGHT AT MAX. LIFT | 73.4" (1860 mm) |
| TRACK WIDTH | 7.8" (200 mm) |
| GROUND CLEARANCE(S/T) | S: 6.7" (170 mm) T: 5.5" (140 mm) |
| ANGLE OF DEPARTURE | 15° |

PERFORMANCE

| | |
|-------------------------------------|--|
| ATTACHMENT MOUNTING SYSTEM | CII (Common Industry Interface) or 2 Lever Quick-Attach |
| BATTERY CAPACITY | 12V, 48AH |
| AUXILIARY HYDRAULIC FLOW | 11.3 gal/min (43 L/min) |
| AUXILIARY HYDRAULIC PRESSURE | 2610 psi (18 mPa) (183.4 kgf/cm ²) |

SERVICE AND FILL CAPACITIES

| | |
|---------------------------|-----------------|
| FUEL TANK CAPACITY | 4.23 gal (16 L) |
| HYDRAULIC SYSTEM | 5.82 gal (22 L) |

