

323S STAND ON COMPACT LOADER

ENGINE

ENGINE TYPE	Dual cylinder(90° V type) 4 stroke forced air cooling
MODEL NAME	HONDA GX690 or VANGUARD
DISPLACEMENT	688 (ml)
ENGINE POWER - SAE J1995 GROSS	23 HP
RATED POWER	3600 rpm
MAXIMUM NET TORQUE	38.6(n·m) 2500 rpm

DIMENSIONS

OVERALL LENGTH-TRANSPORT (W/STD BUCKET PARALLEL TO GROUND)	94.5" (2400 mm)
OVERALL LENGTH (W/O BUCKET)	67" (1700 mm)
OVERALL HEIGHT	60.2" (1530 mm)
OVERALL WIDTH W/STD BUCKET	44" (1140 mm)
OPERATING WEIGHT (W/O OPERATOR) LBS	1900 lbs (870 kgs)
RATED OPERATING CAPACITY (35%)	883 lb (400 kg) ROC
WHEELBASE	28.5" (720 mm)
HINGE PIN HEIGHT AT MAX. LIFT	73.4" (1860 mm)
GROUND CLEARANCE	6.7" (170 mm)
ANGLE OF DEPARTURE	15°

PERFORMANCE

ATTACHMENT MOUNTING SYSTEM	or 2 Lever Quick-Attach
BATTERY CAPACITY	12V, 48AH
AUXILIARY HYDRAULIC FLOW	11.3 gal/min (43 L/min)
AUXILIARY HYDRAULIC PRESSURE	2610 psi (18 mPa) (183.4 kgf/cm ²)

SERVICE AND FILL CAPACITIES

FUEL TANK CAPACITY	4.23 gal (16 L)
HYDRAULIC SYSTEM	5.82 gal (22 L)

