

## The measurement of an "acre" is uniformly equivalent to: 66 lineal feet x 660 lineal feet = 43,560 square feet

1 acre = 43,560 sq. ft.

 $\frac{3}{4}$  acre = 32,670 sq. ft.

 $\frac{1}{2}$  acre = 21,780 sq. ft.

 $\frac{1}{3}$  acre = 14,520 sq. ft.

 $\frac{1}{4}$  acre = 10,890 sq. ft.

Caravan G - 30 lb bag covers approximately 10,000 sq. ft.

Arena - 30 lb bag covers approximately 10,000 sq. ft.

## **Spreader Settings**

Spreader Brand	Model	2.0 lb. per 1,000 ft <sup>2</sup>	2.8 lb. per 1,000 ft <sup>2</sup>	Approximate Swath Width
Agri-Fab	45-03881	N/A	2	6 ft.
Andersons	AccuPro 1000	L 1/2	M <sup>1</sup> / <sub>2</sub>	10 ft.
Andersons	AccuPro 2000	L 1/2	M <sup>1</sup> / <sub>2</sub>	10 ft.
Andersons	SR-2000	L 1/2	M <sup>1</sup> / <sub>2</sub>	10 ft.
Earthway Ev-N-Spread	2050	7	8	8 ft.
Earthway Ev-N-Spread	2170	13	14	8 ft.
Lesco	Commercial Plus	8	10	10 ft.
Lesco	Commercial Rotary	A 1/2	B 1/2	10 ft.
Perma-Green	Magnum B1B	5.5	6	7 ft.
Prizelawn	BF I	M	N	10 ft.
Prizelawn	CBR III	J 1/2	К	10 ft.
Scotts	Precision Green	3.5	4.5	2 ft.
Spyker Rotary	46-22	2.5	3	6 ft.
Turfco	T-3000	3.5	4	13 ft.

Spreader settings are approximate. Differences may occur due to condition of spreader, speed at which applied, and roughness of area treated. Be sure to check spreader at the beginning of the application; adjust spreader if necessary.

**Broadcast Spreaders:** If your lawn is rectangular, apply two border strips across each end for a turning area. If your lawn is an irregular shape, apply a border strip completely around it. Then apply product back and forth in the longest direction. Turn the spreader off and on at the edge of each strip to prevent uneven application. Overlap the throw pattern by about a foot to ensure complete coverage.

## **DIY Pest and Lawn 386-774-2847**

2417 Enterprise Rd., Orange City, FL 32763

WARRANTY AND CONDITIONS OF SALE Seller makes no warranty, expressed or implied, concerning the use and handling of this product other than indicated on the label. Buyer assumes all risk of use and handling of this material when such use and handling are contrary to label instructions.