



EnviroECOats MS-Cement Modifier by Milenium is a polymer cement modifier for use with concrete powder to provide a polymer modified cement for pedestrian traffic application. The mixed cement product is used for underlayment and for fill and sloping as needed prior to applying the acrylic base / top coatings. The product is intended to be mixed with fine concrete mixed at 1 gallon per 50 lbs. bag. The modified concrete mixture has to be mixed thoroughly until homogeneous and applied using a trowel at ¼' thick. Allow the modified concrete to dry prior to adding surface treatment or texturing. Allow 24 hours to cure prior to adding an acrylic topcoat.

MS-Cement Modifier is intended for:

- Thin Concrete topper
- Refinish layer mixed with fine concrete
- Decorative Finish on walls and non-vehicular flooring
- Concrete patching
- Thin layer wall surface
- Cement overlay
- Application on cured concrete
- Plywood with an application of no greater than ½' of polymer modified concrete
- Application on plywood with supporting metal lath at no greater than 1" of polymer modified concrete

MS-Cement Modifier is not intended for:

- Areas where vehicle are expected
- Submerge application
- Do not apply on a wet surface

Who is EnviroECOats?

Milenium Solutions is a company started by 2 Engineers with over 30 years combined experience in the Building Materials industry. Their expertise resides in Process Engineering, Material Performance, Laboratory Testing and Qualification, Code Compliance and Quality Management in a high volume, multiple locations, and manufacturing environment. With access to the most up-to-date testing equipment, both founders can test and validate product quality and performance. In addition, the mission is to provide the Market with high performance, highly competitive, cost effective, and environmentally friendly solutions.

