



BEESWIFT
ONLINE

Product Code:
GZ01

Available in Sizes:
S - 2XL

Unit of Measure:
Pair

Available in Colours:

 Grey
GZ01GY

GLOVEZILLA NITRILE PALM COATED GLOVE

- HPPE 40.9%, Nylon 14.1%, Polyester 15.9%, Glass Fibre 21.3%, Spandex 7.8% Liner.
- 100% Nitrile rubber coating.
- Ventilated back.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications

- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 2 - Puncture Resistance
- Level C - TDM Cut Resistance (ISO 13997)



BEESWIFT
ONLINE

Product Code:
GZ10

Available in Sizes:
S-XXL

Unit of Measure:
Pair

Available in Colours:

 Blue
GZ10B

GLOVEZILLA CUT RESISTANT FOOD SAFE GLOVE

- HPPE 47.4%, Polyester 20.1%, Glass Fibre 17.2%, Steel 14%, Spandex 1.3%.
- Food Safe and washable.
- Extremely high cut protection.
- Suitable for general food preparation and areas where high cut protection is needed.

- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 2 - Puncture Resistance
- Level F - TDM Cut Resistance (ISO 13997)





BEESWIFT
ONLINE


Product Code:
GZ112

Available in Sizes:
S - 2XL


Unit of Measure:
PK 10

Available in Colours:

 Blue
GZ112B

 CE Marked CAT 2

 UK CA Marked CAT 2

 Food Handling

GLOVEZILLA HPPE 18G GLOVE CUT E

- 18 Gauge knit
- Grey PU palm coating
- UHMWPE liner
- Comfortable ergonomic fit
- EN388: 2016
- Level 4 - Abrasion
- Level X - Cut Resistance
- Level 4 - Tear Resistance
- Level 2 - Puncture
- Level E - ISO 13997 Cut Resistance
- Foodsafe (Except for fatty foods)



GLOVEZILLA HPPE 18G GLOVE CUT F

- 18 Gauge knit
- Grey nitrile palm coating
- HPPE liner
- Comfortable ergonomic fit
- EN388: 2016
- Level 4 - Abrasion
- Level X - Cut Resistance
- Level 4 - Tear Resistance
- Level 2 - Puncture
- Level F - ISO 13997 Cut Resistance
- Foodsafe (Except for fatty foods)



BEESWIFT
ONLINE

Product Code:
GZ113B

Available in Sizes:
S - 2XL

Unit of Measure:
PK 10

Available in Colours:

 Blue
GZ113B





BEESWIFT
O N L I N E

Product Code:
GZ13Y12TH

Available in Sizes:
12"

Unit of Measure:
Pair

Available in Colours:

 Yellow
GZ13Y12TH

GLOVEZILLA PARA-ARAMID SLEEVE WITH THUMB HOLES 12"

- 100% Para-Aramid Liner.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 1 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 2 - Tear Resistance
- Level 3 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)

- EN ISO 11612: 2015
- A1 - Limited Flame Spread (Method A)
- F2 - Contact Heat (250C for between 10 to 15 Seconds)



GLOVEZILLA PARA-ARAMID SLEEVE 10"

- 100% Para-Aramid Liner.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 1 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 2 - Tear Resistance
- Level 3 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)

- EN ISO 11612: 2015
- A1 - Limited Flame Spread (Method A)
- F2 - Contact Heat (250C for between 10 to 15 Seconds)



BEESWIFT
O N L I N E

Product Code:
GZ14Y10

Available in Sizes:
10"

Unit of Measure:
Pair

Available in Colours:

 Yellow
GZ14Y10





BEESWIFT
ONLINE

Product Code:
GZ15Y18

Available in Sizes:
18"

Unit of Measure:
Pair

Available in Colours:

 Yellow
GZ15Y18

GLOVEZILLA PARA-ARAMID SLEEVE 18"

- 100% Para-Aramid Liner.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 1 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 2 - Tear Resistance
- Level 3 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)

- EN ISO 11612: 2015
- A1 - Limited Flame Spread (Method A)
- F2 - Contact Heat (250C for between 10 to 15 Seconds)



GLOVEZILLA PARA-ARAMID SLEEVE WITH THUMB HOLE 18"

- 100% Para-Aramid Liner.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 1 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 2 - Tear Resistance
- Level 3 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)

- EN ISO 11612: 2015
- A1 - Limited Flame Spread (Method A)
- F2 - Contact Heat (250C for between 10 to 15 Seconds)



BEESWIFT
ONLINE

Product Code:
GZ15Y18TH

Available in Sizes:
10"

Unit of Measure:
Pair

Available in Colours:

 Yellow
GZ15Y18TH





BEESWIFT
ONLINE

Product Code:
GZ16Y22TH

Available in Sizes:
22"

Unit of Measure:
Pair

Available in Colours:

 Yellow
GZ16Y22TH

GLOVEZILLA PARA-ARAMID SLEEVE WITH THUMB HOLES 22"

- 100% Para-Aramid Liner.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 1 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 2 - Tear Resistance
- Level 3 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)

- EN ISO 11612: 2015
- A1 - Limited Flame Spread (Method A)
- F2 - Contact Heat (250C for between 10 to 15 Seconds)



BEESWIFT
ONLINE

Product Code:
GZ61

Available in Sizes:
S-XXL

Unit of Measure:
Pair

Available in Colours:

 Orange
GZ61OR

CUT RESISTANT FULLY COATED IMPACT GLOVE

- 13 Gauge Liner.
- 20% UHMW PE+ 80% rubber
- 100% TPE Fully Injection coating.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 3 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 2 - Puncture Resistance
- Level C - TDM Cut Resistance (ISO 13997)
- Level P - Impact Protection





BEESWIFT
ONLINE

Product Code:
GZ62

Available in Sizes:
S-XXL

Unit of Measure:
Pair

Available in Colours:



Green
GZ62G

CUT RESISTANT FULLY COATED IMPACT GLOVE

- 13 Gauge Liner.
- 20% UHMW PE+ 80% rubber
- 100% TPE Fully Injection coating.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.
- EN 388:2016+A1:2018
- Level 3 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 2 - Puncture Resistance
- Level D - TDM Cut Resistance (ISO 13997)
- Level P - Impact Protection



GLOVEZILLA CUT RESISTANT DRIVERS GLOVE

- Premium soft grain Leather.
- Natural Coloured backing.
- Half elasticsation to back of cuff.
- Para-Aramid lining.
- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 4 - Puncture Resistance
- Level D - TDM Cut Resistance (ISO 13997)



BEESWIFT
ONLINE

Product Code:
GZ71

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:



White
GZ71W





BEESSWIFT
ONLINE

Product Code:
GZ50BR

Available in Sizes:
XL

Unit of Measure:
Pair

Available in Colours:



Brown
GZ50BR

GLOVEZILLA THERMAL LEATHER GLOVE

- Premium Cowhide Split Leather
- G-150gram Thinsulate and Micro Fleece
- Nylon Cuff
- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 3 - Tear Resistance
- Level 4 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)
- EN 511:2006
- Level 1 - Convective Cold Resistance
- Level 3 - Contact Cold Resistance
- Level X - Water Penetration



GLOVEZILLA ANTI-VIBRATION GLOVE

- 40% polyester +60% Latex
- High performance anti-vibration gloves
- EN388: 2016
- Level 4 - Abrasion
- Level X - Cut Resistance
- Level 4 - Tear Resistance
- Level 2 - Puncture
- Level B - ISO 13997 Cut Resistance

EN10819:
Medium Frequency Spectrum "M" - 0.865 Pass
High Frequency Spectrum "H" - 0.598 Pass



BEESSWIFT
ONLINE

Product Code:
GZAVG

Available in Sizes:
L - XL

Unit of Measure:
Each

Available in Colours:



Black
GZAVG

Anti-Vibration

Mechanical Handling





BEESWIFT
ONLINE

Product Code:
GZ103

Available in Sizes:
S-XXL

Unit of Measure:
PK 10

Available in Colours:



Red
GZ103RE

GLOVEZILLA NITRILE NYLON GLOVE

- Microfiber knitting
 - Single nitrile coating
 - 18 gauge nylon
 - Breathable
 - Mixed spandex
 - Oil and wet resistance
 - High level abrasion resistance
- EN 388: 2016
 - Level 3 - Abrasion
 - Level X - Cut Resistance
 - Level 2 - Tear Resistance
 - Level 1 - Puncture
 - Level A - ISO 13997 Cut Resistance



BEESWIFT
ONLINE

Product Code:
GZ09

Available in Sizes:
S-XXL

Unit of Measure:
Pair

Available in Colours:



Green
GZ09G

GLOVEZILLA LATEX PALM COATED GLOVE

- Para-Aramid 25.5, Steel 11%, Polyester 16.6%, Polycotton 46% Liner.
 - Latex palm Coating.
 - Ventilated back.
 - Lightweight for maximum dexterity and comfort with sensitivity.
 - Suitable for general assembly handling and engineering applications.
- EN 388:2016+A1:2018
 - Level 3 - Abrasion Resistance
 - Level X - Cut resistance (Coupe Test)
 - Level 4 - Tear Resistance
 - Level 2 - Puncture Resistance
 - Level D - TDM Cut Resistance (ISO 13997)





BEESWIFT
ONLINE

Product Code:
GZ102

Available in Sizes:
S-XXL

Unit of Measure:
PK 10

Available in Colours:



Blue
GZ102B

GLOVEZILLA LATEX F/C WATER RESISTANT GLOVE

- 15-gauge nylon liner
- Fully coated with latex
- Water resistant
- Dry/wet grip
- EN388: 2016
- Level 2 - Abrasion
- Level X - Cut Resistance
- Level 4 - Tear Resistance
- Level 1 - Puncture
- Level A - ISO 13997 Cut Resistance



BEESWIFT
ONLINE

Product Code:
GZ105

Available in Sizes:
S-XXL

Unit of Measure:
PK 10

Available in Colours:



Orange
GZ105OR

GLOVEZILLA LATEX THERMAL GLOVE

- Double coated latex
- 13-gauge napped acrylic liner
- Wet/dry grip
- Extra cold resistance
- EN388: 2016
- Level 1 - Abrasion
- Level X - Cut Resistance
- Level 4 - Tear Resistance
- Level 1 - Puncture
- Level B - ISO 13997 Cut Resistance
- EN 511: 2006
- Level 1 - Convective Cold
- Level 1 - Contact Cold
- Level X - Water Permeability
- EN 407: 2004
- Level X - Burning Behaviour
- Level 2 - Contact Heat
- Level X - Convective heat
- Level X - Radiant heat
- Level X - Small splashes of Molten Metal
- Level X - Large splashes of Molten Metal





BEESWIFT
ONLINE

Product Code:
GZ02LG

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:



Green
GZ02LG

GLOVEZILLA NITRILE PALM COATED HI-VIS GLOVE

- HPPE 49%, Polyester 25%, Glass Fibre 12%, Steel 8%, Spandex 6% Liner.
- 100% Nitrile Rubber Coating
- 100% PVC TPR Back of hand protection.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 2 - Puncture Resistance
- Level D - TDM Cut Resistance (ISO 13997)



BEESWIFT
ONLINE

Product Code:
GZ04

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:



Grey
GZ04GY

GLOVEZILLA NITRILE PALM COATED GLOVE

- HPPE 40.9%, Nylon 14.1%, Polyester 15.9%, Glass fibre 21.3%, Spandex 7.8% Liner.
- 100% Nitrile Rubber Coating.
- 100% PVC TPR back of hand protection.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 2 - Puncture Resistance
- Level D - TDM Cut Resistance (ISO 13997)





BEESSWIFT
ONLINE

Product Code:
GZ06

Available in Sizes:
S-XXL

Unit of Measure:
Pair

Available in Colours:



Yellow
GZ06Y

GLOVEZILLA NITRILE PALM COATED GLOVE

- Para-Aramid 71.2%, Steel 13.5%, Polyester 10.5%, Spandex 8% Liner.
- 100% Nitrile rubber coating.
- Ventilated back.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 1 - Puncture Resistance
- Level D - TDM Cut Resistance (ISO 13997)



GLOVEZILLA NITRILE FOAM NYLON GLOVE

- Nitrile Foam coating
- 15 Gauge - Nylon and Polyester
- Comfortable and breathable for prolonged periods when performing precision tasks

- EN 388: 2016
- Level 4 - Abrasion
- Level X - Cut resistance
- Level 3 - Tear resistance
- Level 1 - Puncture
- Level A - ISO 13997 Cut Resistance



BEESSWIFT
ONLINE

Product Code:
GZ104

Available in Sizes:
S-XXL

Unit of Measure:
PK 10

Available in Colours:



Purple
GZ104PU





BEESWIFT
ONLINE

Product Code:
GZ107BN

Available in Sizes:
S-XXL

Unit of Measure:
Bx 10

Available in Colours:



Blue
GZ107BN

GLOVEZILLA WATERPROOF THERMAL NITRILE GLOVE

- Double coated nitrile offers water and oil resistance
- Wet/dry grip
- Washable and can be tumble dried (Follow instructions)

- EN388: 2016
- Level 4 - Abrasion
- Level X - Cut Resistance
- Level 2 - Tear Resistance
- Level 1 - Puncture
- Level B - ISO 13997 Cut Resistance

- EN 511: 2006
- Level X - Convective Cold
- Level 2 - Contact Cold
- Level X - Water Penetration




BEESWIFT
ONLINE

Product Code:
GZ109REN

Available in Sizes:
S-XXL

Unit of Measure:
Bx 10

Available in Colours:



Red
GZ109REN

GLOVEZILLA WATERPROOF NITRILE CUT D GLOVE

- Double coated nitrile
- 13-gauge HPPE/Glass Fiber/Spandex liner
- Wet/dry grip
- Offers fantastic oil and water resistance
- Washable and can be tumble dried (follow instructions)

- EN 388: 2016
- Level 4 - Abrasion
- Level X - Cut resistance
- Level 4 - Tear resistance
- Level 3 - Puncture
- Level D - ISO 13997 Cut Resistance





BEESWIFT
ONLINE

Product Code:
GZ60

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:



Green
GZ60LG

GLOVEZILLA SANDY NITRILE COATED GLOVE

- 13 Gauge, HPPE, Polyester, Glass Fibre Green Liner.
- 100% Sandy Nitrile Coating
- 100% TPR Back of hand protection.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 3 - Puncture Resistance
- Level C - TDM Cut Resistance (ISO 13997)
- Level P - Impact Protection




BEESWIFT
ONLINE

Product Code:
GZ63

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:



Orange
GZ63OR

GLOVEZILLA SANDY NITRILE COATED GLOVE

- 13 Gauge, HPPE, Polyester, Glass Fibre Orange Liner.
- 100% Sandy Nitrile Coating
- 100% TPR Back of hand protection.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 3 - Puncture Resistance
- Level C - TDM Cut Resistance (ISO 13997)
- Level P - Impact Protection





BEESWIFT
ONLINE

Product Code:
GZ64

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:



GLOVEZILLA FOAM NITRILE COATED GLOVE

- 13 Gauge, HPPE, Polyester, Glass Fibre Green Liner.
- 100% Foam Nitrile Coating
- 100% TPR Back of hand protection.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 3 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 3 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)
- Level P - Impact Protection



GLOVEZILLA FOAM NITRILE COATED GLOVE

- 13 Gauge Orange Liner.
- 45% UHMW PE + 30% nitrile + 25% rubber
- 100% Foam Nitrile Coating
- 100% TPR Back of hand protection.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.

- EN 388:2016+A1:2018
- Level 3 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 3 - Puncture Resistance
- Level B - TDM Cut Resistance (ISO 13997)
- Level P - Impact Protection



BEESWIFT
ONLINE

Product Code:
GZ65

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:





BEESWIFT
ONLINE

Product Code:
GZ70

Available in Sizes:
M-XXL

Unit of Measure:
Pair

Available in Colours:



White
GZ70W

GLOVEZILLA CUT RESISTANT RIGGER GLOVE

- Premium Grey split leather.
- Heavyweight cotton backing and safety cuff.
- Para-Aramid lining.
- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 4 - Puncture Resistance
- Level E - TDM Cut Resistance (ISO 13997)



BEESWIFT
ONLINE

Product Code:
GZ03

Available in Sizes:
S-XXL

Unit of Measure:
Pair

Available in Colours:



Grey
GZ03GY

GLOVEZILLA PU PALM COATED GLOVE

- HPPE 40.9%, Nylon 14.1%, Polyester 15.9%, Glass fibre 21.3%, Spandex 7.8% Liner.
- 100% PU Coating.
- Ventilated back.
- Lightweight for maximum dexterity and comfort with sensitivity.
- Suitable for general assembly handling and engineering applications.
- EN 388:2016+A1:2018
- Level 4 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 2 - Puncture Resistance
- Level C - TDM Cut Resistance (ISO 13997)





BEESWIFT
ONLINE

Product Code:
GZNDG10BL

Available in Sizes:
S-XXL

Unit of Measure:
Bx 1Th

Available in Colours:

Black
GZNDG10BL

Glovezilla Chemical

Glovezilla Micro Organisms

NITRILE DISPOSABLE GRIPPER GLOVE POWDER FREE

- Sizes S-XL comes in boxes of 100 pieces.
- Size XXL comes in boxes of 90 pieces.

- Powder Free black textured Nitrile Gloves
- CE category III
- Excellent elasticity
- Textured for added grip
- 7 mil


- EN420: 2003 +A1:2009

- EN 388:2016+A1:2018
- Level 0 - Abrasion Resistance
- Level X - Cut resistance (Coupe Test)
- Level 0 - Tear Resistance
- Level 0 - Puncture Resistance
- Level A - TDM Cut Resistance (ISO 13997)

- EN 374-1:2016
- EN 374-4: 2013
- EN 374-5: 2016

Chemical - Breakthrough Time
 n-Heptane(J) - More than 30 Mins (level 2).
 Sodium Hydroxide 40%(K) - More than 480 Mins (level 6).

Additional Chemical Test
 Ammonia 25% - More than 10 Mins (level 1).
 Formaldehyde 37%- More than 480 Mins (level 6).
 Hydrogen Peroxide 30% - More than 480 Mins (level 6).



GLOVEZILLA TITAN ARMOUR NEEDLESTICK GLOVE

FEATURES

- Dependable grip, excellent flexibility and a comfortable ergonomic shape.
- Puncture-resistant with latex coating
- Lined with two layers of Titan Armour
- Makes a great general-purpose work glove
- ASTM F2878 14.4 newtons of puncture protection (hypodermic needle)
- The protective area is on the palm side of the glove only

- EN388: 2016
- Level 2 - Abrasion
- Level X - Cut Resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 4 - Puncture
- Level F - ISO 13997 Cut Resistance

- EN 407: 2004
- Level X - Burning Behaviour
- Level 2 - Contact Heat
- Level X - Convective heat
- Level X - Radiant heat
- Level X - Small splashes of Molten Metal
- Level X - Large splashes of Molten Metal

• Please note: there is no European standard for needle resistance. Current industry practice is to utilize the American Standard ASTM F2878 as a guide, and to allow comparisons between different products. These products are not needle proof. Your own risk assessment therefore needs to be undertaken to decide the suitability of this product.



BEESWIFT
ONLINE

Product Code:
GZ67

Available in Sizes:
S-XL

Unit of Measure:
Pair

Available in Colours:

Blue
GZ67B