Printing date 01/14/2021 Reviewed on 11/09/2016

1 Identification

· Product identifier

· Trade name: Sebastian Trilliant Thermal Protect

· Article number: 90572757

· Application of the substance / the mixture

Hair care products Cosmetic product

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Wella International Operations Switzerland Sarl, Chemin Louis-Hubert 1-3, 1213 Petit-Lancy, Switzerland

· Information department: Wella SDS Info Team

· Emergency telephone number:

CHEMTREC Emergency number: +1-703-527-3887

CHEMTREC US/NA Emergency number(toll free): 800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS02

- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

- U

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture: consisting of the following components.

· Dangerous components:		
64-17-5	ethyl alcohol	>25-≤50%
13475-82-6	Heptane, 2,2,4,6,6-pentamethyl-	>10-≤25%
107-46-0	hexamethyldisiloxane	>2.5-≤10%
56-81-5	glycerol	>2.5-≤10%

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

Protective Action Ci	iteria for Chemicals	(Contd. of page
· PAC-1:		
64-17-5 ethyl alco	hol	1,800 ppn
107-46-0 hexamethy	disiloxane	13 ppm
56-81-5 glycerol		45 mg/m ³
· PAC-2:		
64-17-5 ethyl alco	hol	3300* ppn
107-46-0 hexamethy	disiloxane	140 ppm
56-81-5 glycerol		180 mg/m
PAC-3:		
64-17-5 ethyl alco	hol	15000* ppn
107-46-0 hexamethy	disiloxane	150 ppm
56-81-5 glycerol		1,100 mg/m

7 Handling and storage

- · Handling:
- · **Precautions for safe handling** No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

64-1	7-5 ethyl alcohol
PEL	Long-term value: 1900 mg/m³, 1000 ppm
REL	Long-term value: 1900 mg/m³, 1000 ppm
TLV	Short-term value: 1880 mg/m³, 1000 ppm
56-8	1-5 glycerol
PEL	Long-term value: 15* 5** mg/m³
	mist; *total dust **respirable fraction
TLV	TLV withdrawn-insufficient data human occup. exp.

(Contd. on page 4)

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

(Contd. of page 3)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on	basic physical (and chemical	properties
------------------	------------------	--------------	------------

· General Information

· Appearance:

Form: Fluid

Color: According to product specification

· Odor: Characteristic · Odor threshold: Not determined.

· pH-value at 20 °C (68 °F): 6

· Change in condition

· Decomposition temperature:

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined. 26 °C (78.8 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. 425 °C (797 °F) · Ignition temperature:

Not determined.

(Contd. on page 5)

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

	(Contd. of page
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	15 Vol %
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	e r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	42.6 %
Water:	30.6 %
VOC content:	60.48 %
	604.8 g/l / 5.05 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
64-17-5 et	64-17-5 ethyl alcohol		
Oral	LD50	10470 mg/kg (rat) (bw (OECD 401))	
Inhalative	LC50/4 h	116.9 mg/l (rat) (air (//OECD 403))	

(Contd. on page 6)

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

		(Contd. of page 5)
107-46-0 h	examethy	ldisiloxane
Oral	LD50	>12160 mg/kg (rat) (bw)
Dermal	LD50	>2000 mg/kg (rabbit) (bw (//OECD 402))
Inhalative	LC50/4 h	106 mg/l (rat) (air (OECD 403))
56-81-5 gl	ycerol	
Oral	LD50	23000 mg/kg (rat)
Dermal	LD50	56745 mg/kg (rabbit)
Inhalative	LC50/4 h	4655 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

64-17-5 ethyl alcohol

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

(Contd. of page 6)

- Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number	
DOT, IMDG, IATA	UN1266
UN proper shipping name	
DOT	Perfumery products
IMDG, IATA	PERFUMERY PRODUCTS
Transport hazard class(es)	
DOT	
R AMMONT COLOR	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
Quantity timutions	On cargo aircraft only: 220 L
<i>IMDG</i>	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
1 1 (2)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

(Contd. of page 7)

· UN "Model Regulation":

UN 1266 PERFUMERY PRODUCTS, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethyl alcohol

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

64-17-5 ethyl alcohol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Flammable liquid and vapor.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

(Contd. on page 9)

Printing date 01/14/2021 Reviewed on 11/09/2016

Trade name: Sebastian Trilliant Thermal Protect

(Contd. of page 8)

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eve protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Hr. Dr. Speckbacher
- · Date of preparation / last revision 01/14/2021 / -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3

US