

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

1 Identification

- **Product identifier**
- **Trade name:** Magma Cleartone /00
- **Article number:** 95811032
- **Application of the substance / the mixture** Hair coloring product
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Coty Cosmetics, Inc.
4500 Park Granada
Calabasas, CA 91302
USA
- **Information department:** Coty SDS Info Team
- **Emergency telephone number:**
CHEMTREC Emergency number: +1-703-527-3887
CHEMTREC US/NA Emergency number(toll free): 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS03 Flame over circle

Ox. Sol. 3 H272 May intensify fire; oxidizer.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS03



GHS05



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Silicic acid, sodium salt
dipotassium peroxodisulphate
diammonium peroxodisulphate
Octadecanoic acid, sodium salt (1:1)

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: **Magma Cleartone /00**

(Contd. of page 1)

- **Hazard statements**

May intensify fire; oxidizer.
 Causes skin irritation.
 Causes serious eye damage.
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 May cause an allergic skin reaction.

- **Precautionary statements**

Keep away from heat.
 Keep/Store away from clothing/combustible materials.
 Take any precaution to avoid mixing with combustibles.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 [In case of inadequate ventilation] wear respiratory protection.
 If on skin: Wash with plenty of water.
 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If experiencing respiratory symptoms: Call a poison center/doctor.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3
 Fire = 0
 Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *3
 Fire = 0
 Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1332-58-7	Kaolin	>50-≤100%
7727-21-1	dipotassium peroxodisulphate	>10-<20%
1344-09-8	Silicic acid, sodium salt	≥3-<10%
8012-95-1	Paraffin oils	>2.5-<10%
7727-54-0	diammonium peroxodisulphate	>2.5-<10%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: **Magma Cleartone /00**

822-16-2 Octadecanoic acid, sodium salt (1:1)

(Contd. of page 2)

≥1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7727-21-1	dipotassium peroxodisulphate	0.3 mg/m ³
1344-09-8	Silicic acid, sodium salt	5.9 mg/m ³
7727-54-0	diammonium peroxodisulphate	0.3 mg/m ³
822-16-2	Octadecanoic acid, sodium salt (1:1)	0.17 mg/m ³
139-33-3	Disodium EDTA	11 mg/m ³
7631-86-9	Silica	18 mg/m ³

· PAC-2:

7727-21-1	dipotassium peroxodisulphate	26 mg/m ³
1344-09-8	Silicic acid, sodium salt	65 mg/m ³
7727-54-0	diammonium peroxodisulphate	22 mg/m ³
822-16-2	Octadecanoic acid, sodium salt (1:1)	1.8 mg/m ³
139-33-3	Disodium EDTA	120 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: **Magma Cleartone /00**

(Contd. of page 3)

7631-86-9	Silica	740 mg/m ³
· PAC-3:		
7727-21-1	dipotassium peroxodisulphate	160 mg/m ³
1344-09-8	Silicic acid, sodium salt	390 mg/m ³
7727-54-0	diammonium peroxodisulphate	130 mg/m ³
822-16-2	Octadecanoic acid, sodium salt (1:1)	11 mg/m ³
139-33-3	Disodium EDTA	730 mg/m ³
7631-86-9	Silica	4,500 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Thorough dedusting.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 5.1 B
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m ³ E; as respirable fraction

7727-21-1 dipotassium peroxodisulphate

TLV	Long-term value: 0.1 mg/m ³ as persulfate
-----	---

8012-95-1 Paraffin oils

PEL	Long-term value: 5 mg/m ³
REL	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³ oil mist
TLV	L

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: *Magma Cleartone /00*

(Contd. of page 4)

7727-54-0 diammonium peroxodisulphate

TLV	Long-term value: 0.1 mg/m ³ as persulfate
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Powder

Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value at 20 °C (68 °F):** 9.5

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: *Magma Cleartone /00*

(Contd. of page 5)

· Flash point:	<i>Not applicable.</i>
· Flammability (solid, gaseous):	<i>Not determined.</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>Product does not present an explosion hazard.</i>
· Explosion limits:	
Lower:	<i>Not determined.</i>
Upper:	<i>Not determined.</i>
· Vapor pressure:	<i>Not applicable.</i>
· Density:	<i>Not determined.</i>
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not applicable.</i>
· Evaporation rate	<i>Not applicable.</i>
· Solubility in / Miscibility with Water:	<i>Insoluble.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not applicable.</i>
Kinematic:	<i>Not applicable.</i>
· Solvent content:	
Water:	<i>0.1 %</i>
VOC content:	<i>0.00 %</i>
Solids content:	<i>99.9 %</i>
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7727-21-1 dipotassium peroxodisulphate

Oral	LD50	500 mg/kg (rat)
------	------	-----------------

1344-09-8 Silicic acid, sodium salt

Oral	LD50	3,400 mg/kg (rat) (bw (Similar to OECD 401; standard acute method; ra)
Dermal	LD50	>5,000 mg/kg (rabbit) (bw (Read across data on AgSil TM 25 Potassium sili)
Inhalative	LC50/4 h	>2.06 mg/l (rat) (air (Read across data AgSil TM 25 Potassium silica)

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: **Magma Cleartone /00**

(Contd. of page 6)

8012-95-1 Paraffin oils

Oral LD50 >5,000 mg/kg (rat) (bw)

Dermal LD50 >2,000 mg/kg (rabbit) (bw)

7727-54-0 diammonium peroxodisulphate

Oral LD50 500 mg/kg (rat)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Strong irritant with the danger of severe eye injury.· **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

9003-01-4 Carbomer

3

7631-86-9 Silica

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.**13 Disposal considerations**· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: *Magma Cleartone /00*

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|-----------------|
| · UN-Number | |
| · DOT, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
--

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):
--

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:
--

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
--

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)
--

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: **Magma Cleartone /00**

(Contd. of page 8)

· TLV (Threshold Limit Value established by ACGIH)	
1332-58-7	Kaolin
A4	

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS03

GHS05

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Silicic acid, sodium salt

dipotassium peroxodisulphate

diammonium peroxodisulphate

Octadecanoic acid, sodium salt (1:1)

· Hazard statements

May intensify fire; oxidizer.

Causes skin irritation.

Causes serious eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat.

Keep/Store away from clothing/combustible materials.

Take any precaution to avoid mixing with combustibles.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Abteilung Umweltschutz

· Contact: Hr. Dr. Speckbacher

· Date of preparation / last revision 08/20/2019 / -

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/20/2019

Reviewed on 08/20/2019

Trade name: Magma Cleartone /00

(Contd. of page 9)

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Ox. Sol. 3: Oxidizing solids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1

US