

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

1 Identification

- **Product identifier**
- **Trade name:** Sebastian Craft Clay Texturizer
- **Article number:** 95869244
- **Application of the substance / the mixture** Hair dye
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Coty Cosmetics, Inc.
4500 Park Granada
Calabasas, CA 91302
USA
- **Information department:** Coty SDS Info Team
- **Emergency telephone number:**
CHEMTREC Emergency number: +1-703-527-3887
CHEMTREC US/NA Emergency number(toll free): 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard-determining components of labeling:**
dioctyl maleate
- **Hazard statements**
May cause an allergic skin reaction.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves.
If on skin: Wash with plenty of water.
If skin irritation or rash occurs: Get medical advice/attention.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

2915-53-9	dioctyl maleate	>2.5-≤10%
57-55-6	Propylene glycol	>2.5-≤10%
1332-58-7	Kaolin	>2.5-≤10%
13463-67-7	titanium dioxide	≥0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 2)

· Protective Action Criteria for Chemicals

· PAC-1:		
57-55-6	Propylene glycol	30 mg/m ³
7631-86-9	Silica	18 mg/m ³
13463-67-7	titanium dioxide	30 mg/m ³
1343-98-2	Silicic acid	18 mg/m ³
7439-89-6	iron	3.2 mg/m ³
24800-44-0	Propanol, [(1-methyl-1,2-ethanediyl)bis(oxy)]bis-	1.1 ppm
504-63-2	propane-1,3-diol	7.8 mg/m ³
7647-01-0	hydrogen chloride	1.8 ppm
123-91-1	1,4-dioxane	17 ppm
7439-92-1	lead	0.15 mg/m ³
· PAC-2:		
57-55-6	Propylene glycol	1,300 mg/m ³
7631-86-9	Silica	740 mg/m ³
13463-67-7	titanium dioxide	330 mg/m ³
1343-98-2	Silicic acid	95 mg/m ³
7439-89-6	iron	35 mg/m ³
24800-44-0	Propanol, [(1-methyl-1,2-ethanediyl)bis(oxy)]bis-	13 ppm
504-63-2	propane-1,3-diol	86 mg/m ³
7647-01-0	hydrogen chloride	22 ppm
123-91-1	1,4-dioxane	320 ppm
7439-92-1	lead	120 mg/m ³
· PAC-3:		
57-55-6	Propylene glycol	7,900 mg/m ³
7631-86-9	Silica	4,500 mg/m ³
13463-67-7	titanium dioxide	2,000 mg/m ³
1343-98-2	Silicic acid	570 mg/m ³
7439-89-6	iron	150 mg/m ³
24800-44-0	Propanol, [(1-methyl-1,2-ethanediyl)bis(oxy)]bis-	76 ppm
504-63-2	propane-1,3-diol	520 mg/m ³
7647-01-0	hydrogen chloride	100 ppm
123-91-1	1,4-dioxane	760 ppm
7439-92-1	lead	700 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class:** 11

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

57-55-6 Propylene glycol

WEEL Long-term value: 10 mg/m³

1332-58-7 Kaolin

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fractionREL Long-term value: 10* 5** mg/m³
*total dust **respirable fractionTLV Long-term value: 2* mg/m³
E; as respirable fraction

13463-67-7 titanium dioxide

PEL Long-term value: 15* mg/m³
*total dust

REL See Pocket Guide App. A

TLV Long-term value: 10 mg/m³· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Not required.

-US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
· Form:	Solid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value: Not applicable.	
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Undetermined.
· Flash point: Not applicable.	
· Flammability (solid, gaseous): Not determined.	
· Ignition temperature: 371 °C (699.8 °F)	
· Decomposition temperature: Not determined.	
· Auto igniting: Product is not selfigniting.	
· Danger of explosion: Product does not present an explosion hazard.	
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapor pressure: Not applicable.	
· Density: Not determined.	
· Relative density Not determined.	
· Vapor density Not applicable.	
· Evaporation rate Not applicable.	
· Solubility in / Miscibility with	
· Water:	Insoluble.
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
· Dynamic:	Not applicable.
· Kinematic:	Not applicable.
· Solvent content:	
· Organic solvents:	9.0 %
· Water:	0.0 %
· VOC content:	9.01 %
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 5)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:**

8009-03-8 Petrolatum

Oral	LD50	>5,000 mg/kg (rat) (bw (//OECD 401))
Dermal	LD50	>2,000 mg/kg (rabbit) (bw (//OECD 402))

57-55-6 Propylene glycol

Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)

13463-67-7 titanium dioxide

Oral	LD50	>5,000 mg/kg (rat) (bw (OECD 425))
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>3.43 mg/l (rat) (air (OECD 403))

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** No irritating effect.· **Sensitization:** Sensitization possible through skin contact.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

7631-86-9	Silica	3
13463-67-7	titanium dioxide	2B
7647-01-0	hydrogen chloride	3
123-91-1	1,4-dioxane	2B
7439-92-1	lead	2B

· **NTP (National Toxicology Program)**

123-91-1	1,4-dioxane	R
7439-92-1	lead	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 6)

Danger to drinking water if even extremely small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADN, IMDG, IATA** *not regulated*

· **UN proper shipping name**

· **DOT, ADN, IMDG, IATA** *not regulated*

· **Transport hazard class(es)**

· **DOT, ADN, IMDG, IATA**

· **Class** *not regulated*

· **Packing group**

· **DOT, IMDG, IATA** *not regulated*

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **UN "Model Regulation":**

not regulated

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

7647-01-0	hydrogen chloride
-----------	-------------------

· **Section 313 (Specific toxic chemical listings):**

7647-01-0	hydrogen chloride
-----------	-------------------

123-91-1	1,4-dioxane
----------	-------------

7439-92-1	lead
-----------	------

· **TSCA (Toxic Substances Control Act):**

8009-03-8	Petrolatum				<i>ACTIVE</i>
-----------	------------	--	--	--	---------------

8012-89-3	Beeswax				<i>ACTIVE</i>
-----------	---------	--	--	--	---------------

2915-53-9	dioctyl maleate				<i>ACTIVE</i>
-----------	-----------------	--	--	--	---------------

57-55-6	Propylene glycol				<i>ACTIVE</i>
---------	------------------	--	--	--	---------------

1332-58-7	Kaolin				<i>ACTIVE</i>
-----------	--------	--	--	--	---------------

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 7)

68953-58-2	QUATERNIUM-18 BENTONITE	ACTIVE
7631-86-9	Silica	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
8028-89-5	Caramel (color)	ACTIVE
1343-98-2	Silicic acid	ACTIVE
7439-89-6	iron	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
24800-44-0	Propanol, [(1-methyl-1,2-ethanediyl)bis(oxy)]bis-	ACTIVE
25265-71-8	Dipropylene glycol (isomer unspecified)	ACTIVE
110-98-5	Dipropylene glycol	ACTIVE
4430-18-6	D&C VIOLET No 2 EXT (CI 60730)	ACTIVE
504-63-2	propane-1,3-diol	ACTIVE
1406-18-4	Vitamin E	ACTIVE
7647-01-0	hydrogen chloride	ACTIVE
123-91-1	1,4-dioxane	ACTIVE
7439-92-1	lead	ACTIVE

· **Hazardous Air Pollutants**

7647-01-0	hydrogen chloride
123-91-1	1,4-dioxane
7439-92-1	lead

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
123-91-1	1,4-dioxane
7439-92-1	lead

· **Chemicals known to cause reproductive toxicity for females:**

7439-92-1	lead
-----------	------

· **Chemicals known to cause reproductive toxicity for males:**

7439-92-1	lead
-----------	------

· **Chemicals known to cause developmental toxicity:**

7439-92-1	lead
-----------	------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

123-91-1	1,4-dioxane	L
7439-92-1	lead	B2

· **TLV (Threshold Limit Value established by ACGIH)**

1332-58-7	Kaolin	A4
13463-67-7	titanium dioxide	A4
7647-01-0	hydrogen chloride	A4
123-91-1	1,4-dioxane	A3
7439-92-1	lead	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
123-91-1	1,4-dioxane

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/18/2020

Reviewed on 01/20/2020

Trade name: Sebastian Craft Clay Texturizer

(Contd. of page 8)

· **Hazard pictograms**

GHS07

· **Signal word** Warning· **Hazard-determining components of labeling:***dioctyl maleate*· **Hazard statements***May cause an allergic skin reaction.*· **Precautionary statements***Avoid breathing dust/fume/gas/mist/vapors/spray**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves.**If on skin: Wash with plenty of water.**If skin irritation or rash occurs: Get medical advice/attention.**Specific treatment (see on this label).**Wash contaminated clothing before reuse.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Abteilung Umweltschutz· **Contact:** Hr. Dr. Speckbacher· **Date of preparation / last revision** 02/18/2020 / -· **Abbreviations and acronyms:***IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Skin Sens. 1: Skin sensitisation – Category 1*