

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

## 1 Identification

- **Product identifier**
- **Trade name:** Sebastian Molding Mud
- **Article number:** 96925176
- **Application of the substance / the mixture** Hair styling product
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Coty Cosmetics, Inc.  
4500 Park Granada  
Calabasas, CA 91302  
USA
- **Information department:** Coty SDS Info Team
- **Emergency telephone number:**  
CHEMTREC Emergency number: +1-703-527-3887  
CHEMTREC US/NA Emergency number(toll free): 800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Poly(oxy-1,2-ethanediyl), alpha-(9Z)-9-octadecen-1-yl-omega-hydroxy-, phosphate dioctyl maleate

Polyethylene glycol monooleyl ether

3,3'-Bis (1-hydroxymethyl-2,5-dioximidazolidin-4-yl)-1,1'-methylenediurea

- **Hazard statements**

Causes serious eye damage.

May cause an allergic skin reaction.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

**Trade name: Sebastian Molding Mud**

(Contd. of page 1)

*If skin irritation or rash occurs: Get medical advice/attention.*

*Wash contaminated clothing before reuse.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*3

Fire = 0

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

2915-53-9	dioctyl maleate	>2.5-≤10%
57-55-6	Propylene glycol	>2.5-≤10%
39464-69-2	Poly(oxy-1,2-ethanediyl), alpha-(9Z)-9-octadecen-1-yl-omega-hydroxy-, phosphate	≥3-<10%
9004-98-2	Polyethylene glycol monooleyl ether	≥3-≤10%
39236-46-9	3,3'-Bis (1-hydroxymethyl-2,5-dioximidazolidin-4-yl)-1,1'-methylenediurea	≥0.1-<1%

### 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

*Supply fresh air and to be sure call for a doctor.*

*In case of unconsciousness place patient stably in side position for transportation.*

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

*No further relevant information available.*

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

Trade name: Sebastian Molding Mud

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

57-55-6	Propylene glycol	30 mg/m <sup>3</sup>
124-68-5	Aminomethyl Propanol	17 mg/m <sup>3</sup>
122-99-6	2-Phenoxyethanol	1.5 ppm
25086-89-9	VP/VA Copolymer	1.9 mg/m <sup>3</sup>
25322-68-3	Polyethylene glycol	30 mg/m <sup>3</sup>
139-33-3	Disodium EDTA	11 mg/m <sup>3</sup>
55406-53-6	3-Iodo-2-propynylbutylcarbamate	3.3 mg/m <sup>3</sup>
120-51-4	Benzyl benzoate	5.7 mg/m <sup>3</sup>
91-64-5	Coumarin	0.88 mg/m <sup>3</sup>
100-51-6	Benzyl alcohol	30 ppm
119-36-8	methyl salicylate	2.3 ppm
123-92-2	isopentyl acetate	100 ppm

### · PAC-2:

57-55-6	Propylene glycol	1,300 mg/m <sup>3</sup>
124-68-5	Aminomethyl Propanol	190 mg/m <sup>3</sup>
122-99-6	2-Phenoxyethanol	16 ppm
25086-89-9	VP/VA Copolymer	21 mg/m <sup>3</sup>
25322-68-3	Polyethylene glycol	1,300 mg/m <sup>3</sup>
139-33-3	Disodium EDTA	120 mg/m <sup>3</sup>
55406-53-6	3-Iodo-2-propynylbutylcarbamate	36 mg/m <sup>3</sup>
120-51-4	Benzyl benzoate	63 mg/m <sup>3</sup>
91-64-5	Coumarin	9.7 mg/m <sup>3</sup>
100-51-6	Benzyl alcohol	52 ppm
119-36-8	methyl salicylate	25 ppm
123-92-2	isopentyl acetate	500 ppm

### · PAC-3:

57-55-6	Propylene glycol	7,900 mg/m <sup>3</sup>
124-68-5	Aminomethyl Propanol	570 mg/m <sup>3</sup>
122-99-6	2-Phenoxyethanol	97 ppm
25086-89-9	VP/VA Copolymer	120 mg/m <sup>3</sup>

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

**Trade name: Sebastian Molding Mud**

		(Contd. of page 3)
25322-68-3	Polyethylene glycol	7,700 mg/m <sup>3</sup>
139-33-3	Disodium EDTA	730 mg/m <sup>3</sup>
55406-53-6	3-Iodo-2-propynylbutylcarbamate	220 mg/m <sup>3</sup>
120-51-4	Benzyl benzoate	380 mg/m <sup>3</sup>
91-64-5	Coumarin	58 mg/m <sup>3</sup>
100-51-6	Benzyl alcohol	740 ppm
119-36-8	methyl salicylate	150 ppm
123-92-2	isopentyl acetate	3000* ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 12
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.  
At this time, the other constituents have no known exposure limits.

### 57-55-6 Propylene glycol

WEEL	Long-term value: 10 mg/m <sup>3</sup>
------	---------------------------------------

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

Trade name: Sebastian Molding Mud

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Viscous

Color: Beige

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value at 20 °C (68 °F):** 4.5-6

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure:** Not determined.

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

Trade name: Sebastian Molding Mud

(Contd. of page 5)

· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	8.5 %
<b>Water:</b>	51.0 %
<b>VOC content:</b>	8.50 %
	85.0 g/l / 0.71 lb/gal
· <b>Solids content:</b>	0.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 57-55-6 Propylene glycol

Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)

### 39236-46-9 3,3'-Bis (1-hydroxymethyl-2,5-dioximidazolidin-4-yl)-1,1'-methylenediurea

Oral	LD50	>5,000 mg/kg (rat) (bw)
Dermal	LD50	>8,000 mg/kg (rabbit) (bw)
Inhalative	LC50/4 h	>5.5 mg/l (rat) (air)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

97-53-0	Eugenol	3
91-64-5	Coumarin	3
128-37-0	BHT	3

(Contd. on page 7)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

Trade name: Sebastian Molding Mud

(Contd. of page 6)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 1 (Self-assessment): slightly hazardous for water  
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |                                                                                  |                        |
|----------------------------------------------------------------------------------|------------------------|
| · <b>UN-Number</b>                                                               |                        |
| · <b>DOT, ADN, IMDG, IATA</b>                                                    | <i>not regulated</i>   |
| · <b>UN proper shipping name</b>                                                 |                        |
| · <b>DOT, ADN, IMDG, IATA</b>                                                    | <i>not regulated</i>   |
| · <b>Transport hazard class(es)</b>                                              |                        |
| · <b>DOT, ADN, IMDG, IATA</b>                                                    |                        |
| · <b>Class</b>                                                                   | <i>not regulated</i>   |
| · <b>Packing group</b>                                                           |                        |
| · <b>DOT, IMDG, IATA</b>                                                         | <i>not regulated</i>   |
| · <b>Environmental hazards:</b>                                                  | <i>Not applicable.</i> |
| · <b>Special precautions for user</b>                                            | <i>Not applicable.</i> |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | <i>Not applicable.</i> |

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

Trade name: Sebastian Molding Mud

(Contd. of page 7)

· UN "Model Regulation": not regulated

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

122-99-6 2-Phenoxyethanol

55406-53-6 3-Iodo-2-propynylbutylcarbamate

· TSCA (Toxic Substances Control Act):

2915-53-9 dioctyl maleate

ACTIVE

8001-75-0 Ceresin

ACTIVE

57-55-6 Propylene glycol

ACTIVE

25383-99-7 Octadecanoic acid, 2-(1-carboxyethoxy)-1-methyl-2-oxoethyl ester, sodium salt (1:1)

ACTIVE

39464-69-2 Poly(oxy-1,2-ethanediyl), alpha-(9Z)-9-octadecen-1-yl-omega-hydroxy-, phosphate

ACTIVE

9004-98-2 Polyethylene glycol monooleyl ether

ACTIVE

124-68-5 Aminomethyl Propanol

ACTIVE

122-99-6 2-Phenoxyethanol

ACTIVE

1117-86-8 octane-1,2-diol

ACTIVE

6920-22-5 DL-hexane-1,2-diol

ACTIVE

25086-89-9 VP/VA Copolymer

ACTIVE

24634-61-5 potassium (E,E)-hexa-2,4-dienoate

ACTIVE

39236-46-9 3,3'-Bis (1-hydroxymethyl-2,5-dioxoimidazolidin-4-yl)-1,1'-methylenediurea

ACTIVE

25322-68-3 Polyethylene glycol

ACTIVE

77-92-9 citric acid

ACTIVE

139-33-3 Disodium EDTA

ACTIVE

128446-33-3 alpha-Cyclodextrin, 2-hydroxypropyl ethers

ACTIVE

25265-71-8 Dipropylene glycol (isomer unspecified)

ACTIVE

101-86-0 Hexyl cinnamal

ACTIVE

78-70-6 Linalool

ACTIVE

107-75-5 Hydroxycitronellal

ACTIVE

31906-04-4 Hydroxyisohexyl 3-cyclohexene carboxaldehyde

ACTIVE

55406-53-6 3-Iodo-2-propynylbutylcarbamate

ACTIVE

1406-18-4 Vitamin E

ACTIVE

1934-21-0 CI 19140

ACTIVE

118-58-1 benzyl salicylate

ACTIVE

32388-55-9 Acetyl cedrene

ACTIVE

54982-83-1 Ethylene dodecanedioate

ACTIVE

97-53-0 Eugenol

ACTIVE

3100-36-5 A mixture of cis- and trans-cyclohexadec-8-en-1-one

ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

(Contd. on page 9)

US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

Trade name: Sebastian Molding Mud

(Contd. of page 8)

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

128-37-0 | BHT

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS05    GHS07

· **Signal word** Danger· **Hazard-determining components of labeling:**

Poly(oxy-1,2-ethanediyl), alpha-(9Z)-9-octadecen-1-yl-omega-hydroxy-, phosphate dioctyl maleate

Polyethylene glycol monooleyl ether

3,3'-Bis (1-hydroxymethyl-2,5-dioximidazolidin-4-yl)-1,1'-methylenediurea

· **Hazard statements**

Causes serious eye damage.

May cause an allergic skin reaction.

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Abteilung Umweltschutz

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 12/20/2019

Reviewed on 12/20/2019

**Trade name: Sebastian Molding Mud**

(Contd. of page 9)

· **Contact:** Hr. Dr. Speckbacher

· **Date of preparation / last revision** 12/20/2019 / -

· **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

US