Printing date 01/18/2021

Reviewed on 07/26/2017

# **1** Identification

- · Product identifier
- Trade name: Sebastian Professional Shaper STYLE
- · Article number: 99210003698, 315000014401
- · Application of the substance / the mixture Cosmetic product
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier:
  Wella International Operations Switzerland Sàrl, Chemin Louis-Hubert 1-3, 1213 Petit-Lancy, Switzerland
- · Information department: Wella SDS Info Team
- Emergency telephone number: CHEMTREC Emergency number: +1-703-527-3887 CHEMTREC US/NA Emergency number(toll free): 800-424-9300

# 2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Aerosol 1 H222 Extremely flammable aerosol.

GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



• Signal word Danger

• **Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 2)

US

Printing date 01/18/2021

Reviewed on 07/26/2017

Trade name: Sebastian Professional Shaper STYLE

(Contd. of page 1)

>25-≤50%

>10-≤25%

# 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

#### • Dangerous components:

115-10-6 dimethyl ether

64-17-5 ethyl alcohol

#### 4 First-aid measures

#### · Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## 6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:		
		3,000 ppm
	ethyl alcohol	1,800 ppm
		5500* ppm
124-68-5	Aminomethyl Propanol	17 mg/m³
68439-49-6	Ceteareth-20	3.8 mg/m <sup>3</sup>
	* *	5500* ppm
75-28-5	isobutane	5500* ppm
	(0	Contd. on page 3)

Printing date 01/18/2021

Reviewed on 07/26/2017

# Trade name: Sebastian Professional Shaper STYLE

65-85-0	Benzoic acid	(Contd. of page 13 mg/m <sup>3</sup>
	ammonia, anhydrous	30 ppm
	Limonene	
	Coumarin	15 ppm 0.88 mg/n
	Benzyl benzoate	5.7 mg/m <sup>2</sup>
PAC-2:	·	8
	dimethyl ether	3800* ppm
	ethyl alcohol	3300* ppm
	butane, pure	17000** pp
124-68-5	Aminomethyl Propanol	190 mg/m <sup>3</sup>
68439-49-6	Ceteareth-20	42 mg/m <sup>3</sup>
74-98-6	propane	17000** pp
75-28-5	isobutane	17000** pp
65-85-0	Benzoic acid	140 mg/m <sup>3</sup>
7664-41-7	ammonia, anhydrous	160 ppm
5989-27-5	Limonene	67 ppm
91-64-5	Coumarin	9.7 mg/m <sup>3</sup>
120-51-4	Benzyl benzoate	63 mg/m <sup>3</sup>
PAC-3:		
115-10-6	dimethyl ether	7200* ppm
64-17-5	ethyl alcohol	15000* ppm
	butane, pure	53000***pp
124-68-5	Aminomethyl Propanol	570 mg/m <sup>3</sup>
68439-49-6	Ceteareth-20	250 mg/m <sup>3</sup>
74-98-6	propane	33000*** pp
75-28-5	isobutane	53000*** pp
65-85-0	Benzoic acid	830 mg/m <sup>3</sup>
	ammonia, anhydrous	1,100 ppm
5989-27-5	Limonene	170 ppm
	Coumarin	58 mg/m <sup>3</sup>
120-51-4	Benzyl benzoate	380 mg/m <sup>3</sup>

# 7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:
- Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.
- $\cdot$  Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurized containers.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)

<sup>–</sup> ÚS

Printing date 01/18/2021

Reviewed on 07/26/2017

Trade name: Sebastian Professional Shaper STYLE

• Further information about storage conditions: Keep receptacle tightly sealed.

• Storage class: 2 B

• *Specific end use(s) No further relevant information available.* 

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

#### 115-10-6 dimethyl ether

WEEL Long-term value: 1000 ppm

#### 64-17-5 ethyl alcohol

PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

TLV Short-term value: 1880 mg/m<sup>3</sup>, 1000 ppm

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

· Personal protective equipment:

· General protective and hygienic measures: Wash hands before breaks and at the end of work.

- Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Not required.

Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Aerosol	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	

(Contd. of page 3)

Printing date 01/18/2021

Reviewed on 07/26/2017

Trade name: Sebastian Professional Shaper STYLE

	(Contd. of pag
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	235 °C (455 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Not determined.
Explosion limits: Lower: Upper:	3 Vol % 18.6 Vol %
Vapor pressure at 20 °C (68 °F):	5200 hPa (3900.3 mm Hg)
Density: Relative density Vapor density Evaporation rate	Not determined. Not determined. Not determined. Not applicable.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: Organic solvents: Water: VOC content:	54.7 % 41.0 % 55.00 % 550.0 g/l / 4.59 lb/gal
Solids content:	3.9 %
Other information	No further relevant information available.

# **10** Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

US

Printing date 01/18/2021

Reviewed on 07/26/2017

Trade name: Sebastian Professional Shaper STYLE

(Contd. of page 5)

· Acute toxi	city:	cological effects	
· LD/LC50	values that	t are relevant for classification:	
115-10-6 a	•		
Inhalative	LC50/4 h	308 mg/l (rat)	
64-17-5 et	hyl alcoho	Î.	
Oral	LD50	10470 mg/kg (rat) (bw (OECD 401))	
Inhalative	LC50/4 h	116.9 mg/l (rat) (air (//OECD 403))	
• Additional • Carcinoge	toxicologi nic catego	nsitizing effects known. ical information: ries Agency for Research on Cancer)	
	ethyl alco	, , , , , , , , , , , , , , , , , , ,	
5989-27-5	-		
	Coumarin		
128-37-0		-	
· NTP (Nati	onal Toxic	cology Program)	
None of the	e ingredien	nts is listed.	
· OSHA-Ca	(Occupati	ional Safety & Health Administration)	
None of the	a in anadiar	ata ia liatad	

# **12 Ecological information**

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- $\cdot$  Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 01/18/2021

Reviewed on 07/26/2017

Trade name: Sebastian Professional Shaper STYLE

(Contd. of page 6)

US

# **13 Disposal considerations**

# · Waste treatment methods

## · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1950
UN proper shipping name	
DOT	Aerosols, flammable
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
Transport hazard class(es)	
DOT	
T results for	
Class	2.1
Label	2.1
IMDG, IATA	
Class Label	2.1 2.1
	2.1
Packing group DOT, IMDG, IATA	not regulated
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Gases
Hazard identification number (Kemler code)	
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litt
	Category A. For AEROSOLS with a capacity above 1 lith Category B. For WASTE AEROSOLS: Category C, Clear of livi
	quarters.
Segregation Code	<i>SG69 For AEROSOLS with a maximum capacity of 1 litre:</i>
Segregation coue	Segregation as for class 9. Stow "separated from" class 1 exce
	for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:

US

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/18/2021

Reviewed on 07/26/2017

Trade name: Sebastian Professional Shaper STYLE

	(Contd. of page
	Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(EQ)$	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

Section 355 (extremely hazardous substances):	
7664-41-7 ammonia, anhydrous	
Section 313 (Specific toxic chemical listings):	
7664-41-7 ammonia, anhydrous	
TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
64-17-5 ethyl alcohol	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
65-85-0 Benzoic acid	
TLV (Threshold Limit Value established by ACGIH)	
64-17-5 ethyl alcohol	
128-37-0 BHT	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

Printing date 01/18/2021

Reviewed on 07/26/2017

#### Trade name: Sebastian Professional Shaper STYLE

(Contd. of page 8) • *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

- Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
- **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

- Pressurized container: Do not pierce or burn, even after use.
- Protect from sunlight. Store in a well-ventilated place.
- Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Hr. Dr. Speckbacher
- · Date of preparation / last revision 01/18/2021 / -
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Dependence at of Transportation

- DOT: US Department of Transportation
- IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINECS: European Inventory of Existing Commercial Chemica ELINCS: European List of Notified Chemical Substances
- *ELINCS: European List of Notified Chemical Substances* CAS: Chemical Abstracts Service (division of the American Chemical Soci
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Flam. Aerosol 1: Aerosols Category 1 Press. Gas: Gases under pressure – Compressed gas

US —