



Air Conditioning Ducting

FEATURES:

- Excellent UV stabilization with mold and mildew inhibitors for rigorous outdoor use
- Flame resistant in accordance with UL94VTM-O, California Fire Marshal, and NFPA701 Method 2 specifications

Heavy-Duty Ducting

ENVIRODUCT®
1399-SD



| SPECIFICATIONS | | |
|------------------------|---|--|
| Construction: | Sewn | |
| Weight: | 13 oz./yd. ² (441 g/m ²) | |
| Temperature | -20° to 180° (-29° to 82° C) | |
| Standard Pitch: | Pitch | Diameter |
| | 3" (7.5 cm) 4" (10 cm) | 6" & 7" (150 & 200 mm) 8" (200 mm) & Larger |
| Expanded Pitch | 7" (18 cm) | 12" (300 mm) & Larger |
| Inside Diameter: | 6" - 36" (150 - 900 mm) | |
| Length: | 15', 25' (4.5, 7.5 m) | |
| Color: | Black, Blue, Desert Tan, Kelly Green, Olive Drab, Red, White, Yellow | |
| Wire | Hard-Drawn Steel | |
| Optional Wearstrip: | Heavy-Duty Extruded or Light-Duty PVC Fabric | |
| Optional End Finishes: | Belt Cuff, Soft Cuff, Wire Rope Coupling, Screw Clamp Cuff, Zipper Cuff | |

Standard-Duty Ducting

THERMOHOSE®
1399-SD



| SPECIFICATIONS | | |
|------------------------|---|---|
| Construction: | Heat-Sealed | |
| Weight: | 13 oz./yd. ² (441 g/m ²) | |
| Temperature | -20° to 180° (-29° to 82° C) | |
| Standard Pitch: | Pitch | Diameter |
| | 1" (2.5 cm) 2" (5 cm) 3" (7.5 cm) 4" (10 cm) | 2" & 3" (50 & 100 mm) 4" & 5" (100 & 150 mm) 6" & 7" (150 & 200 mm) 8" (200 mm) & Larger |
| Expanded Pitch: | 6" (15 cm) | 12" (300 mm) & Larger |
| Inside Diameter: | 2" - 30" (50 - 750 mm) | |
| Length: | 25', 50' (7.5, 15 m) | |
| Color: | White, Yellow. Other colors available upon request. | |
| Wire | Hard-Drawn Steel | |
| Optional Wearstrip: | Heavy-Duty Extruded PVC, Standard-Duty Extruded PVC, or Light-Duty PVC Fabric | |
| Optional End Finishes: | Belt Cuff, Soft Cuff, Wire Rope Coupling, Screw Clamp Cuff, Zipper Cuff | |

Blower & Diffuser Tubing

AIRVENT™
1399-SD



| SPECIFICATIONS | |
|------------------------|---|
| Weight: | 13 oz./yd. ² (441 g/m ²) |
| Temperature | -20° to 180° (-29° to 82° C) |
| Inside Diameter: | 8" - 72" (200 - 1,850 mm) |
| Length: | 25', 50', 100' (7.5, 15.5, 30.5 m) Custom lengths available upon request |
| Diffuser Holes | 2" & 3" Diameter (5 & 7.5 cm) |
| Color: | Yellow, White, Black |
| Optional End Finishes: | Belt Cuff, Soft Cuff, Wire Rope Coupling, End Cap |

Light-Duty Ducting

THERMOHOSE®
1095-LD



| SPECIFICATIONS | | |
|------------------------|---|---|
| Construction: | Heat-Sealed | |
| Weight: | 10 oz./yd. ² (339 g/m ²) | |
| Temperature | -20° to 180° (-29° to 82° C) | |
| Standard Pitch: | Pitch | Diameter |
| | 1" (2.5 cm) 2" (5 cm) 3" (7.5 cm) 4" (10 cm) | 2" & 3" (50 & 100 mm) 4" & 5" (100 & 150 mm) 6" & 7" (150 & 200 mm) 8" (200 mm) & Larger |
| Expanded Pitch: | 6" (15 cm) | 12" (300mm) & Larger |
| Inside Diameter: | 2" - 30" (50 - 750 mm) | |
| Length: | 25', 50' (7.5, 15 m) | |
| Color: | White | |
| Wire | Hard-Drawn Steel | |
| Optional Wearstrip: | Standard-Duty Extruded PVC or Light-Duty PVC Fabric | |
| Optional End Finishes: | Belt Cuff, Soft Cuff, Wire Rope Coupling, Screw Clamp Cuff, Zipper Cuff | |

ABC INDUSTRIES, INC.

P.O. Box 77, Warsaw, IN 46581-0077
800.426.0921 Toll-Free
574.267.5166 Phone
574.267.2045 Fax
sales@abc-industries.net
www.abc-industries.net



For custom ducting solutions, contact ABC at (800) 426-0921 to speak with a sales specialist.