



Manufactured by United CoolAir Corporation

Horizontal Portable Products



Cooling Only or Cooling/Heating Available with Optional Dehumidification Mode

Narrow Portable 5 Ton
-5 ton Heat Pump

- • Only 29.5" wide- fits through standard 3.0 doors
- • Available as cooling only, cooling with electric heat, heat pump or heat pump with auxiliary electric heat configuration

Compact MACH145
-12 ton

- • Only 34.5" wide - fits through standard 3.0 doors
- • Available as cooling or cooling with electric heat
- • Integral Fork lifting pod and 8" casters

3-15 Tons Cooling
-Up to 45kW Heating
-Pod Mounted or Casters

- • Low profile design provides easy maneuverability

20-30 Tons Cooling
-Up to 60 kW Heating
-Base, Pod or DOT approved Trailer Mounted

- • Tubular frame construction
- • Low profile design
- • Pod mounted units can be stacked for storage
- • Ideal for temporary cooling or heating in renovation projects, spot cooling or heating, temporary cooling when the building air conditioner is down or when extra cooling or heating is needed to supplement the building system



*All units utilize scroll design compressors.

Unique Solutions for All-Indoor/Outdoor HVAC Projects

Horizontal Portable Air Conditioning Products

	Model Number	Tons	Dimensions (W x H x L)	Approx. Weight	Voltage/Phase	MCA
Cooling/ Heating	PACH3	3	34.00 x 49.50 x 58.625	580	208/1 208/1	37.822.1 22.1
	PACH3N	3	29.50 x 54.50 x 67.00	590	208/3 208/3	38.9 25.3
	PACH5	5	34.00 x 49.50 x 58.625	670	208/1 208/3 460/3	54.4 32.5 16.5
	PACH5N	5	29.50 x 54.50 x 67.00	690	208/1 208/3	55.6 36.6
	PACH10	10	43.00 x 59.00 x 68.00	1105	208/3 460/3	70.1 32.4
	PACH12	12	43.00 x 58.250 x 68.00	1180	208/3 460/3	73.3 29.3
	MACH145 (12T)	12	34.50 x 71.00 x 78.00	1500	208/3 460/3	59.6 30.4
	PACH15	15	46.00 x 64.625 x 86.50	1640	208/3 460/3	102 51.1
	PACH20	20	95.50 x 57.00 x 95.50	2780	208/3 460/3	130.1 52.0
	PACH25	25	95.50 x 57.00 x 95.50	3000	208/3 460/3	162.4 67.5
	PACH30	30	95.50 x 57.00 x 95.50	3220	208/3 460/3	180.8 86.1
Heat Pump	PHP3N	3	29.50 x 54.50 x 67.00	690	208/1 208/3 460/3	40.1 24.2 17.2
	PHP5N	5	29.50 x 54.50 x 67.00	705	208/1 208/3 460/3	55.6 36.6 17.2

Note: PACH10-30 ton units also available mounted on DOT approved trailer assembly.

Standard Features	Options
<ul style="list-style-type: none"> Catalog Unit Capacities: 3, 5, 10, 12, 15, 20, 25 and 30 tons Duct Collars Evaporator Stainless Steel Drain Pan R-410a Refrigerant Terminal Block Power Connection Phase Reversal Indicator Light Durable White Powder Coat Finish Condenser Coil Guard Threaded Condensate Drain Connection Main Circuit Breaker Pleated Filters Mode Switch 	<ul style="list-style-type: none"> Available Voltages: 208/230-1-60 (3 thru 5 ton) 208/230-3-60, 460-3-60, 575-3-60, 415-3-50 Ductable Condenser Discharge Hour Meter Casters, Swivel/Lockable Quarter Turn Access Panel Fasteners Remote Thermostat w/ Cable Trailer Mounted Electric Heat 10kW-60kW Phase Reversal Indicator Duct Collar Covers 4-Way Lifting Pod Camlock Power-In Connectors Customer Supplied Panel Mount Plug

Note: Products can be configured with select features and a wider variety of options than what are listed here. Please contact the factory to discuss special features, paint colors, capabilities and configurations.



Scan to learn more about all of our products!



Manufactured by United CoolAir Corporation

491 East Princess Street, York, PA 17403 Phone: 717-843-4311 Fax: 717-854-4462
email: uca@unitedcoolair.com web: www.unitedcoolair.com/Portable



Copyright © by United CoolAir Corporation 2019. All rights reserved. Manufacturer reserves the right to make changes without notice.

