

# 1000-SK-I

# LOW TEMPERATURE SMOKER OVEN



• HALO HEAT . . . a controlled, uniform heat source that maintains close temperature tolerances throughout the cooking and holding function. Offers uniform and consistent cooking on a daily basis, low shrinkage of bulk or portion-cut protein items, higher food moisture content, and significantly longer holding life.

- Smokes with real wood chips no pressure cooking, no artificial smoke flavor.
- Smoke timer offers a choice of mild, medium, or heavy smoke flavor.
- Cooks, smokes, and holds meats, poultry, and fish.
- Cold smokes fish and cheese.
- Induces natural enzyme action in meat for tenderizing.
- Less energy usage than conventional ovens.
- Reduces labor and evens-out work loads.
- Non-magnetic stainless steel interior, racks, and shelves resist corrosion.
- Simple control senses temperature drops faster, providing quick heat recovery time.

Two (2) individually controlled oven compartments are enclosed in one 20 gauge stainless steel exterior. Each door is furnished with a magnetic door latch. Each compartment is equipped with two (2) stainless steel side racks with eight (8) pan positions spaced on 2-5/16" (59mm) centers, two (2) stainless steel wire shelves, one (1) stainless steel Rib Rack, a removable stainless steel drip pan with drain and a wood chip container. Oven is furnished with an exterior, front mounted stainless steel drip tray and one (1) sample bag each of cherry, hickory, apple & maple wood chips. Oven includes one (1) set of 5" (127mm) casters — 2 rigid, and 2 swivel with brake.

Each compartment is controlled by one (1) Simple control with an ON/OFF power switch; cook temperature knob, 200° to 325°F (94° to 160°C); hold temperature knob, 60° to 205°F (16° to 96°C); digital display, UP/DOWN arrows to set cook and hold time; and a sixty minute smoking timer. Control features indicator lights for the cook, hold, and smoke functions, and when the oven is calling for heat. Oven is equipped with a voltage conversion switch, located on the back of the oven, for voltage selection (208 or 240 V.A.C.) at time of installation.

☐ MODEL 1000-SK-I: Double compartment low temperature smoker oven with Simple control.

### FACTORY INSTALLED OPTIONS

- Door Choices:
- ☐ Solid Door, standard ☐ Window Door, optional
- Door Swing Choices: ☐ Right-hand swing, standard ☐ Left-hand swing, optional



- Voltage Choices: □ 208-240
  - □ 230




- Exterior Panel Color Choices: ☐ Stainless steel, standard
- ☐ Burgundy, optional
- ☐ Custom color, optional
- Cooking thermostat limit set at 250°F for restricted areas of the U.S.A.  $\square$  Specify on order as required.

### ADDITIONAL FEATURES

☐ Rib Rack Shelf • Item SH-29474

Special non-magnetic stainless steel wire shelf designed to hold ribs or fish in an upright position for more even smoking. Each shelf will hold thirteen full ribs. One (1) Rib Rack Shelf is furnished with each compartment. Additional racks are available as an option. Capacity: Three (3) Rib Rack Shelves per compartment.





On all Cook & Hold heating elements (EXCLUDES LABOR).




W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY


DUE TO ONGOING PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



# 1000-SK-I

# LOW TEMPERATURE SMOKER OVEN





ELECTRICAL						
VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW	CORD & PLUG	
208	1	60	31.4	6.5	NO CORD	
240	1	60	24.3	5.8	OR PLUG	
230	1	50/60	24.1	5.5	NO CORD	
					OR PLUG	

75-5/8" x 23-15/16" x 32-1/4"


(1920mm x 608mm x 819mm)

26-7/8" x 18-7/8" x 26-1/2" (683mm x 479mm x 673mm)

**DIMENSIONS:** H x W x D

**INTERIOR:** (EACH COMPARTMENT)

**EXTERIOR**:



*74-1/4" (1885mm) - with optional 3-1/2" (89mm) c	asters
*75-1/2" (1917mm) - with optional 6" (152mm) legs	

PRODUCT\PAN CAPACITY PER COMPARTMENT						
	120 lbs (54kg) maximum					
volume maximum: 60 quarts (76 liters)						
	FULL-SIZE PANS:	GASTRONORM 1/1:				
Three (3)	20" x 12" x 2-1/2"	530mm x 325mm x 65mm				
ON OPTIONAL WIRE SHELVES ONLY						
	FULL-SIZE SHEET PANS	):				
Seven (7)	18" x 26" x 1"					

CLEARANCE REQUIREMENTS			INSTALLATION REQUIREMENTS	
BACK	BACK 3" (76mm)		<ul> <li>Oven must be installed level.</li> <li>The oven must not be installed in any area where it may be affected by steam, grease, dripping water, extreme</li> </ul>	
TOP	2" (51mm)			
EACH SIDE	1" (25mm)			
WEIGHT			temperatures, or any other severely adverse conditions.  — Appliances with casters and no cord or plug must	
NET: 377 lb (171 kg)		<b>SHIP:</b> 445 lb (202 kg) EST.	be secured to the building structure with a flexible	
CRATE DIMENSION	IS: (LXWXH)		connector. NOT FACTORY SUPPLIED.	
35" x 35" x 82" (889mm x 889mm x 2083mm)			— Smoker ventilation requirements to be determined by	

OPTIONS & ACCESSORIES			
☐ Bumper, Full Perimeter 5009		☐ Pan Grid, Wire — 18" x 26" PAN INSERT	PN-2115
☐ Carving Holder, Prime Rib	HL-2635	☐ Security Panel w / Key Lock	5013935
☐ Carving Holder, Steamship (Cafeteria) Round 4459		☐ Shelf, Stainless Steel, Flat Wire	SH-2325
Casters, Stem - 2 RIGID, 2 SWIVEL W/BRAKE		☐ Shelf, Stainless Steel, Rib Rack	SH-29474
□ 3-1/2" (89mm)	5008017	Wood Chips bulk pack - 20 lb (9 kg)	011 2717 1
☐ Door Lock with Key - EACH HANDLE	LK-22567	=	****C 00=40
☐ Drip Pan with Drain, 1-7/8" (48mm deep)	5005616	☐ Apple	WC-22543
☐ Drip Pan without Drain 1-7/8" (48mm deep)		☐ Cherry	WC-22541
☐ Drip Pan without Drain 4" (101mm deep)	15929	☐ Hickory	WC-2829
☐ Legs, 6" (152mm), Flanged (SET OF FOUR)	5011149	□ Maple	WC-22545



#49 - 08/15

W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY