

**The popular C-Phone 2 diver communications system is now available in panel-mount format**

Totally up to date modern electronics have been carefully selected and tested to give the clarity you would expect from modern surface communications equipment - even with standard microphones and earphones found on most dive sites. Clear and crisp, even the untuned ear can now understand what it being said. The C-Phone 2P is perfectly suited for installation in fixed dive control stations and even portable gas control panels.

- Separate diver inputs: two-pin 4mm terminal posts
- Hand-held PTT microphone as standard
- Mains trickle charge to heavy duty battery
- 12v external battery input for back-up
- Recording output
- External speaker output
- Waterproof speaker with high quality sound
- Diver selection switch
- Speaker or headset for tender operator (optional)
- Output for recording device or external speaker

**Dimensions**

238 Wide x 188 High x 170 Deep (mm)

**Weight**

3kg

**Mounting**

10x M4 x 10mm screws

**Power Supply**

Internal 12V SLA battery and 96 -230V  
Mains AC 50-60Hz external 12V battery capability  
Battery Life - Up to 30 hours  
Battery Charge Time - 6-8 hours

**Standby Current**

58mA

**Nominal Frequency Response**

400Hz to 10KHz

**Audio Power Output**

7.8W into 8ohm



**Ordering Information**

Description	Order Code
C-Phone 2 Panel Mount Radio with PTT Microphone	CP2P