





- 1. Face to face dimension meets the customer's requirement;

- 2.Testing conforms to FM;3.Working pressure:175 PSI;4.The groove connection conforms to AWWAC606;

ć		
П		
	$\bigwedge$	
11	(=0)	
4	Ų	Ъ
<b>©</b>		<u> </u>

DN	L	0	С	Α	В	H1	H2	L1
50	114	60.3	57.15	16	8	50	50	66.5
65	114	73	69.1	16	8	55.5	55.5	66.5

9	Electric Signal Gear Box	
8	Key	1045
7	Circlip	65Mn
6	Gasket	SS304
5	O-Ring	EPDM
4	Lower Shaft	SS630
3	Disc	65-45-12+EPDM
2	Upper Shaft	SS630
1	Body	ASTM B62 C83600
Item	Name	Material

Manufacture/Supplier:	SHOP DRAWING					FIG NO. GB-3100				
						DRAWN	Date		TITLE: Fire Butterfly Valve	
SENTRY SPRINKLERS						Checked	Date		(Groove Connection)	
						Approved	Date		2"-2.5" (DN50-DN65)	
						Projection	ALL DIM'S IN: mm		DRAWING NO.:	
	REV.	BY	APP.	Description	Date			NOT SCALE M DRAWING		