



# SUBMERSIBLE CABLE

## FLAT JACKETED HEAVY DUTY WITH GROUND

Premium 600V cable, Rated 75°C, Black, Yellow, Red conductors; w/Green ground. Stranded Copper Conductors. Moisture Resistant PVC Insulation, Flat Parallel Configuration, Black PVC Jacket.

ITEM NO.	SIZE	STRANDS	WEIGHT	STANDARD REEL LENGTH
14/2G10	14-2	7 STR W/GRD	113	1000'   500'
12/2G10	12-2	19 STR W/GRD	151	1000'   500'
10/2G10	10-2	19 STR W/GRD	203	1000'   500'
8/2G10	8-2	19 STR W/GRD	282	1000'   500'
14/3G10	14-3	7 STRW/GRD	152	1000'   500'
12/3G10	12-3	19 STR W/GRD	200	1000'   500'
10/3G10	10-3	19 STR W/GRD	268	1000'   500'
8/3G10	8-3	19 STR W/GRD	384	1000'   500'
6/3G10	6-3	19 STR W/GRD	532	1000'   500'
4/3G10	4-3	19 STR W/GRD	733	1000'   500'
2/3G10	2-3	19 STR W/GRD	1048	1000'   500'
1/0G	1/0-3	19 STR W/GRD	1661	SPECIAL CUTS AVAIL
2/0G	2/0-3	19 STR W/GRD	1904	SPECIAL CUTS AVAIL
3/0G	3/0-3	19 STR W/GRD	2493	SPECIAL CUTS AVAIL
4/0G	4/0-3	19 STR W/GRD	2984	SPECIAL CUTS AVAIL
250MCM	250-3	37 STR W/GRD	3387	SPECIAL CUTS AVAIL
350MCM	350-3	37 STR W/GRD	4592	SPECIAL CUTS AVAIL
500MCM	500-3	37 STR W/GRD	6207	SPECIAL CUTS AVAIL



## TWISTED WITH GROUND

Premium 600V cable, Rated 75°C, Twisted Black, Yellow, Red conductors; w/Green ground. Stranded Copper Conductors. Moisture Resistant Plastic Insulation, Twisted Configuration.

ITEM NO.	SIZE	STRANDS	WEIGHT	STANDARD REEL LENGTH
14/2T10	14-2	SOLID W/GRD	65	1000'   500'
12/2T10	12-2	SOLID W/GRD	91	1000'   500'
10/2T10	10-2	SOLID W/GRD	132	1000'   500'
8/2T10	8-2	SOLID W/GRD	195	1000'   500'
14/3T10	14-3	SOLID W/GRD	86	1000'   500'
12/3T10	12-3	SOLID W/GRD	122	1000'   500'
10/3T10	10-3	SOLID W/GRD	176	1000'   500'
8/3T10	8-3	19 STR W/GRD	270	1000'   500'
6/3T10	6-3	19 STR W/GRD	402	1000'   500'
4/3T10	4-3	19 STR W/GRD	564	1000'   500'
2/3T10	2-3	19 STR W/GRD	861	1000'   500'



Due to the rapid changes in copper prices, prices may vary from sale to sale. Call your local branch to confirm price and availability by calling 1-866-E-WATER1 (866-392-8371)