HIGH PERFORMANCE MONOCRYSTALLINE PERC MODULE

RSM120-6-315M/5BB 120

CELL MONOCRYSTALLINE MODULE

315Wp power output range

1500VDC MAXIMUM SYSTEM VOLTAGE

18.9% MAXIMUM EFFICIENCY





About Risen Energy

Risen Energy is a leading, global tier 1 manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation. The company, founded in 1986, and publicly listed in 2010, compels value generation for its chosen global customers. Techno-commercial innovation, underpinned by consummate quality and support, encircle Risen Energy's total Solar PV business solutions which are among the most powerful and cost-effective in the industry. With local market presence and strong financial bankability status, we are committed, and able, to building strategic, mutually beneficial collaborations with our partners, as together we capitalise on the rising value of green energy.

KEY SALIENT FEATURES



Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing



Photon independent field testing - Ranked in the top 2 of 176 international suppliers



Industry leading lowest thermal co-efficient of power



Industry leading 15 years product warranty



Excellent low irradiance performance



Excellent PID resistance



Positive tight power tolerance of 3%



Dual stage 100% EL Inspection warranting defect-free product



Module Imp binning radically reduces string mismatch losses



Warranted reliability and stringent quality assurances well beyond certified requirements



Certified to withstand severe environmental conditions

- Anti-reflective & anti-soiling surface minimise power loss from dirt and dust
- Severe salt mist, ammonia & blown sand resistance, for seaside, farm and desert environments
- Excellent mechanical load 2400Pa & snow load 5400Pa resistance





























RISEN ENERGY CO., LTD.

Tashan Industry Zone ,Meilin, Ninghai 315609,Ningbo PRC Tel: +86-574-59953239

Fax: +86-574-59953599 E-mail: info@risenenergy.com Website: www.risenenergy.com



















Solar Imperium 1300 99 77 72

Dimension of PV Modules Unit: mm











REM120-5BB-EN-BVC-H1.2018

ELECTRICAL DATA (STC)	
Model Number	RSM120-6-315M
Rated Power in Watts-Pmax(Wp)	315
Open Circuit Voltage-Voc(V)	40.9
Short Circuit Current-Isc(A)	9.96
Maximum Power Voltage-Vmpp(V)	33.6
Maximum Power Current-Impp(A)	9.38
Module Efficiency (%)	18.9

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

ELECTRICAL DATA (NOCT)	
Model Number	RSM120-6-315M
Maximum Power-Pmax (Wp)	234.7
Open Circuit Voltage-Voc (V)	38.1
Short Circuit Current-Isc (A)	8.10
Maximum Power Voltage-Vmpp (V)	31.2
Maximum Power Current-Impp (A)	7.52

NOCT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA		
Solar cells	Monocrystalline 156.75×78.375mm	
Cell configuration	120 cells (6×10+6×10)	
Module dimensions	1685×992×35mm	
Weight	19kg	
Superstrate	3.2 mm, High Transmission, Low Iron, Tempered ARC Glass	
Substrate	White Backsheet	
Frame	Silver Anodized Aluminium Alloy type 6063T5, Silver Color	
J-Box	Potted, IP67, 1500VDC, 3 Schottky bypass diodes	
Cables	4.0mm² (12AWG), Positive(+)270mm, Negative(-)100mm	
Connector	IP67 MC4 Compatible	

TEMPERATURE & MAXIMUM RATINGS		
Nominal Operating Cell Temperature (NOCT)	45°C±2°C	
Temperature Coefficient of Voc	-0.29%/°C	
Temperature Coefficient of Isc	0.05%/°C	
Temperature Coefficient of Pmax	-0.39%/°C	
Operational Temperature	-40~+85°C	
Maximum System Voltage	1500VDC	
Max Series Fuse Rating	15A	
Limiting Reverse Current	15A	

PACKAGING CONFIGURATION				
	40ft	20ft		
Number of modules per container	780	360		
Number of modules per pallet	30	30		
Number of pallets per container	26	12		
Packaging box dimensions (LxWxH) in mm	1715×1120×1130	1715×1120×1130		
Box gross weight[kg]	615	615		

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

©2018 Risen Energy. All rights reserved. Specifications included in this datasheet are subject to change without notice.