

MOLD RELEASE

Asphalt and Concrete Mold Release Agent



An heavy duty blend of surfactants and emulsifiers to be used as a mould release agent for asphalt, concrete and other adhesive products.

DIRECTIONS FOR USE

Can be diluted with up to 30 parts water to 1 part chemical. Apply with a trigger spray applicator or brush directly to mould, tank or truck body. Mould surfaces must be clean of solvents or other coatings. Can be used undiluted for extreme applications. Rinse with high pressure water to remove residue



Pre-spray Asphalt or Concrete Carrier Vehicles. Promotes easy off-loading.

Pre-spray forms for quick and effective forms removal.

CAUTION: Eye and skin irritant.

PRECAUTIONS: Avoid eye or skin contact. Do not take internally. Wear suitable protective clothing.

FIRST AID: For Inhalation use proper respiratory protection to remove victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Seek prompt medical attention. For eye contact flush thoroughly with water holding eyelids open. For skin contact wash with warm water and soap. Launder clothes before reuse. If Ingested do NOT induce vomiting. Keep at rest. Get prompt medical attention.

Canada Cleaning Systems

15 Simpson Rd. Unit 1
Bolton, Ont. L7E 1E4

Phone: 905-857-7676 / Fax: 905-857-7680
canadacleaningsystems.com

A Canadian Company

