

## 1 INTO 2

Equipment provided: Two 50' sections of 2 1/2" hose, two 50' sections of 1 1/2" hose. All hose to be doubled jacketed. One 2 1/2" solid bore nozzle. Two 1 1/2" solid bore nozzles and on 2 1/2" to 1 1/2" gated wye. One Herbert screw type hose clamp. Water to be supplied from a discharge at 100 P.S.I. All hoses, nozzles and gated wye shall have gaskets in place.

Personal equipment: Helmet and boots shall be supplied by each team. Bunker Coats are optional.

All equipment to be supplied and in place in the equipment area prior to the start of the event. Five team members will position themselves at the start line located 25' from the equipment area. They are to be dressed in their gear prior to the start of the event. When the last signal is given, by the judge, they will proceed to the equipment area, remove and connect the two sections of 2 1/2" hose and the 2 1/2" nozzles. Connect it to the water supply, open the discharge and hit the center target. When the target is hit, the hose clamp is properly applied to the first section of 2 1/2" hose. The hose clamp is then **UNSCREWED** and the two outside targets are hit. Time is taken when both targets have been hit. Water from the left nozzle must knock down the left target and water from the right nozzle must knock down the right target. Hoses, nozzles and gated wye shall not be preconnected prior to the start of the event. All four lengths of hose are to be rolled with the male coupling on the inside of the roll. Once the 2 1/2" discharge has been opened at the start of the event it is not to be touched again during the event or the team will be disqualified. Upon the completion of the event do not disconnect or touch any equipment until told to do so by the judge. If a coupling becomes disconnected and deemed unsafe by the judges, the team will be disqualified. The clamp may be closed and opened if there are no safety violations.

