


An adjustable arm board allows for the installation of tonearms of 9 to 12 inches.



47 mm tick translucent acrylic platter supporting 12 stainless steel weights mounted on the periphery for a total mass of 5.9 kg ensures maximum rotational stability.



Optimum platter drive is provided by a powerful 7.5 Watts AC synchronous motor coupled to a dual step pulley (33.3 / 45 RPM).

STABLE 33.2 Mk2


After years of hard work and development, we are pleased to present our brand new analog turntable:

THE STABLE 33.2 Mk2

This turntable is inspired by our state-of-the-art high-end model STABLE 33.1.

By staying true to our values, we achieved the little miracle of creating a high-quality analog turntable. The STABLE 33.2 Mk2 is an extremely musical turntable.


Your STABLE 33.2 Mk2 turntable, tonearm and cartridge not included, will be offered with the Reed™ tonearm of your choice, but the STABLE 33.2 Mk2 can accommodate most tonearms currently available on the market by simply replacing the tonearm mounting base.



Arm board assembled in three layers of different thicknesses and densities for an inert result.



Oversized bearing axis shaft ($\varnothing \frac{1}{8}''$) with extra-long engagement (3'') for regular and constant lubrication of the mechanism.



Decoupling and adhesion provided by three polyurethane domes paired with a spring suspension wrapped in natural fibers to convert energy into heat and control movement.

Technical Specifications

WEIGHT:

Turntable: 36 lbs / 16.3 Kg

Platter: (47mm clear acrylic) 13 lbs / 5.9 Kg
(50mm black Delrin™) 14.8 lbs / 6.7 Kg

Motor: 10,8 lbs / 4,9 Kg

Total: 60 lbs / 27 Kg

MOTOR:

110 volts, 60 Hz, 300 RPM

DIMENSIONS:

Footprint: (D / W) 17" X 19"

OVERALL: (D / W / H) 17" X 22" X 10"

