

SKU	Dia	ORIENTATION	Type Dopant	RESISTIVITY Ω-CM	THICKNESS	BACKSIDE FINISH	SEMI STD FLAT
QS02NA01	2"	<100>	N/As	<0.005	279±25μm	SSP	1
QS02NP02	2"	<100>	N/Ph	1-10	279±25μm	SSP	1
QS02PB03	2"	<100>	P/B	1-10	279±25μm	SSP	1
QS02PB04	2"	<100>	P/B	10-20	279±25μm	SSP	1
QS03NA01	3"	<100>	N/As	<0.005	381±25μm	SSP	2
QS03NP02	3"	<100>	N/Ph	1-10	381±25μm	SSP	2
QS03NP03	3"	<100>	N/Ph	10-20	381±25μm	SSP	2
QS03PB04	3"	<100>	P/B	<0.005	381±25μm	SSP	2
QS03PB05	3"	<100>	P/B	1-10	381±25μm	SSP	2
QS03PB06	3"	<100>	P/B	10-20	381±25μm	SSP	2
QS04NA01	100mm	<100>	N/As	<0.005	525±20μm	SSP	2
QS04PH02	100mm	<100>	N/Ph	1-5	525±20μm	SSP	2
QS04NP03	100mm	<100>	N/Ph	5-10	525±25μm	SSP	2
QS04NP04	100mm	<100>	N/Ph	10-20	525±25μm	SSP	2
QS04PB05	100mm	<100>	P/B	<0.005	525±25μm	SSP	2
QS04PB06	100mm	<100>	P/B	<0.01-0.02	525±25μm	SSP	2
QS04PB07	100mm	<100>	P/B	1-5	525±25μm	SSP	2
QS04PB08	100mm	<100>	P/B	5-10	525±25μm	SSP	2
QS04PB09	100mm	<100>	P/B	10-20	525±25μm	SSP	2
QS04NP10	100mm	<100>	N/Ph	5-10	525±25μm	DSP	2
QS04PB11	100mm	<100>	P/B	5-10	525±25μm	SSP	2
QS06PB01	150mm	<100>	P/B	1-10	675±25μm	SSP	1
QS06PB02	150mm	<100>	P/B	5-10	675±25μm	SSP	1
QS06PB03	150mm	<100>	P/B	10-20	675±25μm	SSP	1
QS06PB04	150mm	<100>	P/B	1-30	675±25μm	SSP	1
SPECIFICATION: PRIME WAFER, BOW/WARP <40μm, TTV <10μm, <10@0.3μm							
FACTORY SEALED CASSETTES WITH QTY - 25							