

FIG. 1




FIG. 2




FIG. 3

20




FIG. 4




FIG. 5




FIG. 6

1

DEVICE FOR NEURO-PHYSIOLOGIC STIMULATION

REFERENCE TO RELATED APPLICATION

This is a continuation in Parts of U.S. Pat. No. 8,457,754, entitled Method, System and Apparatus for Control of Pancreatic Beta Cell Function to Improve Glucose Homeostasis and Insulin Production, filed Oct. 30, 2012, and the same is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

With the exception of TENS machines, there exist very few bioelectrical systems that apply an electrical waveform, or a sequence thereof, to the human body. Yet less common are bioelectric systems that apply electrical waveforms to the human neurologic system. Some such systems are implanted into the human body, such as heart pacemakers.

U.S. Pat. No. 8,078,281 to Priori teaches a system of monitoring brain waves and providing a feedback for bio-stimulation of the brain.

U.S. Pat. No. 4,165,750 to Aleev teaches a system of electrical stimulation of muscles.

Electro-stimulation is sometimes used in diagnostic devices as in U.S. Pat. No. 5,823,190 to Voipio which is used in certain examinations of the human eye.

The present invention relates to a special-purpose applicator of electrical waveforms to directly nerves of the parasympathetic nervous system.

SUMMARY OF THE INVENTION

A apparatus for the electro-physiologic stimulation of the human nervous system, comprising a positive electrical assembly having (i) an integrated circuit (IC) producing a sequence of physiologically compatible and acceptable electromagnetic waveforms, the IC having ungrounded positive and negative outputs of the waveforms; (ii) a battery substantially conformal in geometry and in electrical communication with said IC board; (iii) a positive electrode pad in electrical communication with said positive output of said waveforms; (iv) a lower housing in which said IC battery and positive electrode pad are secured; and (v) an upper housing in circumferential press-swivel contact with an outer periphery of said lower housing in which 360 degrees of rotation of said upper housing relative to said lower housing is enabled. The apparatus also includes a flexible housing for said electrical cable. And further includes negative electrical assembly comprising: (i) a conductive plate in electrical communication with an opposite end of said cable, carrying said negative side of said waveforms; (ii) a negative electrode pad in electrical communication with said conductive plate; (iii) a lower housing secured about said conductive plate; and (iv) an upper housing at least partially circumferentially secured about said lower housing, in pressure-swivel relation thereto, said opposite cable end secured between said plate and said upper housing.

It is an object of the invention to provide an apparatus for the application of electro-neurologic waveforms to the anatomy of a patient.

It is a further object to provide an applicator for electro-neurologic waveforms to areas related to the vagus and celiac schema of the sympathetic nervous system.

It is another object to provide an apparatus useful in innervating neural pathways associated with the pancreas and the activity of its beta cells.

2

The above and yet other objects of the invention will become apparent from the hereinafter set forth Brief Description of the Drawings, Detailed Description of the invention and Claims appended herewith.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the present apparatus.

FIG. 2 is a cross-section view of the positive electrode assembly taken along Line 2-2 of FIG. 1.

FIG. 3 is an exploded view showing the parts of the positive electrode assembly.

FIG. 4 is an exploded view showing the parts of the negative electrode assembly.

FIG. 5 is a side elevational view of the inventive apparatus.

FIG. 6 is a neurological schema of the back showing areas of application of electrodes of the present apparatus.

DETAILED DESCRIPTION OF THE INVENTION

With reference to FIG. 1 there is shown, in perspective view, the instant device for application of a neurophysiologic electrical waveforms to the human body. A positive electrode assembly 20 and negative electrode assembly 22, connected by a flexible elongate cable housing 50 are shown in a generally top perspective view.

A cross-sectional view, taken through the middle of positive electrode assembly, through Line 2-2 of FIG. 1 is shown in FIG. 2. Therein may be seen the general top of outer housing 26 of the structure, which centrally disposed therein is on-off switch 46 which also rotates to control potentiometer 29 which controls the voltage amplitude of the waveform applied through the electrodes. Said housing 26 includes vents 28 and employs generally circular sidewalls 31. Potentiometer 29 is offset from integrated circuit ("IC") board 32 through the use of a conductive bracket 34 which electrically communicates with the positive side of the waveform output of circuit (IC) board 32 and stabilizes it relative to battery 36 (which may be a 3 VDC lithium battery) and a flexible bio-compatible surface 38, such as a gel, by which metallic electrode 40 comes into contact with the skin of the patient to be treated. IC board 32 is more fully described in parent application Ser. No. 13/663,658, now U.S. Pat. No. 8,457,745, at Cols. 15-17, and FIGS. 13-15 thereof, which has been incorporated hereinto by reference. Further shown in FIG. 2 is a flexible cable 24 (within housing 50) which is in electrical communication with the negative side of the waveform produced by the IC board 32.

FIG. 3 is an exploded view of FIG. 2 in which, however, cable 24 is shown to the left. As may be noted, the top surface of housing 26 and the electrode 40 at the bottom of each electrode assembly 20 is held together by the metallic electrode 40 and a screw 44 fitting into a knob 45 which communicates with control switch 46. See FIG. 2. Also shown in FIG. 3 are appropriate screws 48 provided to secure the IC board and battery, above-described, and fit within sidewalls 31 of a lower area 33 of the assembly 20, and to secure cable 24 to the IC board 32. Also shown in FIG. 3 is biocompatible surface 38.

It is noted that threads 31A of sidewalls 31 are slidably inserted and press-swivel rotatable upon threaded surface 30A of upper sidewalls 30 of positive electrode assembly 20.

In FIG. 4 is shown an exploded view of negative assembly 22 in which may also be seen cable 24 within cable housing 50. An end 63 of cable 24 is held by axial element 52 and by the walls of assembly 22. Negative electrode assembly 22, like the positive assembly 20, is provided with a metallic

electrode **42** and also a layer of electrically conductive gel **38A**, above which is provided a plastic plate **54**, conformal in geometry to the interior of top region **56** of the negative assembly **22** and sidewalls **58** thereof. Also shown in FIG. **4** are air vents **57**. It is also noted that plate **54** provides an insulation between gel **38A** and current that passes through wire **24** from the IC board and through axial element **52** to negative electrode **42**.

Further provided are protectors **60** and **62** for the exposed segment of cable **24** and, also, to ensure the stability of the cable within entry port **64/64.1**, the lower part of which projects from sidewalls **66** and the upper second part of which depends from sidewalls **58** of the negative assembly **22**. It is noted that the interface between essentially circular sidewall **58** of the top region **56** and lower sidewalls **66** is such that a limited degree of pressure-swivel polar rotation of the top region relative to the bottom part of assembly **22** can be accomplished. That is, the top relative to the top and sidewalls **56/58** of the negative electrode are able to rotate to a limited extent relative to each other.

It is noted that the same, but to a greater extent, is the case (see FIG. **3**) in the relationship of the sidewall of wall **30** of the positive electrode assembly which enables its circular relation to sidewalls **31**. As such, negative assembly **22** (see FIG. **1**) is able to rotate fully about positive assembly **20**, and positive assembly itself is partially rotatable on its own axis. This, as will be seen below, is necessary for the clinical use of the present apparatus.

FIG. **5** is an assembly side view of the entire apparatus above-described.

It should be noted in FIG. **1** that cable **24** is provided with air vents **25** in order to minimize the accumulation of heat within the housing **50** thereof. This is shown in greater detail in FIG. **3**.

In FIG. **6** are shown locations at which the electromagnetic physiologic waveform applicator is applied to the human body. Therein, each of the locations indicated at A, A1 and A2 represent locations of positive assembly **20**, while the locations indicated by the letters D thru A, F, G, H and I are all locations at which the negative assembly **22** are placed, all in the manner set forth in our parent application Ser. No. 13/663, 658, referenced above. Actual contact with the skin occurs via gel through anode electrode **40** and cathode electrode **42**. As in noted in said parent application, one-half of the treatment by the respective anodes and cathodes occurs in the manner shown in FIG. **6**, whereas in a second phase thereof, the locations of the anode are respectively reversed such that anodes therein are used at the right side of the body and all cathodes are used at the left side. The duration of the on and off periods of the waveform are controlled by a microprocessor in the IC board **32**.

While there has been shown and described above the preferred embodiment of the instant invention it is to be appreciated that the invention may be embodied otherwise than is herein specifically shown and described and that, within said embodiment, certain changes may be made in the form and arrangement of the parts without departing from the underlying ideas or principles of this invention as set forth in the Claims appended herewith.

The invention claimed is:

1. A apparatus for the electro-physiologic stimulation of the human nervous system, the apparatus comprising:

- (a) a positive electrical assembly comprising;
 - (i) an integrated circuit (IC) board producing a sequence of physiologically acceptable electromagnetic waveforms;
 - (ii) a battery substantially conformal in geometry and in electrical communication with said IC board;
 - (iii) a positive electrode pad in electrical communication with said positive output of said waveforms;
 - (iv) a lower housing in which said IC, battery and positive electrode pad are secured; and
 - (v) an upper housing in circumferential press-swivel contact with an outer periphery of said lower housing in which 360 degrees of rotation of said upper housing relative to said lower housing is enabled;
 - (vi) a first side of an electrical cable in electrical communication with said positive electrode pad;
- (b) a housing for said electrical cable; and
- (c) a negative electrical assembly comprising:
 - (i) a conductive element in electrical communication with a second end of said electrical cable, carrying said negative side of said waveforms;
 - (ii) a negative electrode pad in electrical communication with said conductive element;
 - (iii) a lower housing secured about said conductive element; and
 - (iv) an upper housing at least partially circumferentially secured about said lower housing in pressure-swivel relation thereto.

2. The apparatus as recited in claim **1**, in which said cable communicates with an electrically negative output of said IC.

3. The apparatus as recited in claim **2**, in which a positive output of said IC defines a direct connection to said positive electrode pad.

4. The apparatus as recited in claim **3**, in which said housing of said cable comprises a flexible housing.

5. The apparatus as recited in claim **4**, in which said housing includes air vents.

6. The apparatus as recited in claim **3**, in which a layer of electrically conductive biocompatible material is provided above each of said positive and negative electrode pads.

7. The apparatus as recited in claim **3**, in which a potentiometer is provided on said positive electrode to control an amplitude of said waveform output of said IC.

8. The apparatus as recited in claim **7**, comprises: said potentiometer axially centered at a top of said upper housing of said positive electrode assembly.

9. The apparatus as recited in claim **6**, in which said biocompatible material comprises a gel.

10. The apparatus as recited in claim **1**, in which each of said upper housings include air vents.

11. The apparatus as recited in claim **10**, in which said housing of said cable is provided with air vents.

12. The apparatus as recited in claim **1**, in which said IC includes a microprocessor that includes on-off durations of said waveforms.

* * * * *



US008688240B1

(12) **United States Patent**
Garcia et al.

(10) **Patent No.:** **US 8,688,240 B1**

(45) **Date of Patent:** **Apr. 1, 2014**

(54) **DEVICE FOR NEURO-PHYSIOLOGIC STIMULATION**

USPC 607/40, 136, 133, 145-150, 2, 116
See application file for complete search history.

(71) Applicants: **Julio Luis Garcia**, Coral Gables, FL (US); **Oresteban Carabeo**, Miami Gardens, FL (US); **Ruben Valdes**, Beverly Hills, FL (US); **Robert Valdes**, Miami Lakes, FL (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,165,750 A 8/1979 Alev et al.
5,823,190 A 10/1998 Voipio
8,078,281 B2 12/2011 Priori et al.

(72) Inventors: **Julio Luis Garcia**, Coral Gables, FL (US); **Oresteban Carabeo**, Miami Gardens, FL (US); **Ruben Valdes**, Beverly Hills, FL (US); **Robert Valdes**, Miami Lakes, FL (US)

Primary Examiner — Carl H Layno

Assistant Examiner — Paula J Stice

(74) *Attorney, Agent, or Firm* — Melvin K. Silverman

(73) Assignee: **Mitosis Inc.**, Sunrise, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(57) **ABSTRACT**

A apparatus for the electro-physiologic stimulation of the human nervous system includes an electrical assembly having an integrated circuit (IC) producing a sequence of physiologically compatible electromagnetic waveforms, the IC having ungrounded positive and negative outputs of the waveforms, a battery in electrical communication with the IC board, a positive electrode pad in electrical communication with positive outputs of the waveforms, a lower housing in which the IC battery and positive electrode pad are secured, and an upper housing in press-swivel contact with an outer periphery of the lower housing in which 360 degrees of rotation of the upper housing relative to the lower housing is enabled. Also included is a flexible housing for an electrical cable in electrical communication with an opposite end of the cable, carrying the negative sides of the waveforms, and a negative electrode pad in electrical communication with the conductive plate.

(21) Appl. No.: **13/675,287**

(22) Filed: **Nov. 13, 2012**

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/663,658, filed on Oct. 30, 2012, now Pat. No. 8,457,745.

(51) **Int. Cl.**
A61N 1/32 (2006.01)

(52) **U.S. Cl.**
USPC **607/145; 607/46**

(58) **Field of Classification Search**
CPC . A61N 1/0553; A61N 1/3605; A61N 1/3603; A61N 1/36067; A61N 1/36071; A61N 1/36057

12 Claims, 6 Drawing Sheets

