

# E-SCOUT EL-2650

## TECHNICAL SPECIFICATIONS



Features			
Electric powered	√	Motor brake	√
Remote controlled	√	Linear speed control	√
Modular platform	√	Switchable LED lighting (front & rear)	√
Switchable Motion Alarm	√	Maintenance Free AGM Batteries	√
CAN bus communication	√	Upgradable and configurable software	√
Auxiliary output socket	√	12V & USB Ports	√
Multi-axial Grade monitoring	√	On-board tracking & diagnostics	0

### PHYSICAL CHARACTERISTICS

Frame	Steel
Cabinet	Steel
Length	46 1/2 in (1185 mm)
Width	29 1/2 in (750 mm)
Height	15 3/4 in (399 mm)
Weight	750 lb (340 kg)
Ground clearance	2 1/8 in (54 mm)
Turning diameter	approx. 53 1/4 in (1352 mm)

### PERFORMANCE

Load bearing capacity (Leveled surface)	2650 lb (1202 kg)
Zero-Turn Capacity	Yes

### POWER

Motor power	1.6 HP (X2)
Battery pack configuration	2 x 12 Volts (series)
Battery pack Amperage	115 Ah
Operating voltage	24 VDC
Run-time	Varies according to the operating conditions (Contact Movex Innovation for more information)
Charger	Integrated AC-DC (x1) 110V-230V
Control	Wireless Linear

#### Notes :

1. The information contained in this document is subject to change without notice.