

PACKAGED TERMINAL AIR CONDITIONERS

Expect comfort, reliability and easy maintenance
from one of the toughest names in the industry.



Hotpoint® America's hardest working appliances.



WE'RE BUILDING ON A STRONG REPUTATION.

Since 1903, Hotpoint® has created appliances that get the job done right. In fact, we invented the Packaged Terminal Air Conditioner category back in the 1960s.

Today, Hotpoint PTACs continue that tradition with affordable, dependable units that offer Electric Heat and Heat Pump with Backup Electric Heat options. Our latest features enhance guest comfort and simplify installation & maintenance. And—after extensive product testing from our engineers—you can expect these durable Hotpoint PTACs to provide years of reliable service.



DESIGNED FOR DEPENDABILITY

No matter how it feels outside, Hotpoint® PTACs are engineered with durable materials to provide unwavering comfort inside.

3-Speed Fan

Give guests control over their comfort with three fan speeds to choose from.

4 Temperature-Limiting Options

Easily select one of four temperature ranges for peak efficiency and total customer comfort.

Intuitive Display

Allow guests to easily customize their preferred settings and reduce maintenance calls with an easy-to-use control panel.

Power Cord (LCDI) Included

Hotpoint PTACs come with everything needed for a quick and easy installation.

Automatic Emergency Heat

Keep guests comfortable with a heating option that automatically kicks in when temperatures drop and heat pumps shut down.

Freeze and Frost Protection

Automatic indoor frost control keeps units operating in peak condition.

Auto Power Recovery

In case of power failures, units automatically resume their operation when power restores, reducing maintenance calls.

Self-Diagnostics

Quickly and easily identify service needs with a nine-point diagnostic code system.

Constant Fan Button

Gives guests the option of running the indoor fan continuously even if the unit is in off mode.





◀ CHASSIS ▶

◀ OUTDOOR GRILLE ▶

(Sold Separately)

◀ ROOM FRONT ▶

◀ WALL SLEEVE ▶

(Sold Separately)

Hoipoint



PROVIDE TOTAL COMFORT WITH COMPLETE CONFIDENCE

1-YEAR FULL PARTS & LABOR WARRANTY

Protected for 1 year after original date of purchase

Hotpoint® will provide—free of charge—all labor and related service costs to replace any part of the air conditioner which fails due to a defect in materials or workmanship.

2-5-YEAR LIMITED WARRANTY

Protected for 2-5 years after original date of purchase

Hotpoint will provide—free of charge—all labor and related service costs to replace any part of the Sealed Refrigerating System (the compressor, condenser, evaporator, connecting tubing and the makeup air system) which fails due to a defect in materials or workmanship.

5-YEAR LIMITED WARRANTY

Protected for 5 years after original date of purchase

Hotpoint will provide—free of charge—a replacement part for fan motors, switches, heater, heater protectors, compressor overload, solenoids, circuit boards, auxiliary controls, thermistors, freeze sentinel, frost controls, ICR pump, capacitors, varistors and indoor blower bearing, if this part fails due to a defect in materials or workmanship. Customers will be responsible for any labor and related service costs.

ADDITIONAL FEATURES

- ◆ 24 VAC Remote wall thermostat compatibility
- ◆ Works with central desk control systems
- ◆ Energy-efficient heat pump models available
- ◆ Tangential fan for smooth airflow and sound
- ◆ Heat pump models include staged heating
- ◆ Removable filters for easy maintenance

HOTPOINT PTAC NOMENCLATURE

AH	11	H	09	D	3	B
Brand H=Hotpoint® PTAC	Unit Series Chassis series	Unit Type E= cooling with electric resistance heat H= cooling/heat pump with backup electric heat	Nominal Cooling Capacity 07=7,000 BTUH cooling 09=9,000 BTUH cooling 12=12,000 BTUH cooling 15=15,000 BTUH cooling	Voltage/Phase/Frequency D=230/208 volt, single phase, 60 Hz E=265 volt, single phase, 60 Hz	Heater Watts/Amps 2=2.5 kW; 15 amp 3=3.5 kW; 20 amp 5=5.0 kW; 30 amp	Special Features B=base unit

HOTPOINT COOL SERIES

	HOTPOINT 230/208V								
	COOLING WITH ELECTRIC RESISTANCE HEAT								
	AH11E07D2B	AH11E07D3B	AH11E09D2B	AH11E09D3B	AH11E12D3B	AH11E12D5B	AH11E15D3B	AH11E15D5B	
Voltage	230/208	230/208	230/208	230/208	230/208	230/208	230/208	230/208	
COOLING CAPACITY									
Cooling BTUH	7,200/7,000	7,200/7,000	9,200/9,000	9,200/9,000	12,000/11,800	12,000/11,800	14,500/14,400	14,500/14,400	
EER (BTU/Watt)	11.9	11.9	11.3	11.3	10.7	10.7	9.7	9.7	
Heater Watts	2,500/2,050	3,500/2,900	2,500/2,050	3,500/2,900	3,500/2,900	5,000/4,090	3,500/2,900	5,000/4,090	
Total Electric Heating Watts	2,535/2,080	3,535/2,935	2,535/2,080	3,535/2,935	3,535/2,935	5,036/4,125	3,535/2,935	5,036/4,125	
FEATURES									
Refrigerant Type	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	
Electronic Controls	◆	◆	◆	◆	◆	◆	◆	◆	
LCDI Power Cord	◆	◆	◆	◆	◆	◆	◆	◆	
Remote Thermostat Capable	◆	◆	◆	◆	◆	◆	◆	◆	
Slide-In Chassis	◆	◆	◆	◆	◆	◆	◆	◆	
Discharge Grille	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position	
Fan Motors	2	2	2	2	2	2	2	2	
Fan Speeds	3	3	3	3	3	3	3	3	
Heat - Cool	◆	◆	◆	◆	◆	◆	◆	◆	
Rotary Compressor	◆	◆	◆	◆	◆	◆	◆	◆	
Fan Cycle Control	◆	◆	◆	◆	◆	◆	◆	◆	
Freeze Control	◆	◆	◆	◆	◆	◆	◆	◆	
Automatic Indoor Frost Control	◆	◆	◆	◆	◆	◆	◆	◆	
Auto Power Recovery	◆	◆	◆	◆	◆	◆	◆	◆	
Central Desk Control Capable	◆	◆	◆	◆	◆	◆	◆	◆	
Fresh Air Vent	Concealed Manual Vent Control / Vent Air Filter								
WEIGHT & DIMENSIONS									
Overall Dimensions (including room cover) (WxHxD in in.)	42 x 16 x 21								
Net Weight	102 lb	102 lb	98 lb	98 lb	109 lb	109 lb	113 lb	113 lb	
Approximate Shipping Weight	112 lb	112 lb	109 lb	109 lb	120 lb	120 lb	123 lb	123 lb	

HOTPOINT HEAT PUMP SERIES

	HOTPOINT 230/208V								HOTPOINT 265V (Coming Soon)	
	HEAT PUMP WITH ELECTRIC RESISTANCE HEAT BACKUP									
	AH11H07D2B	AH11H07D3B	AH11H09D2B	AH11H09D3B	AH11H12D3B	AH11H12D5B	AH11H15D3B	AH11H15D5B	AH11H09E3B	AH11H12E3B
Voltage	230/208	230/208	230/208	230/208	230/208	230/208	230/208	230/208	265	265
COOLING CAPACITY										
Cooling BTUH	7,200/6,800	7,200/6,800	9,000/8,800	9,000/8,800	12,000/11,800	12,000/11,800	14,700/14,500	14,700/14,500	9,000	12,000
EER (BTU/Watt)	11.9	11.9	11.4	11.4	10.5	10.5	9.7	9.7	11.3	10.5
Heating HP BTUH	6,000/5,800	6,000/5,800	8,100/7,900	8,100/7,900	10,800/10,500	10,800/10,500	13,500/13,200	13,500/13,200	8,100	10,800
COP	3.4	3.4	3.4	3.4	3.2	3.2	3.0	3.0	3.1	3.2
Heater Watts	2,500/2,050	3,500/2,900	2,500/2,050	3,500/2,900	3,500/2,900	5,000/4,100	3,500/2,900	5,000/4,100	3,500/2,900	3,500/2,900
Total Electric Heating Watts	2,535/2,080	3,535/2,935	2,535/2,080	3,535/2,935	3,535/2,935	5,035/4,125	3,535/2,935	5,035/4,125	3,535/2,935	3,535/2,935
FEATURES										
Refrigerant Type	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A
Electronic Controls	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
LCDI Power Cord	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Remote Thermostat Capable	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Slide-In Chassis	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Discharge Grille	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position
Fan Motors	2	2	2	2	2	2	2	2	2	2
Fan Speeds	3	3	3	3	3	3	3	3	3	3
Heat - Cool	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Rotary Compressor	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Fan Cycle Control	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Freeze Control	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Automatic Indoor Frost Control	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Automatic Emergency Heat	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Auto Power Recovery	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Central Desk Control Capable	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Fresh Air Vent	Concealed Manual Vent Control / Vent Air Filter									
WEIGHT & DIMENSIONS										
Overall Dimensions (including room cover) (WxHxD in in.)	42 x 16 x 21									
Net Weight	105 lb	105 lb	103 lb	103 lb	116 lb	116 lb	117 lb	117 lb	102 lb	113 lb
Approximate Shipping Weight	116 lb	116 lb	113 lb	113 lb	125 lb	125 lb	127 lb	127 lb	112 lb	127 lb



Hotpoint Wall Thermostat
RAK148H2



Hotpoint Wall Case
RAB80



Hotpoint Grille
RAG70



Hotpoint Filter
RAA70



Hotpoint Curtain Guard
RAK44



AIR&WATER
SOLUTIONS

Appliance Park
Louisville, KY 40225
hotpoint.com
Pub. No. 20-T0018 PC95615



Hotpoint®

America's hardest working appliances.