

		STYLE/COLOR	SIZE	FEATURES
VALOR		UL10014 BLACK/BLACK page 22	3.5 - 12, 13, 14  niversal Fit	I/C EH SRO Aluminum Toe
SENTINEL		UL20014 BLACK/BLACK page 22	3.5 - 12, 13, 14  niversal Fit	I/C EH SRO Aluminum Toe
KEG		UL10194 TOBACCO/BLACK page 23	3.5 - 12, 13, 14  niversal Fit	I/C EH SRO Aluminum Toe
CASPER		UL20194 TOBACCO/BLACK page 23	3.5 - 12, 13, 14  niversal Fit	I/C EH SRO Aluminum Toe
BEDROCK		UL10034 CHARCOAL/SLATE page 24	3.5 - 12, 13, 14  niversal Fit	I/C EH SRO Aluminum Toe
VANGUARD		UL20034 CHARCOAL/SLATE page 24	3.5 - 12, 13, 14  niversal Fit	I/C EH SRO Aluminum Toe
TURBO		UL10026 BLACK/SLATE page 25	3.5 - 12, 13, 14  niversal Fit	I/C SD35 SRO Aluminum Toe
APEX		UL20026 BLACK/SLATE page 25	3.5 - 12, 13, 14  niversal Fit	I/C SD35 SRO Aluminum Toe

		STYLE/COLOR	SIZE	FEATURES
TRACE		UL20204 TOBACCO/BLACK page 26	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
PHANTOM		UL20166 BLACK/BLACK page 26	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
FLEXION		UL20086 CHARCOAL/ YELLOW page 27	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
REACTOR		UL20096 CHARCOAL/ GREEN page 27	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
STRICKER		UL20066 CHARCOAL/SLATE page 28	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
NEXOR		UL20076 NAVY/SLATE page 28	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
KINETIC		UL20056 SLATE/SLATE page 29	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
SHADOW		UL20176 BLACK/SLATE page 29	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe

		STYLE/COLOR	SIZE	FEATURES
TEMPEST MF		UL10154 BLACK/BLACK page 32	3.5 - 12, 13, 14  Universal Fit	I/C EH SRO Composite Toe
DASH MF		UL20154 BLACK/BLACK page 32	3.5 - 12, 13, 14  Universal Fit	I/C EH SRO Composite Toe
MACH MF		UL20136 CHARCOAL/SLATE page 33	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
DARK MF		UL20186 BLACK/SLATE page 33	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
NEON MF		UL20146 CHARCOAL/ ORANGE page 34	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
VELOCITY MF		UL20116 GREY/YELLOW page 34	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
ARROW MF		UL20266 BLACK/BLACK page 35	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe

RED FIT

		STYLE/COLOR	SIZE	FEATURES
BULWARK HF		UL10204 BLACK/BLACK page 40	7 - 12, 13, 14  Universal Fit	I/C EH PR SRO FiberToe WP = Waterproof
BARREL HF		UL10224 TOBACCO/BLACK page 40	7 - 12, 13, 14  Universal Fit	I/C EH PR SRO FiberToe WP = Waterproof
FORTRESS HF		UL10214 CHOCOLATE page 41	7 - 12, 13, 14  Universal Fit	I/C EH PR SRO FiberToe WP = Waterproof
TITAN HF		UL10244 BLACK/BLACK page 42	7 - 12, 13, 14  Universal Fit	I/C SD35 PR SRO FiberToe WP = Waterproof
ROANOKE HF		UL10254 CHARCOAL page 42	7 - 12, 13, 14  Universal Fit	I/C EH PR SRO FiberToe WP = Waterproof

SD 35 STATIC DISSIPATIVES

RED LION

		STYLE/COLOR	SIZE	FEATURES
TURBO		UL10026 BLACK/SLATE page 25	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
APEX		UL20026 BLACK/SLATE page 25	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
TRACE		UL20204 TOBACCO/BLACK page 26	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
PHANTOM		UL20166 BLACK/BLACK page 26	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
FLEXION		UL20086 CHARCOAL/YELLOW page 27	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
REACTOR		UL20096 CHARCOAL/GREEN page 27	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
STRICKER		UL20066 CHARCOAL/SLATE page 28	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
NEXOR		UL20076 NAVY/SLATE page 28	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
KINETIC		UL20056 SLATE/SLATE page 29	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe
SHADOW		UL20176 BLACK/SLATE page 29	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Aluminum Toe

RED LION
METAL FREE

MACH MF		UL20136 CHARCOAL/SLATE page 33	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
DARK MF		UL20186 BLACK/SLATE page 33	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
NEON MF		UL20146 CHARCOAL/ORANGE page 34	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
VELOCITY MF		UL20116 GREY/YELLOW page 34	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe
ARROW MF		UL20266 BLACK/BLACK page 35	3.5 - 12, 13, 14  Universal Fit	I/C SD35 SRO Composite Toe

RED
FIT

TITAN HF		UL10244 BLACK/BLACK page 42	7 - 12, 13, 14  Universal Fit	I/C SD35 PR SRO FiberToe WP = Waterproof
-----------------	---	--	--	--

EH - ELECTRICAL HAZARD RATED

RED LION

VALOR



STYLE/COLOR

UL10014
BLACK/BLACK
page 22

SIZE

3.5 - 12, 13, 14
 Universal Fit

FEATURES

I/C EH SRO
Aluminum Toe

SENTINEL



UL20014
BLACK/BLACK
page 22

3.5 - 12, 13, 14
 Universal Fit

I/C EH SRO
Aluminum Toe

KEG



UL10194
TOBACCO/BLACK
page 23

3.5 - 12, 13, 14
 Universal Fit

I/C EH SRO
Aluminum Toe

CASPER



UL20194
TOBACCO/BLACK
page 23

3.5 - 12, 13, 14
 Universal Fit

I/C EH SRO
Aluminum Toe

BEDROCK



UL10034
CHARCOAL/SLATE
page 24

3.5 - 12, 13, 14
 Universal Fit

I/C EH SRO
Aluminum Toe

VANGUARD



UL20034
CHARCOAL/SLATE
page 24

3.5 - 12, 13, 14
 Universal Fit

I/C EH SRO
Aluminum Toe

RED LION METAL FREE

**TEMPEST
MF**



UL10154
BLACK/BLACK
page 32

3.5 - 12, 13, 14
 Universal Fit

I/C EH SRO
Composite Toe

DASH MF



UL20154
BLACK/BLACK
page 32

3.5 - 12, 13, 14
 Universal Fit

I/C EH SRO
Composite Toe

RED FIT

**BULWARK
HF**



UL10204
BLACK/BLACK
page 40

7 - 12, 13, 14
 Universal Fit

I/C EH PR SRO
FiberToe
WP = Waterproof

BARREL HF



UL10224
TOBACCO/BLACK
page 40

7 - 12, 13, 14
 Universal Fit

I/C EH PR SRO
FiberToe
WP = Waterproof

**FORTRESS
HF**



UL10214
CHOCOLATE
page 41

7 - 12, 13, 14
 Universal Fit

I/C EH PR SRO
FiberToe
WP = Waterproof

**ROANOKE
HF**



UL10254
CHARCOAL
page 42

7 - 12, 13, 14
 Universal Fit

I/C EH PR SRO
FiberToe
WP = Waterproof

UL10014

VALOR

- **UPPER** Soft nubuck water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/black

ASTM F2413-24
I/C EH SRO



EH Rated



Aluminum Toe



SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



UL20014

SENTINEL

- **UPPER** Soft nubuck water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/black

ASTM F2413-24
I/C EH SRO



EH Rated



Aluminum Toe



SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



UL10194

KEG

- **UPPER** Pull-up full-grain water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** tobacco/black

ASTM F2413-24
I/C EH SRO



Airtoe
ALUMINIUM

Infinergy®

U-POWER
ORIGINAL

wingtex



Infinergy® midsole with over
55% ENERGY RETURN



EH Rated



Aluminum Toe



SRO

CASPER

UL20194

- **UPPER** Pull-up full-grain water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** tobacco/black

ASTM F2413-24
I/C EH SRO



Airtoe
ALUMINIUM

Infinergy®

U-POWER
ORIGINAL

wingtex



Infinergy® midsole with over
55% ENERGY RETURN



EH Rated



Aluminum Toe



SRO

UL10034

BEDROCK

- **UPPER** Pull-up full-grain water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** charcoal/slate

ASTM F2413-24
I/C EH SRO



EH Rated



Aluminum Toe



SRO



Airtoe
ALUMINIUM

Infinergy®

U-POWER
ORIGINAL

wingtex

**Infinergy® midsole with over
55% ENERGY RETURN**

UL20034

VANGUARD

- **UPPER** Soft nubuck water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** charcoal/slate

ASTM F2413-24
I/C EH SRO



EH Rated



Aluminum Toe



SRO



Airtoe
ALUMINIUM

Infinergy®

U-POWER
ORIGINAL

wingtex

**Infinergy® midsole with over
55% ENERGY RETURN**

UL10026

TURBO

- **UPPER** High abrasion resistant PUTEK® PLUS, water resistant and breathable
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED U-POWER original**
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissapitive SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/slate

ASTM F2413-24
I/C SD 35 SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



SD 35



Aluminum Toe



SRO

UL20026

APEX

- **UPPER** High abrasion resistant PUTEK® PLUS, water resistant and breathable
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED U-POWER original**
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissapitive SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/slate

ASTM F2413-24
I/C SD 35 SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



SD 35



Aluminum Toe



SRO

UL20204

TRACE

- **UPPER** Pull-up full-grain water resistant leather with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** from 3.5-12,13,14 U-niversal Fit width
- **COLOR** tobacco/black

ASTM F2413-24
I/C SD 35 SRO



Airtoe
ALUMINIUM

Infinergy®

U-POWER
ORIGINAL

wingtex



Infinergy® midsole with over
55% ENERGY RETURN



SD 35



Aluminum Toe



SRO

UL20166

PHANTOM

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/black

ASTM F2413-24
I/C SD 35 SRO



Airtoe
ALUMINIUM

Infinergy®

U-POWER
ORIGINAL

wingtex



Infinergy® midsole with over
55% ENERGY RETURN



SD 35



Aluminum Toe



SRO

UL20086

FLEXION

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyuethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissapitive SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** charcoal/yellow
- **Interchangeable black laces included**



Infinergy® midsole with over 55% ENERGY RETURN



SD 35



Aluminum Toe



SRO

UL20096

REACTOR

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyuethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissapitive SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** charcoal/green



Infinergy® midsole with over 55% ENERGY RETURN



SD 35



Aluminum Toe



SRO

UL20066

STRICKER

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissapitive SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** charcoal/slate

ASTM F2413-24
I/C SD 35 SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



SD 35



Aluminum Toe



SRO

NEXOR

UL20076

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissapitive SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** navy/slate

ASTM F2413-24
I/C SD 35 SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



SD 35



Aluminum Toe



SRO

UL20056

KINETIC

- **UPPER** Ultra-breathable AIRNET and soft suede upper
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** slate/slate

ASTM F2413-24
I/C SD 35 SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



SD 35



Aluminum Toe



SRO

SHADOW

UL20176

- **UPPER** Ultra-breathable AIRNET and soft suede upper
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Aluminum, maximum protection with streamlined shape
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/slate

ASTM F2413-24
I/C SD 35 SRO



**Infinergy® midsole with over
55% ENERGY RETURN**



SD 35



Aluminum Toe



SRO

UL10154 **TEMPEST MF**

- **UPPER** Soft nubuck water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Composite Metal Free
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** from 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/black

ASTM F2413-24
I/C EH SR

wingtex

METAL FREE 100%

PATENTED

Airtoe COMPOSITE

Infinergy

U-POWER ORIGINAL



Infinergy® midsole with over 55% ENERGY RETURN



EH Rated



Composite Toe



SRO

UL20154 **DASH MF**

- **UPPER** Soft nubuck water resistant leather
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Composite Metal Free
- **FOOTBED** In soft polyurethane dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/black

ASTM F2413-24
I/C EH SR

wingtex

METAL FREE 100%

PATENTED

Airtoe COMPOSITE

Infinergy

U-POWER ORIGINAL



Infinergy® midsole with over 55% ENERGY RETURN



EH Rated



Composite Toe



SRO

UL20136

MACH MF

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Composite Metal Free
- **FOOTBED U-POWER original**
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** charcoal/slate

ASTM F2413-24
I/C SD 35 SR

wingtex

METAL FREE 100%



Airtoe COMPOSITE

Infinergy®

U-POWER ORIGINAL



Infinergy® midsole with over
55% ENERGY RETURN



SD 35



Composite Toe



SRO

UL20186

DARK MF

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Composite Metal Free
- **FOOTBED U-POWER original**
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/slate

ASTM F2413-24
I/C SD 35 SR

wingtex

METAL FREE 100%



Airtoe COMPOSITE

Infinergy®

U-POWER ORIGINAL



Infinergy® midsole with over
55% ENERGY RETURN



SD 35



Composite Toe



SRO

UL20146

NEON MF

- **UPPER** Soft suede upper with textile inserts
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Composite Metal Free
- **FOOTBED U-POWER original**
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** charcoal/orange
- **Interchangeable black laces included**

METAL FREE 100%

PATENTED

Airtoe COMPOSITE

Infinergy



U-POWER ORIGINAL

wingtex



ASTM F2413-24
I/C SD 35 SR



SD 35



Composite Toe



SRO

**Infinergy® midsole with over
55% ENERGY RETURN**

VELOCITY MF

UL20116

- **UPPER** Ultra-breathable AIRNET and soft suede upper
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Composite Metal Free
- **FOOTBED U-POWER original**
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** grey/yellow

wingtex

METAL FREE 100%

PATENTED

Airtoe COMPOSITE

Infinergy



U-POWER ORIGINAL



ASTM F2413-24
I/C SD 35 SR



SD 35



Composite Toe



SRO

**Infinergy® midsole with over
55% ENERGY RETURN**

UL20266

ARROW MF

- **UPPER** Ultra-breathable AIRNET and soft suede upper
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** AirToe Composite Metal Free
- **FOOTBED U-POWER original**
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 3.5-12,13,14 U-niversal Fit width
- **COLOR** black/black

wingtex

METAL FREE 100%

PATENTED

Airtoe COMPOSITE

Infinergy®

U-POWER ORIGINAL

ASTM F2413-24
I/C SD 35 SR



SD 35



Composite Toe



SRO

Infinergy® midsole with over
55% ENERGY RETURN



BULWARK HF

UL10204

- **UPPER** Pull-up full grain leather U-DRYTECH membrane
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** FiberToe lightweight and metal free
- **PUNCTURE RESISTANCE** Save & Flex® PLUS Lightweight and flexible composite puncture resistant midsole
- **FOOTBED** 3-insole set in soft PU dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 7-12, 13, 14 U-niversal Fit width
- **COLOR** black/black

ASTM F2413-24
I/C EH PR SRO



EH



FiberToe



SRO



PR



WP



Infinergy® midsole with over 55% ENERGY RETURN

METAL FREE 100%



Fibertoe

Infinergy®

U-POWER ORIGINAL

U DRYTECH

BARREL HF

UL10224

- **UPPER** Soft nubuck leather U-DRYTECH membrane
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** FiberToe lightweight and metal free
- **PUNCTURE RESISTANCE** Save & Flex® PLUS Lightweight and flexible composite puncture resistant midsole
- **FOOTBED** 3-insole set in soft PU dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 7-12, 13, 14 U-niversal Fit width
- **COLOR** tobacco/black

ASTM F2413-24
I/C EH PR SRO



EH



FiberToe



SRO



PR



WP



Infinergy® midsole with over 55% ENERGY RETURN

METAL FREE 100%



Fibertoe

Infinergy®

U-POWER ORIGINAL

U DRYTECH

FORTRESS HF

UL10214

- **UPPER** Pull-up full grain leather U-DRYTECH membrane
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **SAFETY TOE CAP** FiberToe lightweight and metal free
- **PUNCTURE RESISTANCE** Save & Flex® PLUS Lightweight and flexible composite puncture resistant midsole
- **FOOTBED** 3-insole set in soft PU dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 7-12, 13, 14 U-niversal Fit width
- **COLOR** chocolate

METAL FREE 100%



Fibertoe

Infinergy®

U-POWER Original N.A.C.

U DRYTECH



ASTM F2413-24
I/C EH PR SRO



EH



Fibertoe



SRO



PR



WP

Infinergy® midsole with over 55% ENERGY RETURN



UL10244

TITAN HF

- **UPPER** High abrasion resistant Putek HD with waterproof
- **LINING** 3D Mesh lining for superior breathability and moisture wicking U-DRYTECH membrane.
- **BOA Lacing system**
- **SAFETY TOE CAP** FiberToe lightweight and metal free
- **PUNCTURE RESISTANCE** Save & Flex® PLUS Lightweight and flexible composite puncture resistant midsole
- **FOOTBED** 3-insole set in soft PU dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Static Dissipative SD 35 Rated**
- **SIZE** 7-12, 13, 14 U-niversal Fit width
- **COLOR** black/black

ASTM F2413-24
I/C SD 35 PR SRO



PU Tek HD
HYPERTEX technology

METAL FREE
100%



Fibertoe

Infinergy®

U-POWER
ORIGINAL

U DRYTECH



Infinergy® midsole with over
55% ENERGY RETURN



SD 35



FiberToe



SRO



PR



WP

UL10254

ROANOKE HF

- **UPPER** Nubuck full grain leather with waterproof U-DRYTECH membrane
- **LINING** 3D Mesh lining for superior breathability and moisture wicking
- **BOA Lacing system**
- **SAFETY TOE CAP** FiberToe lightweight and metal free
- **PUNCTURE RESISTANCE** Save & Flex® PLUS Lightweight and flexible composite puncture resistant midsole
- **FOOTBED** 3-insole set in soft PU dynamic compound
- **SOLE** Direct-attach construction dual density PU with **Infinergy®** midsole Slip, Oil & Abrasion Resistant
- **Electrical Hazard Rated**
- **SIZE** 7-12, 13, 14 U-niversal Fit width
- **COLOR** charcoal

ASTM F2413-24
I/C EH PR SRO



Fibertoe

Infinergy®

U-POWER
ORIGINAL

U DRYTECH



Infinergy® midsole with over
55% ENERGY RETURN




EH



Fibertoe



SRO



PR



WP