

Product Bulletin

SLIDE OUT

FOOD GRADE DRY SILICONE SPRAY

FEATURES:

Concentrated formula. A little SLIDE OUT goes a long way.
Reduces friction between moving parts even for metal-to-metal contact surfaces.
Clean, dry spray does not leave a sticky residue behind.

DESCRIPTION:

SLIDE OUT is designed to lubricate equipment used in the packaging and processing industry. Slide Out leaves a non-staining, dry, pure silicone film to lubricate moving parts, reducing friction and wear. SLIDE OUT is heat stable from -30°F to 300°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Complies with FDA regulations, CFR Title 21, paragraph 178.3570 when fully cured. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.

APPLICATIONS:

Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. An excellent product for food processing plants, restaurants, apparel and accessory manufacturing, tank closure seals, plastic products, RV dealers, hotels/motels, machine shops, homes, service hinges, auto/RV repair shops and institutions.

DIRECTIONS:

Read cautions carefully before use. Area to be lubricated should be clean and dry. Shake well before use. Hold can 6-8 inches from surface. Spray in short bursts. Spray no more than required to lubricate surface. Do not spray electrical equipment while in use. Wait 5-10 minutes before operating electrical equipment after using. Spray is dry. Do not expect a liquid. Used as directed, it will not harm most surfaces.

SPECIFICATIONS:

FORM:.....Solvent-Based Aerosol	FLASH POINT:.....<5°F TCC
ODOR:.....Mild Solvent	FLAME EXTENSION:.....None
COLOR:.....Clear	SOLUBILITY IN WATER:.....40%
COLD STABILITY:.....0°F	SPECIFIC GRAVITY:.....0.76
TOXICITY:.....400 ppm OSHA TLV	% VOLATILE BY VOLUME:.....96%
STORAGE STABILITY:.....1 Year +	PROPELLANT:.....Hydrocarbon

FOR FURTHER INFORMATION REFER TO THE MATERIAL SAFETY DATA SHEET

PACKAGING:

Available in 12 - 20 oz. cans per case.

PRODUCT CODE:.....5380



INDUSTRIAL RESEARCH PRODUCTS

2505 Frank Albert Road, Suite B 120
Fife, Washington 98424

Toll Free 1-800-400-0681

Fax 253-926-1577

www.IndustrialResearchProducts.com

Dry Silicone Spray

Food Grade

Lubricant

Release Agent

Colorless

Odorless

Non-Toxic

Heat Stable

No Sticky Residue