

CABIN LEAKAGE TESTER
PART NUMBER 10037-30
LEADING PARTICULARS

OPERATING CHARACTERISTICS

Test Medium	Compressed Air
Pressure, Cabin	2 through 12.5 psig range
Flow	10 through 400 SCFM
Temperature	To within 15 degrees of ambient temperature at maximum flow and pressure
Pressure, Canopy Seal	0 through 65 psig
Flow, Canopy Seal	1 SCFM

OPERATING AMBIENT TEMPERATURE

Range	0 Degree F to + 120 Degree F
-------------	------------------------------

ALTITUDE OPERATING

Range	Sea Level to 6,000 ft
-------------	-----------------------

STORAGE TEMPERATURE

Range	-80 Degree F + 160 Degree F
-------------	-----------------------------

OPERATING POSITIONS	8-1/2 Degree incline with true horizontal plane
---------------------------	--

TOW SPEED	20 mph improved roads, 10 mph unimproved roads
-----------------	---

CRAMPING ANGLE	40 degrees
----------------------	------------

TIRE INFLATION	60 psig
----------------------	---------

OVERALL DIMENSIONS	Height: 59.0 inches Length: 98.0 inches Width: 62.5 inches
--------------------------	--

WEIGHT	3800 LBS w/o hoses 4000 lbs w hoses
--------------	--

ELECTRICAL POWER REQUIREMENTS	230 +/- 23 volts AC, 60 Hz, 3 phase, convertible to 460 +/- 46, volt operation
-------------------------------------	---