

TRAILER MODEL CATALOG



2024



X-ON

DECKOVER TRAILERS

At X-On Trailers, we understand the importance of a dependable hauling solution. Our Deckover Trailers are engineered to provide the strength and stability needed for transporting a variety of heavy loads. Whether you're hauling construction equipment, vehicles, or palletized materials, our trailers are built to withstand the challenges of the road. When it comes to transporting wide and large equipment, vehicles, and palletized material, trust X-On Trailers for unmatched performance and reliability. Our Deckover Trailers are more than just a mode of transport – they're a testament to our commitment to quality, durability, and your peace of mind on the road.



X-ON DECKOVER MODELS

LENGTHS: 16'-44'



14K DECKOVER GOOSENECK

- GVWR: 14,000- 21,000 LBS
- FRAME: 12" 14# I-BEAM FRAME & NECK
- AXLE: 2-7 & 2-8K LBS. AXLES ON 26' AND UNDER, 3-7 & 3-8K ON 28' AND LONGER
- LENGTH: 20-40'
- DECK HEIGHT: 33"
- DECK WIDTH: 102"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES



20K/24K LOW-PRO DUAL TANDEM GOOSENECK

- GVWR: 22,990 - 25,990 LBS.
- FRAME: 12" 19# I-BEAM FRAME & NECK
- AXLE: 2-10K & 2-12K AXLES
- LENGTH: 20-44'
- DECK HEIGHT: 33"
- DECK WIDTH: 102"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES



30K LOW-PRO DUAL TANDEM GOOSENECK

- GVWR: 30,000 LBS.
- FRAME: 12" 22# I-BEAM FRAME & NECK
- AXLE: 2-15K AXLES
- LENGTH: 20-44'
- DECK HEIGHT: 33"
- DECK WIDTH: 102"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES



20K/24K LOW-PRO DUAL TANDEM HYDRAULIC DOVE-TAIL

- GVWR: 22,990 - 25,990 LBS.
- FRAME: 12" 19# I-BEAM FRAME & NECK
- AXLE: 2-10K & 2-12K AXLES
- LENGTH: 26-44'
- DECK HEIGHT: 33"
- DECK WIDTH: 102"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES



12/14K BUMPER PULL DECKOVER (LIGHT DUTY)

- GVWR: 12,000-14,000 LBS
- FRAME: 6" C-CHANNEL FRAME & TONOQUE
- AXLE: 2-6K & 2-7K AXLES
- LENGTH: 16-24'
- DECK HEIGHT: 33"
- DECK WIDTH: 102"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



8" I-BEAM BUMPER PULL DECKOVER

- GVWR: 14,000-16,000 LBS
- FRAME: 8" C-CHANNEL FRAME & TONOQUE
- AXLE: 2-7K & 2-8K AXLES
- LENGTH: 18-24'
- DECK HEIGHT: 33"
- DECK WIDTH: 102"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



16K DECKOVER GOOSENECK

- GVWR: 16,000 LBS
- FRAME: 8" 12" 14# I-BEAM FRAME & NECK
- AXLE: 8K LB SPRING AXLES
- LENGTH: 16-40'
- DECK HEIGHT: 33"
- DECK WIDTH: 102"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES





X-ON

ENCLOSED CARGO

X-On enclosed cargo trailers are engineered to offer unparalleled protection for your cargo. With walls and a roof made of solid steel, these trailers provide a robust shield against road debris, dust, rain, sun, and other hazards that can jeopardize the integrity of your items. When it comes to safeguarding your valuable cargo, trust X-On Trailers to deliver uncompromising protection and reliability. Explore our range of Enclosed Cargo Trailers and experience the peace of mind that comes with knowing your cargo is shielded by innovation.



X-ON CARGO MODELS

LENGTHS: 16'-44'



BUMPERPULL CARGO

- GVWR: 7,000- 14,000 LBS.
- FRAME: 10 GAUGE FENDER & 3X5" X 3/16" ANGLE IRON FRAME
- AXLE: 2-7 & 2-8K LBS. TORSION AXLES ON 26' AND UNDER, 3-7 & 3-8K LBS. TORSION AXLES ON 28' AND LONGER 2-3.5K & 2-6K & 2-7K LBS. TORSION AXLES
- INTERIOR HEIGHT: 6'6"
- WIDTH: 6'. 6'8, 8'
- COUPLERS: ADJUSTABLE 2 5/16
- TIRES: 235/80R16 RADIAL TIRES



GOOSENECK CARGO

- GVWR: 7,000- 14,000 LBS.
- FRAME: 2"X6" TUBING FRAME 8" I-BEAM
- AXLE: 7K,8K, OR 10K TORSION X 2
- INTERIOR HEIGHT: 6'6"
- WIDTH: 6'. 6'8, 8'
- COUPLERS: 2 5/16" 25K ROUND GOOSENECK COUPLER
- TIRES: 235/80R16 RADIAL 10PLY TIRES





X-ON

DUMP TRAILERS

Embraced by professionals in construction, landscaping, and agriculture, our Dump Trailers are versatile workhorses. They adapt to the demands of various industries, providing a reliable solution for transporting and unloading bulk materials on construction sites, farms, and landscaping projects. When it comes to transporting and unloading loose materials, X-On Dump Trailers stand as a testament to reliability and efficiency. Explore our range of Dump Trailers and experience the strength, versatility, and precision engineering that make X-On Trailers the preferred choice for industry professionals.



X-ON DUMP MODELS

LENGTHS: 8-16'



7K BUMPER PULL 60" WIDE DUMP

- GVWR: 7,000 LBS
- FRAME: 6" C-CHANNEL FRAME & 6" I-BEAM TONGUE
- AXLE: 2-3.5K & 1-7K LBS. AXLES
- LENGTH: 8-10'
- SIDE HEIGHT: 18"
- INSIDE HEIGHT: 60"
- BED HEIGHT: 26"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 225/75R15 RADIAL TIRES



12K BUMPER PULL 72" WIDE DUMP

- GVWR: 12,000 LBS
- FRAME: 8" I-BEAM FRAME & TONGUE
- AXLE: 2- 6K LBS. AXLES
- LENGTH: 12'
- SIDE HEIGHT: 21"
- INSIDE HEIGHT: 72"
- BED HEIGHT: 28"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



14K/16K BUMPER PULL 83" WIDE DUMP

- GVWR: 14,000 LBS
- FRAME: 8" I-BEAM FRAME & TONGUE
- AXLE: 2- 8K LBS. AXLES
- LENGTH: 12'-16'
- SIDE HEIGHT: 24", 36", & 48"
- INSIDE WIDTH: 83"
- BED HEIGHT: 24-28"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



14K/16K GOOSENECK 83" WIDE DUMP

- GVWR: 14,000-16,000" LBS
- FRAME: 8" I-BEAM FRAME & 10" I-BEAM NECK
- AXLE: 2- 8K LBS. AXLES
- LENGTH: 12'-16'
- SIDE HEIGHT: 24", 36", & 48"
- INSIDE WIDTH: 83"
- BED HEIGHT: 24-28"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES



X-ON

UTILITY & LANDSCAPE

We understand that every job is unique. That's why X-On offers a range of sizes and customization options for our Utility & Landscape Trailers. Whether you need a trailer for landscaping tools, porta-potties, or waste disposal, we have the perfect solution for you. When you need a trailer that goes beyond transportation, choose X-On Utility & Landscape Trailers. Experience the transformative power of our trailers as they make once laborious tasks simple and efficient.



60" WIDE SINGLE AXLE UTILITY (ANGLE FRAME)

- GVWR: 3,500 LBS
- FRAME: 2"X3"X3/16" ANGLE FRAME & 4" CHANNEL TONGUE
- AXLE: 1-3.5K LBS. AXLE
- LENGTH: 8-14'
- DECK HEIGHT: 21"
- DECK WIDTH: 60"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES



77" WIDE SINGLE AXLE UTILITY (ANGLE FRAME)

- GVWR: 3,500 LBS
- FRAME: 2"X3"X3/16" ANGLE FRAME & 4" CHANNEL TONGUE
- AXLE: 1-3.5K LBS. AXLE
- LENGTH: 8-14'
- DECK HEIGHT: 21"
- DECK WIDTH: 77"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES



83" WIDE SINGLE AXLE UTILITY (ANGLE FRAME)

- GVWR: 3,500 LBS
- FRAME: 2"X3"X3/16" ANGLE FRAME & 4" CHANNEL TONGUE
- AXLE: 1-3.5K LBS. AXLE
- LENGTH: 10-14'
- DECK HEIGHT: 21"
- DECK WIDTH: 83"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES



X-ON UTILITY MODELS

LENGTHS: 8'-22'



60" WIDE TANDEM UTILITY (ANGLE FRAME)

- GVWR: 3,500 LBS
- FRAME: 2"X3"X3/16" ANGLE FRAME & 4" CHANNEL TONGUE
- AXLE: 1-3.5K LBS. AXLE
- LENGTH: 10-14'
- DECK HEIGHT: 21"
- DECK WIDTH: 83"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES



77" WIDE TANDEM UTILITY (ANGLE FRAME)

- GVWR: 7,000 LBS
- FRAME: 2"X3"X3/16" ANGLE FRAME & 4" CHANNEL TONGUE
- AXLE: 2-3.5K LBS. AXLE
- LENGTH: 10-18'
- DECK HEIGHT: 21"
- DECK WIDTH: 77"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES



83" WIDE TANDEM UTILITY (ANGLE FRAME)

- GVWR: 7,000 LBS
- FRAME: 2"X3"X3/16" ANGLE FRAME & 4" CHANNEL TONGUE
- AXLE: 2-3.5K LBS. AXLE
- LENGTH: 10-20'
- DECK HEIGHT: 21"
- DECK WIDTH: 83"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES



60" WIDE TANDEM UTILITY (4" CHANNEL FRAME)

- GVWR: 7,000 LBS
- FRAME: 4" CHANNEL FRAME & TONGUE
- AXLE: 2-3.5K LBS. AXLE
- LENGTH: 10-14'
- DECK HEIGHT: 21"
- DECK WIDTH: 60"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRE



77" WIDE TANDEM UTILITY (4" CHANNEL FRAME)

- GVWR: 7,000 LBS
- FRAME: 4" CHANNEL FRAME & TONGUE
- AXLE: 2-3.5K LBS. AXLE
- LENGTH: 10-20'
- DECK HEIGHT: 21"
- DECK WIDTH: 77"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES



83" WIDE TANDEM UTILITY (4" CHANNEL FRAME)

- GVWR: 7,000 LBS
- FRAME: 4" CHANNEL FRAME & TONGUE
- AXLE: 2-3.5K LBS. AXLE
- LENGTH: 10-22'
- DECK HEIGHT: 21"
- DECK WIDTH: 83"
- COUPLERS: 2" A-FRAME
- TIRES: 205/75R15 RADIAL TIRES





X-ON

EQUIPMENT & CAR-HAULER TRAILERS

X-On Equipment & Car Hauler Trailers are designed with lower deck heights, prioritizing the safety and ease of vehicle transport. Whether you're hauling a single car or multiple vehicles, our trailers offer a reliable solution for your transportation needs. Whether you're a car enthusiast, professional transporter, or in the business of heavy equipment, our trailers are adapted to cater to a variety of hauling demands. When it comes to safe and reliable vehicle transport, trust X-On Equipment & Car Hauler Trailers to deliver unmatched performance.



WWW.XONTRAILERS.COM



(903)739-9402



X-ON HAULER MODELS

LENGTHS: 16'-40'



83" WIDE 12K EQUIPMENT (BUMPER PULL)

- GVWR: 12,000 LBS
- FRAME: 6" C-CHANNEL FRAME & TONGUE
- AXLE: 2-6K LBS. AXLE
- LENGTH: 16-24'
- DECK HEIGHT: 25"
- DECK WIDTH: 83"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



102" WIDE 12K EQUIPMENT (BUMPER PULL)

- GVWR: 12,000 LBS
- FRAME: 6" I-BEAM INNER FRAME & 6" C-CHANNEL OUTER FRAME & TONGUE
- AXLE: 2-6K LBS. AXLE
- LENGTH: 16-22'
- DECK HEIGHT: 26"
- DECK WIDTH: 102"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



83" WIDE 7K EQUIPMENT (BUMPER PULL)

- GVWR: 7,000 LBS
- FRAME: 4" C-CHANNEL FRAME & TONGUE
- AXLE: 2-3.5K LBS. AXLE
- LENGTH: 12-20'
- DECK HEIGHT: 21"
- DECK WIDTH: 83"
- COUPLERS: 2 A-FRAME COUPLERS
- TIRES: 205/75R16 RADIAL TIRES



83" WIDE 14/16K EQUIPMENT (BUMPER PULL)

- GVWR: 14,000-16,000 LBS
- FRAME: 6" C-CHANNEL FRAME & TONGUE
- AXLE: 2-7K & 2-8K LBS. AXLES
- LENGTH: 16-24'
- DECK HEIGHT: 27"
- DECK WIDTH: 83"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



102" WIDE 14/16K EQUIPMENT (BUMPER PULL)

- GVWR: 14,000-16,000 LBS
- FRAME: 6" I-BEAM INNER FRAME & 6" C-CHANNEL OUTER FRAME & TONGUE
- AXLE: 2-7K & 2-8K LBS. AXLES
- LENGTH: 16-24'
- DECK HEIGHT: 26"
- DECK WIDTH: 102"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES



83" WIDE 14K/16K EQUIPMENT (GOOSENECK)

- GVWR: 14,000-24,000 LBS
- FRAME: 8" C-CHANNEL FRAME & 10" I-BEAM NECK ON 26' AND UNDER, 10" C-CHANNEL FRAME & 12" I-BEAM NECK ON 28' AND LONGER
- AXLE: 2-7K & 2-8K LBS. AXLES ON 26' AND UNDER, 10' C-CHANNEL FRAME & 12" I-BEAM NECK ON 28' AND LONGER
- LENGTH: 20-40'
- DECK HEIGHT: 28"
- DECK WIDTH: 83"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES

102" WIDE 14K/16K EQUIPMENT (GOOSENECK)

- GVWR: 14,000-24,000 LBS
- FRAME: 8" C-CHANNEL FRAME & 10" I-BEAM NECK ON 26' AND UNDER, 10" C-CHANNEL FRAME & 12" I-BEAM NECK ON 28' AND LONGER
- AXLE: 2-7K & 2-8K LBS. AXLES ON 26' AND UNDER, 10' C-CHANNEL FRAME & 12" I-BEAM NECK ON 28' AND LONGER
- LENGTH: 20-40'
- DECK HEIGHT: 28"
- DECK WIDTH: 102"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES



8" I-BEAM EQUIPMENT (BUMPER PULL)

- GVWR: 14,000-16,000 LBS
- FRAME: 8" I-BEAM FRAME AND TONGUE
- AXLE: 2-7K & 2-8K LBS. AXLES
- LENGTH: 18-24'
- DECK HEIGHT: 27"
- DECK WIDTH: 83"
- COUPLERS: ADJUSTABLE 2 5/16"
- TIRES: 235/80R16 RADIAL TIRES





X-ON

X-ON EQUIPMENT TILT

X-On Equipment Tilt Trailers are engineered to streamline the loading and unloading process, making it effortless for you to get to work or enjoy your recreational activities sooner. The tilt feature eliminates the need for ramps, providing a hassle-free experience for equipment placement. Experience smooth and controlled tilting with our trailers, thanks to gravity tilts and hydraulics. These features enhance the ease of operation, ensuring a seamless tilt process that aligns with your specific requirements. When it comes to efficient loading and unloading, trust X-On Equipment Tilt Trailers to deliver a hassle-free experience.



WWW.XONTRAILERS.COM



(903)739-9402



X-ON TILT MODELS

LENGTHS: 16'-24'



14/16K BUMPER PULL 102" EQUIPMENT TILT

- GVWR: 14,000- 16,000 LBS.
- FRAME: 2"X6" TUBING FRAME & TONGUE
- AXLE: 2-7 & 2-8K LBS. AXLES
- TILT OPTION: 16' GRAVITY OR POWER UP/DOWN DECK
- LENGTH: 16- 24'
- DECK HEIGHT: 21"
- DECK WIDTH: 83" & 102"
- COUPLERS: ADJUSTABLE 2 5/16
- TIRES: 235/80R16 RADIAL TIRES



14/16K GOOSENECK 102" EQUIPMENT TILT

- GVWR: 14,000- 16,000 LBS.
- FRAME: 2"X6" TUBING FRAME & 10" I-BEAM NECK
- AXLE: 2-7 & 2-8K LBS. AXLES
- TILT OPTION: 16' GRAVITY OR POWER UP/DOWN DECK
- LENGTH: 16- 24'
- DECK HEIGHT: 21"
- DECK WIDTH: 83" & 102"
- COUPLERS: GOOSENECK 25K 2 5/16" ROUND
- TIRES: 235/80R16 RADIAL TIRES

X-ON WARRANTY POLICY

MANUFACTURER'S LIMITED WARRANTY

X-On Trailers, LLC warrants that its product, operated by the original purchaser under normal use and service, is free from defects in material and workmanship for a period of 1-year from the date of the original sale, subject to the requirements, exclusions, and limitations stated below. Upon the purchase of an X-On Trailer, the purchaser agrees to the manufacturer's Limited Warranty, which accompanies the purchase of a new trailer. The purchaser acknowledges being informed of the Limited Warranty and claim procedures and agrees to fulfill all responsibilities under this Limited Warranty.

WARRANTY COVERAGE

This 1-year Limited Warranty on Cargo Trailers, and 2-year Limited Warranty on Utility, Flatbeds, and Dumps covers the structural components of the trailer. This includes the frame, consisting of fenders, crossmembers, side posts, exterior walls, roof rails, bows, and the subframe. Additionally, X-On Trailers, LLC warrants its paint application to adhere to industry standards for 1 year after the original purchase date, with the exception of normal wear conditions and deterioration due to factors such as chipping, scratching, fading, cracks in caulk seams, road salt, or tar, and damage by animals or pressure washers.

WARRANTY EXCLUSIONS

Tires, axles, brake components, springs and suspension components, couplers, jacks, castors, mats, batteries, windows, doors, and any other auxiliary parts purchased and installed by X-On Trailers, LLC are warranted by their manufacturer and are not included in this Limited Warranty.

WARRANTY VOID

This Limited Warranty covers only defects in original components due to normal use and will be void if the product is subject to accident, misuse, negligence, tampering, overloading, improper attachment, or improper maintenance. Normal wear items, including but not limited to flooring, paint, brake linings, and bearings, will not be replaced due to wear. Loading in excess of gross vehicle load ratings stated on the certificate will invalidate all warranties. This Limited Warranty excludes any and all liability for consequential or incidental damages. The Warranty does not cover a product that has been repaired, altered, or tampered with outside of the factory of X-On Trailers, LLC without written approval by X-On Trailers, LLC. If a trailer has been rented or used for commercial hauling, this Limited Warranty is null and void.

LIMITATIONS

The sole responsibility of X-On Trailers, LLC under this Limited Warranty shall be to repair and replace parts at the X-On Trailers, LLC factory, an authorized X-On Trailers, LLC dealer, or another location with prior approval by X-On Trailers, LLC. Any repairs performed at a location other than X-On Trailers, LLC will be granted \$65.00 per hour for labor costs. X-On Trailers, LLC reserves the right to refuse excessive charges for labor costs. Transportation of any trailer to and from your dealer or an approved repair facility shall be the responsibility of the trailer owner. All other obligations or liabilities, including incidental or consequential damages, or contingent liabilities arising out of the failure of any parts to operate properly, are hereby excluded, including but not limited to any damages resulting from loss of use, inconvenience, loss of time, commercial loss, or any type of damages, general or specific, foreseen or unforeseen, unless applicable state law provides otherwise.

DISCLAIMERS

This Limited Warranty is expressly in lieu of all other warranties and representations. X-On Trailers, LLC makes no representation or warranty of any kind, express or implied, with respect to X-On Trailers, LLC, whether as to merchantability, fitness for a particular purpose, or any other matter. No one, including an authorized X-On Trailers, LLC dealer, is authorized to make further or additional warranties on behalf of X-On Trailers, LLC. All implied warranties of merchantability and fitness for intended use are limited to warranty periods stated above unless any applicable state law provides otherwise.

