

SLC CUBE3+ A

Uninterruptible power supply system from 5 to 100 kVA

SLC CUBE3+ A: Energy efficiency with superior electrical protection

Salicru's **SLC CUBE3+ A** series is a UPS range featuring high-performance, On-line double conversion (VFI) technology that provides a reliable, high-quality power supply and, at the same time, achieves significant energy and financial savings in terms of installation and operating costs.

Particularly noteworthy is the unit's input power factor ($PF=1$) and its extremely low distortion rate (THDi even lower than 1%), which help to reduce installation and operating costs, and contribute to improving the quality of the electrical grid.

The output power factor ($PF=0.9$) also stands out, providing optimum electrical protection for computer systems and low harmonic output distortion (THDv even lower than 0.5%), enabling it to protect any type of load (inductive, resistive, capacitive or mixed). In addition, the performance achieved (up to 95% in On-line mode and 98% in Smart Eco-mode) produces significant energy consumption savings and reduces air conditioning needs.

For a full optimum solution, the **SLC CUBE3+ A** provides maximum adaptability (even with the standard model), the possibility of parallel redundant expansion and extensive communication options. Finally, also worth noting is the unit's lightweight design and reduced dimensions, enabling it to be easily installed and ensuring that footprint is minimal.



Applications: Designed to protect any type of environment

High-end design features plus great flexibility capacity (options, power upgrading, communications...) make **SLC CUBE3+ A** series the best option to protect and secure a wide range of environments: data-centres, hosting, housing, IT-networks, server farms, voice and data networks...



salicru
SMART
SOLUTIONS

salicru

Performances

- On-line double conversion (VFI) technology with DSP control.
- Input power factor 1, for better performance.
- Very low input current harmonic distortion (THDi as low as <1%).
- Total flexibility in input/output voltage. ⁽¹⁾
- Designed to withstand any type of load.
- Batt-Watch function for monitoring and battery care.
- High output power factor (PF=0.9).
- Very low output voltage distortion rate (THDv even lower than 0.5%).
- On-line mode efficiency of up to 95%.
- Smart Eco-mode efficiency of up to 98.4%.
- Very compact design with minimal footprint.
- Can be integrated into the most advanced IT environments.
- Parallel redundant configuration (N+1) for critical installations. ⁽²⁾
- Built with 80% recyclable materials.
- SLC Greenergy solution.

ON
LINE

OPF =
0.9

TOWER

UPS
...

SNMP
SLOT

+

Hz

+

ECO
MODE

UPS

+


SLC
GREENERGY
SOLUTIONS

(1) Single/single, single/three and three/single configurations up to 30 kVA

(2) Up to 4 units


High efficiency

High performance in On-line and Smart Eco-mode operation.



Low harmonic distortion

The lowest harmonic distortion in the market.



Options

- Ethernet/SNMP adapter.
- Adapter for remote management.
- Monitoring, management and shutdown software.
- 1 x additional RS-232/485 serial port.
- Extended backup times.
- Common battery set for parallel systems.
- BACS II, battery monitoring, regulation and alarms.
- Dual-level charger for NiCd batteries.
- Separate bypass line.
- Touch screen 7" color. ⁽¹⁾
- Single/single, single/three and three/single configurations. ⁽¹⁾
- External manual bypass.
- Temperature and humidity sensors.
- External display.
- Frequency converter function.

(1) Up to 30 kVA

Technical support and service

- Pre and post-sales advice.
- Start-up.
- Telephone technical support.
- Preventative/corrective intervention.
- Maintenance contracts.
- Remote maintenance contracts.
- Training courses.



Range

MODEL	CODE	POWER (VA / W)	N° CABINETS (UPS + BAT)	DIMENSIONS (D × W × H mm)	WEIGHT (Kg)	BAT DIMENSIONS (D × W × H mm)	BAT WEIGHT (Kg)
SLC-5-CUBE3+ A	681LF000022	5/4,5	1+0	775 × 450 × 1100	164	-	-
SLC-7,5-CUBE3+ A	681LF000011	7,5/6,75	-	775 × 450 × 1100	164	-	-
SLC-10-CUBE3+ A	681LF000009	10/9	1+0	775 × 450 × 1100	165	-	-
SLC-15-CUBE3+ A	681LF000049	15/13,5	-	775 × 450 × 1100	237	-	-
SLC-20-CUBE3+ A	681LF000050	20/18	-	775 × 450 × 1100	323	-	-
SLC-30-CUBE3+ A	681LG000001	30/27	1+1	775 × 450 × 1100	185	1050 × 650 × 1325	424
SLC-40-CUBE3+ A	681TG000001	40/36	1+1	880 × 590 × 1325	265	1050 × 650 × 1325	501
SLC-50-CUBE3+ A	681TG000002	50/45	1+1	880 × 590 × 1325	290	1050 × 650 × 1325	594
SLC-60-CUBE3+ A	681TG000003	60/54	1+1	880 × 590 × 1320	290	1050 × 650 × 1325	594
SLC-80-CUBE3+ A	681TG000004	80/72	1+1	850 × 900 × 1905	540	850 × 1305 × 1905	1096
SLC-100-CUBE3+ A	681TG000005	100/90	1+1	850 × 900 × 1905	550	850 × 1305 × 1905	1096

Nomenclature, dimensions and weights for units with input voltage 3 x 220 V, output voltage 3 x 220 V and standard backup time.

Dimensions



SLC-5÷30-CUBE3+ A




SLC-40÷60-CUBE3+ A



SLC-80/100-CUBE3+ A

Connections



SLC-5÷100-CUBE3+ A

1. Slot for card (option).
2. Internal protection fuses. 40kVA equipments only.
3. Communication interfaces.
4. Circuit breaker switch / Input switch.
5. Output switch.
6. Fuse holder / switch power.
7. Manual bypass.
8. Output terminals.
9. Input and output terminals.

salicru

Technical specifications

MODEL		SLC CUBE3+ A
TECHNOLOGY		On-line, double conversion, HF, DSP control
INPUT	Rated voltage	Single-phase 115 / 120 / 127 / 133 V ⁽¹⁾ / Three-phase 3 × 200 / 3 × 208 / 3 × 220 / 3 × 230 (3F + N)
	Voltage range	+15% / -20% (configurable)
	Rated frequency	50 / 60 Hz
	Total harmonic distortion (THDi)	100% load: <1.5% / 50% load: <2.5% / 10% load: <6.0%
	Power factor	1 from 10% load
	Rectifier topology	Three-phase IGBT full wave, soft start, PFC, transformerless
OUTPUT	Power factor	0.9
	Rated voltage	Single-phase 115 / 120 / 127 / 133 V ⁽¹⁾ / Three-phase 3 × 200 / 3 × 208 / 3 × 220 / 3 × 230 (3F + N)
	Dynamic accuracy	± 2% dynamic
	Static accuracy	± 1% steady
	Response time accuracy	20 ms for load steps 0% ÷ 100% and voltage drop up to -5%
	Total harmonic distortion (THDv)	<0.5% linear load / <1.5% (EN-62040-3) non-linear load
	Synchronised frequency	50/60 Hz ±5 Hz (selectable)
	Free running frequency	50/60 Hz ±0,05%
	Synchronous speed	From 1 Hz/s to 10 Hz/s (programmable)
	Total performance in On-line mode	5÷30 kVA: 90%÷92% / 40÷100 kVA: 92%÷93%
	Performance in Smart Eco-mode	Up to 98.4%
	Admissible overloads	125% for 10 min / 150% for 60 s / >150% for 20ms
	Crest factor	>3:1
MANUAL BYPASS	Type	No breaks
STATIC BYPASS	Type and activation criteria	Solid state, controlled by microprocessor
	Transfer times in Smart Eco-mode (ms)	4 ms (typical)
	Transfer times in On-line	Nil
	Transfer to bypass	Immediate, for overloads exceeding 150%
	Retransfer	Automatic, after alarm deactivation
BATTERY	Battery type	Lead acid, sealed, maintenance free
	Charging voltage regulation	Batt-Watch
COMMUNICATION	Ports	1 × RS232/RS485 + 1xUSB, with Modbus protocol
	Relay interface	4 × AC failure, bypass, low battery and general
	Intelligent slot	1, for SNMP
GENERAL	Operating temperature	0° C ÷ +40° C
	Relative humidity	Up to 95%, non-condensing
	Maximum operating altitude	2,400 masl
	Acoustic noise at 1 metre	<52 dB(A) ⁽²⁾
STANDARDS	Safety	EN-IEC 62040-1
	Electromagnetic compatibility (EMC)	EN-62040-2
	Operation	VFI-SS-11 (EN-62040-3)
	Quality and environmental management	ISO 9001 & ISO 14001

(1) Up to 30 kVA.

(2) <65 dB(A) for 40 to 60 kVA models / <70 dB(A) for 80 to 100 kVA models

Information subject to change without notice.

