

Lab 19 Web App SQL

Monica Um

Flavio Cervantes

Raquel Zuelke


CST 363-30_2252

Professor Arijit Das

June 10, 2025

ER Diagram

This diagram is designed to access and manage a patient's pharmaceutical prescriptions, doctors, and patient information. Both doctors and patients register by storing certain information about them. A unique ID is generated automatically for doctors and patients to help identify them and keep data integrity. The prescription table can be used to store the drug information issued by doctors. It has foreign keys referencing the doctor, patient, and drug tables. Patients are able to request their prescriptions using their RXID, which is how to identify the prescription, their name, and the pharmacy they go to. The refill table will keep track of refills to ensure it does not exceed the number the doctor prescribes. To help facilitate this, the Refill entity will keep track of the pharmacy that has filled it last, the date of the last refill, the number of drugs given, and the price charged by that specific pharmacy. This is accomplished by comparing the refill count with num_refills. The drug table proves the drug name of the needed prescription. This includes both the generic and non generic name. The drug_cost table will determine the price of the drug. The price of the drug varies from different pharmacies.



The SQL schema:

```

1 • drop database prescription;
2 • create database prescription;
3 • use prescription;
4
5 • create table doctor(
6     id int primary key auto_increment,
7     ssn varchar(9) not null unique,
8     last_name varchar(30) not null,
9     first_name varchar(30) not null,
10    specialty varchar(30),
11    practice_since int );
12
13 • create table drug (
14     id int primary key auto_increment,
15     name varchar(50) not null,
16     generic_name varchar(50));
17
18 • create table pharmacy (
19     id int primary key auto_increment,
20     name varchar(50) not null,
21     address varchar(50),
22     phone varchar(15));
23
24 • create table drug_cost (
25     id int primary key auto_increment,
26     drug_id int not null,
27     pharmacy_id int not null,
28     cost decimal(10,2) not null,
29     foreign key (drug_id) references drug(id),
30     foreign key (pharmacy_id) references pharmacy(id));
--
• create table patient (
    id int primary key auto_increment,
    ssn varchar(9) unique,
    first_name varchar(30),
    last_name varchar(30),
    birthdate date,
    street varchar(50),
    city varchar(50),
    state varchar(2),
    zipcode varchar(10),
    doctor_id int,
    foreign key (doctor_id) references doctor(id));

```

```
45 • ○ create table prescription (  
46     RXID int primary key auto_increment,  
47     doctor_id int not null,  
48     patient_id int not null,  
49     drug_id int not null,  
50     date_prescribed date,  
51     quantity int,  
52     refill int,  
53     foreign key (doctor_id) references doctor(id),  
54     foreign key (patient_id) references patient(id),  
55     foreign key (drug_id) references drug(id));  
  
57 • ○ create table refill (  
58     id int primary key auto_increment,  
59     RXID int not null,  
60     pharmacy_id int not null,  
61     fill_date date,  
62     quantity_dispensed int,  
63     price_charged decimal(10,2),  
64     foreign key (RXID) references prescription(RXID),  
65     foreign key (pharmacy_id) references pharmacy(id));  
  
67 • insert into drug (name, generic_name) values  
68     ('Claritin', 'Loratadine'),  
69     ('Tylenol', 'acetaminophen'),  
70     ('Zestril', 'Lisinopril');  
71  
72 • insert into pharmacy (name, address, phone) values  
73     ('Rite Aid', '1380 Barstow Rd, Barstow, CA', '760-252-3502');  
74  
75 • insert into drug_cost (drug_id, pharmacy_id, cost) values  
76     (1, 1, 9.99),  
77     (2, 1, 5.99),  
78     (3, 1, 7.99);
```

1)

Patient ID: 1
First Name:
Last Name: Simpson
Birthdate:
Street:
City: Rockville
State:
Zipcode: 62701
Primary Physican: Spock

[Edit](#) | [Main Menu](#)

2)

Register as new user

Doctor not found. Please check the last name.

Your SSN:

Your First Name:

Your Last Name:

Birth Date: 

Street:

City:

State:

Zipcode:

Primary Physician
Name:

3)

Prescription created.

Rx: 3
Doctor ID: 1
First Name:
Last Name: Spock
Patient ID: 1
First Name:
Last Name: Simpson
Drug: Lisinopril
Quantity: 90
Refills remaining: 0
Pharmacy ID: 0
Name:
Address:
Phone:
Date Filled:
Cost: \$

[Main Menu](#)

4)

New Prescription Form

Drug not found.

Doctor ID:

Doctor First
Name:

Doctor Last
Name:

Patient ID:

Patient First
Name:

Patient Last
Name:

Drug Name:

Quantity:

Number of refills:

Create Prescription

Request Prescription to be filled.

Pharmacy not found: walgreens

Rx:

Patient Last
Name:

Pharmacy
Name:

Pharmacy
Address:

5)

6) Attempt to fill a prescription with an invalid rxid.

Request Prescription to be filled.

Invalid RxID

Rx:

Patient Last
Name:

Pharmacy
Name:

Pharmacy
Address:

Prescription created.

Rx: 0
Doctor ID: 1
First Name:
Last Name: Spock
Patient ID: 1
First Name:
Last Name: Simpson
Drug: Lisinopril
Quantity: 90
Refills remaining: 0
Pharmacy ID: 0
Name:
Address:
Phone:
Date Filled:
Cost: \$

[Main Menu](#)

7)

8) Get the profile for patient "Simpson" and edit the patient record for "Simpson" and change city to Springfield and zip code to 61705. Show the web page of the successful update.

Patient found.

Patient ID: 1
First Name: BV
Last Name: Simpson
Birthdate: 2025-06-10
Street: Rockville st
City: Rockville
State: CA
Zipcode: 62701
Primary Physican: Spock

[Edit](#) | [Main Menu](#)