PRE-HOME INSPECTION CHECK-LIST

This list can also be looked at like a home Maintenance list.



Exterior	All siding should have at least 4" to 8" of space between the ground and siding.	1	Exterior	Clean out debris from gutters and insure they drain	E	Exterior	Remove debris from the roof (leafs, sticks, pine needles)	
Exterior	All water ways should be channeled away from the house. (Drains, downspouts, grade or topography.		Exterior	Trim trees branches and vegetation away from the foundation, roof, siding, and chimney.		Exterior	Paint all weathered exterior wood, and seal/caulk around trim, chimneys, windows and doors.	
HVAC	Furnace or Air handler filter is sized correctly and clean.		Exterior	Address any foundation cracks or stucco cracks.		Exterior	Firewood and debris should be moved as far away from the house.	
Exterior/Interior	Clean & service chimney, fireplace, and wood stoves.		Exterior/Interior	Any windows that are cracked should be repaired. This includes any glass in doors.		Exterior	Seal masonry chimney cap and/or install metal flue cap.	
Exterior/Interior	Replace any windows with broken seals (sweat between panes).		Exterior	HVAC condensor or Heat pump should operate correctly and vegetation is cut back 12" from unit. Condensor.		Electrical	Check for any burned out light bulbs and replace them.	
Garage	Check garage door for operation.	Coo Frada Hope Are Ho	Exterior	Make sure all downspouts are properly diverted away from the house, either with elbows and splash blocks or drain.		Utilities	Are all utilities ON? Including electric, water, and gas. Also, is breaker panel box unlocked, furnace is on, gas stove is lit	





All access Check panels and toilet(s) for doors to the Check all nterior plumbing proper attic. operation. crawlspace, fixtures, Also check heat systems, toilet, tub, for cracks, garage and shower, other areas sinks visible leaks, secured to should be leaks. floor, and clear. clean. Check water GFCI heater for any leaks, venting, (ground Smoke and fault circuit elements, carbon rust, and interrupter) • nterio monoxide operation. outlets in detectors are Electrical wire needed installed and is in shielded areas working. cable. (kitchens, Pressure relief bathrooms, valve drain to exterior outlets...) the outside. Check for **Plumbing** cracked Make sure all Clean dirty air HVAC sealant exhaust ducts around vents are tubs/shower working s and other (bathroom, fixtures. kitchen, laundry room...) Crawlspace/Attic Fix any damaged, Make sure all fallen floor Pets animals are insulation. secure or removed from the property. Stoves are working properly. Kitchen Anti-tip device installed.