

Bushing Cover for Various Switches

PRODUCT OVERVIEW

Designed to provide insulation and protection at the incoming and outgoing connection points of isolation switches, vacuum switches, and fuses. The snap-fastener design allows rapid field installation on energized adjacent equipment, reducing outage duration during commissioning and maintenance activities across distribution and industrial switchgear applications.

APPLICATIONS

- Isolation switch incoming and outgoing connection points
- Vacuum switch bushing interfaces
- Fuse connection insulation in distribution switchgear

KEY FEATURES

- Radiation cross-linked Polyolefin or EPDM rubber construction
- Operating temperature range: -40°C to 105°C
- Quick and easy snap-fastener installation — no special tooling required
- Eliminates risk of short circuit and leakage current
- Facilitates safe routine inspection and maintenance
- Moisture, dust, and contamination resistant
- RoHS compliant | ISO 9001 & ISO 14000 certified manufacturing
- Available in Red, Yellow, Green, and Black | Fully customizable

TECHNICAL DATA

Property	Polyolefin	EPDM	Test Method
Tensile Strength	≥10.0 MPa	≥10 MPa	ASTM D 2671
Elongation at Break	≥300%	≥1000%	ASTM D 2671
Thermo Aging Tensile Strength	≥6.9 MPa	≥9 MPa	90°C/70hrs
Thermo Aging Elongation at Break	≥150%	≥500%	90°C/70hrs
Heat Shock	No Cracking	No Cracking	JB7829
Oxygen Index	≥28	–	GB/T 2406
Dielectric Strength	≥20 kV/mm	≥30 kV/mm	IEC 243
Dielectric Constant	2–3	2–3	IEC 250
Volume Resistance	≥1×10 ¹¹ Ω·cm	≥4.5×10 ¹¹ Ω·cm	IEC 93

<p>STOCKING LOCATIONS Reno, NV · Houston, TX Custom reel lengths available</p>	<p>PROCUREMENT & INQUIRIES GCP Energy LLC — Authorized OEM Representative portal.gcpenergy.us · Salt Lake City, UT</p>	<p>MATERIAL OPTIONS Polyolefin (Standard) EPDM Rubber (High Flex / Submersible)</p>
---	---	--