

BUILT TO A HIGHER STANDARD[®]

American Standard[®]
HEATING & AIR CONDITIONING



RESIDENTIAL PRODUCTS



AIR CONDITIONERS



FURNACES



PACKAGED SYSTEMS



HEAT PUMPS



AIR HANDLERS



INDOOR AIR QUALITY



SMART THERMOSTATS



TRADITIONAL THERMOSTATS



COILS



Lower Global Warming Potential

Includes all new equipment that contains or is compatible with R-454B refrigerant.

AIR CONDITIONERS

ACCUCOMFORT™ VARIABLE SPEED



PLATINUM 20 5A7V0
Up to 23.6 SEER2/14.0 EER2†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Duration™ Variable Speed inverter compressor
- American Standard Link™ Connectivity
- Standard 4 wire connection, 2 wire optional



PLATINUM 18 5A7V8
Up to 18.1 SEER2/11.5 EER2

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Duration™ Variable Speed inverter compressor
- American Standard Link™ Connectivity
- Standard 4 wire connection, 2 wire optional



MULTI-SPEED



GOLD 17 5A7A7
Up to 17.1 SEER2†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- Swept fan blade
- Duration™ inverter compressor

SINGLE STAGE



SILVER 15 5A7A5
Up to 17.0 SEER2†

SILVER 14 5A7A4
Up to 14.3 SEER2

SILVER 13 5A7A3
13.4 SEER2

COMMON FEATURES:

- 1.5 – 5 ton
- Spine Fin™ coil
- Swept fan blade
- Duration™ compressor

3 PHASE



SILVER 14 5A7C4
Up to 16.0 SEER2

SILVER 13 5A7C3
13.4 SEER2

COMMON FEATURES:

- 3, 3.5, 4 & 5 ton
- Spine Fin™ coil

OPTIONAL



ALL WEATHER TOP

- BAYAWGR0003 - Fits Base sizes 33" x 30" (W X D)
- BAYAWGR0004 - Fits Base sizes 37" x 34" (W X D)



- ① Compressor
- ② Coil
- ③ Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

HEAT PUMPS

ACCUCOMFORT™ VARIABLE SPEED



PLATINUM 20 5A6V0
Up to 22.4 SEER2/13.0 EER2/10.5 HSPF2†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Duration™ Variable Speed inverter compressor
- American Standard Link™ Connectivity
- Standard 4 wire connection, 2 wire optional



PLATINUM 18 5A6V8
Up to 18.1 SEER2/11.5 EER2/8.5 HSPF2†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Duration™ Variable Speed inverter compressor
- American Standard Link™ Connectivity
- Standard 4 wire connection, 2 wire optional



MULTI-SPEED



GOLD 17 5A6H7
Up to 17.1 SEER2/11.0 HSPF2†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- Duration™ inverter compressor



SILVER 16 5HPL5
Up to 16.0 SEER2/8.1 HSPF2†

- Side Discharge
- 2, 3, 4 & 5 ton
- Copper tube aluminum fin coil

SINGLE STAGE



SILVER 15 5A6H5
Up to 17.0 SEER2/8.5 HSPF2†

SILVER 14 5A6H4
14.3 SEER2/7.5 HSPF2

COMMON FEATURES:

- 1.5 – 5 ton
- Spine Fin™ coil
- Duration™ compressor
- Compressor sound insulator (select models)

3 PHASE



SILVER 14 5A6C4
Up to 16.0 SEER2/8.1 HSPF2

- 3, 3.5, 4 & 5 ton
- Spine Fin™ coil

OPTIONAL



ALL WEATHER TOP

- BAYAWGR0003 - Fits Base sizes 33" x 30" (W X D)
- BAYAWGR0004 - Fits Base sizes 37" x 34" (W X D)



- ① Compressor
- ② Coil
- ③ Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

† This product meets ENERGY STAR requirements when appropriate coil components are used. Ask your dealer for details.

90%+ AFUE CONDENSING



PLATINUM 95 AUHM / ADHM

COMMUNICATING
Up to 97.3% AFUE

- 60 – 120 MBU input
- AccuLink™ capability
- Fully modulating gas valve
- Three-wire connections
- Variable-speed communicating ECM blower motor
- Continuous Comfort-R™ mode
- Single or two pipe vent options
- Digital user interface for easy set up and diagnostics
- Silicon nitride igniter
- Variable-speed draft inducer
- Certified to 2% air leakage
- ENERGY STAR® qualified



PLATINUM S9V2-VS

97% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Variable speed draft inducer

PLATINUM S9V2

96% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Two-speed draft inducer

GOLD S9X2

Up to 96% AFUE

- Compatible with 1 & 2 stage OD equipment
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer

COMMON 2-STAGE S-SERIES FEATURES INCLUDED

- 40 – 120 MBU input
- Two-stage heat
- Single or two pipe vent options
- Fully insulated/gasketed
- Dry contact Humidifier and EAC terminals
- Silicon nitride igniter
- Standard 34" height
- Certified to 1% air leakage
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified



SILVER S9X1

Up to 96% AFUE

- 40 – 120 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM motor
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated/gasketed
- Single or two pipe vent options
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified
- Certified to 1% air leakage



SILVER L9X1†

95% AFUE

- 50, 70, & 100 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Ultra-Low NOx Certified
- Silicon nitride igniter
- Fully insulated cabinet
- † California Only



SILVER S9B1

92.1% AFUE

- 40 – 120 MBU input
- Single-stage heat
- 9 tap Constant Torque ECM blower motor
- Single-speed draft inducer
- Silicon nitride igniter
- Single or two pipe vent options
- Stainless steel heat exchanger

80% AFUE NON-CONDENSING



PLATINUM S8V2-C

- 40 – 120 MBU input
- American Standard Link Communicating Capability
- Can be connected in communicating or 24V non-communicating modes
- Two-stage heat
- High efficiency, variable speed constant airflow blower motor
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Aluminized steel heat exchanger
- Compatible with AccuClean™



GOLD S8X2

- 40 – 120 MBU input
- Two-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Aluminized steel heat exchanger
- Compatible with AccuClean™



SILVER S8X1

- 40-120 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Humidifier & EAC terminals
- Certified to 1% air leakage



GOLD L8V1†

- 40 – 100 MBU input
- Single-stage heat
- Variable-speed blower motor
- Variable-speed draft inducer
- Ultra-Low NOx Certified
- Certified to 1% air leakage
- † California Only



SILVER S8B1

- 40-120 MBU input
- Single-stage heat
- 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Certified to 1.4% air leakage



SILVER L8X1†

- 55-100 MBU input
- Single-stage heat
- 5 tap Constant Torque ECM blower
- Ultra-Low NOx Certified
- 14 ng/J operation
- Silicon nitride igniter
- Fully insulated cabinet
- † California Only



- ① Heat Exchanger
- ② Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

*Relay panel required when matched with variable speed outdoor units
**14.5" models do not contain blower compartment insulation

COILS

CASED MULTI-POSITION



5TXC

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Enhanced fin design for efficiency and humidity control
- Double-sloped high temp drain pan
- All-aluminum to prevent formicary corrosion
- Factory installed Refrigerant Detection System



5MXC

- Single stage equipment only
- Fixed orifice
- TXV kit available for expanded ratings and applications (heat pump capable)
- All-aluminum to prevent formicary corrosion
- Shipped with Refrigerant Detection System



5PXC-U / 5PXC-D

U = Upflow/Downflow*
D = Downflow only**

(Optimized for downflow efficiency and ratings)

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Double-sloped high temp drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion
- Factory installed Refrigerant Detection System

*Convertible to horizontal left or right with kit.

**Convertible to horizontal right with kit.

UNCASED



5AXA

- TXV (heat pump capable)
- Single sloped non-corrosive drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion
- Single and 2-stage equipment only
- Shorter depth ideal for plenum placement
- Shipped with Refrigerant Detection System

CASED



5PXFH

- Single, 2-stage and variable speed equipment
- TXV (Heat pump capable)
- High temp drain pan
- All-aluminum to prevent formicary corrosion
- Factory installed Refrigerant Detection System



Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?

CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

AIR HANDLERS

FOREFRONT™



PLATINUM 5TAMX

- American Standard Link™ or 24V operation
- American Standard Link mobile app capability
- 2-5 ton
- Continuous AccuComfort™ mode
- Composite Vortica™ blower housing
- All-aluminum epoxy coated coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- Electronic expansion valve
- Variable-speed ECM blower motor
- Meets 2% air leakage requirements



GOLD 5TAM5

- 1.5-5 ton
- High efficiency four-speed ECM blower motor
- Composite Vortica™ blower housing
- All-aluminum epoxy coated coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- R-454B TXV
- Meets 2% air leakage requirements

METAL-STYLE



PLATINUM 5TEM6

- American Standard Link™



COMMON FEATURES FOR 5TEM6 AND 5TEM6:

- 2 - 5 ton
- 24V operation
- Variable-speed ECM blower motor
- All-aluminum coil
- Multi-position installation
- Metal Vortica™ blower
- Galvanized steel metal cabinet
- R-454B TXV
- Meets 2% air leakage requirements

GOLD 5TEM6



SILVER 5TEM4

- 2 - 5 ton
- ECM blower motor
- Metal Vortica™ blower
- All-aluminum coil
- Galvanized steel metal cabinet
- R-454B TXV
- Multi-position installation
- Meets 2% air leakage requirements

UPFLOW



SILVER 5TMM5

- 2 - 3 ton
- Upflow design with front and bottom return options
- ECM blower motor
- R-454B TXV
- Galvanized steel metal cabinet
- Meets 2% air leakage requirements
- All-aluminum coil

MODULAR AIR HANDLER



GOLD 120V MODULAR VARIABLE SPEED

POVO

- 34" cabinet height
- High efficiency, variable speed blower motor
- Fully insulated cabinet
- 4-way multi-poise
- Entirely electric operation
- 24V operation



① Coil
② Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?

CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

AMERICAN STANDARD ACCUCLEAN®



EFD

- Up to 100 times more effective than a standard 1" throwaway filter
- Power door provides easy access to internal components and features a filter status display as well as safety interlocks that automatically shut down the power when the door is opened for maintenance or cleaning
- Removes particles down to 0.3 micron in size
- Removes more than 99% of a surrogate for the virus that causes Covid-19 within 30 minutes
- AccuLink™ communicating or 24 volt capability
- Zero ozone emissions. Cleaner air without harmful ozone byproducts so you can breathe easier
- Allergy and Asthma Friendly® Certified
- Quiet operation



QUIKBOX™



EQBFM

- MERV 11 and MERV 13 filter options
- Quick shirt box type design
- Stores flat, installs in seconds
- 11 sizes to match most cabinet widths
- Backward compatible for all Perfect Fit (TFM) filter boxes
- New smaller cabinet to meet competitive brands
- Low pressure drop; up to 6 mos. lifecycle

SLIMFIT FILTER



BAYSF 1165, 1185, 1235, 1255

- 1" Pleated Filter, MERV 4 rated, lasts up to 90 days
- Made-to-fit cabinet sizes for TEM Air Handlers and S9V and S9X furnace side return cabinets
- 2" depth low profile painted steel cabinet with hinged door for easy filter replacement

EVAPORATIVE HUMIDIFIERS



EHUMD500

FAN POWERED

- Capacity: 18 gallons per day
- Sq. Ft. Capacity: Up to 4,200
- Unit Type: Power humidifier/automatic control



EHUMD300

LARGE BYPASS

- Capacity: 16.8 gallons per day
- Sq. Ft. Capacity: Up to 4,000
- Unit Type: Large bypass humidifier/automatic control

EHUMD200

SMALL BYPASS

- Capacity: 12 gallons per day
- Sq. Ft. Capacity: Up to 3,000
- Unit Type: Small bypass humidifier/manual control

STEAM HUMIDIFIER



EHUMD800

- Capacity: 11 – 34.6 gallons per day
- Sq. Ft. Capacity: Up to 5,000

EHUMD800LC

- For 120V applications only
- For low conductivity water applications
- Up to 11 gal. per day output
- Replaceable LC canister available

DEHUMIDIFIER



EDHUM70H

WATER REMOVAL:
70 Pints/Day
8.75 Gallons /Day



EDHUM98

WATER REMOVAL:
98 Pints/Day
12.25 Gallons /Day



EDHUM120

WATER REMOVAL:
120 Pints/Day
15.125 Gallons /Day

COMMON FEATURES:

- Features a horizontal configuration with optional vertical discharge
- Designed for quiet operation
- Engineered for low temperature operation providing comfort year round
- Optional digital controller for outdoor air ventilation and humidity control
- Superior MERV-13 filtration to improve indoor air quality
- Ducting options for fresh outdoor air ventilation to meet ASHRAE 62.2 ventilation requirements
- Push button reset for transformer protection

VENTILATION



PREMIUM ENERGY RECOVERY VENTILATION (ERV)

EERVE125, EERVE225, EERVE280

COMMON FEATURES:

- Efficient heat and humidity transfer recaptures up to 70-80% of the energy exhausted from the airstream
- Dial-A-Flow adjustment for simple air flow balancing
- 2 high-efficiency variable speed EC motors, meet California energy codes
- Multi position mounting
- Compact design and reduced weight for easier installation vs alternatives
- MERV 8 standard, MERV 13 filter options available
- High-efficiency core operates dry in all conditions, no condensate pans needed
- Energy-efficient operation decreases HVAC load, cutting down on energy use and costs



ENERGY RECOVERY VENTILATOR (ERV)

EERV100, EERV200, EERV300

COMMON FEATURES:

- Multi-position mounting
- Up to 78% sensible heat recovery
- High efficiency crossflow energy transfer core
- Slide out filter
- Percent timer control included
- Permanently lubricated ball bearing fan motor



INLINE VENTILATOR

- 62.2 Compliant Ventilation
- Full ECM Motor with Intelligent Logic Controller
- Adjustable airflow from 30 to 130 cfm to meet ventilation codes for all size homes
- 24V functionality from a smart thermostat, or use the on-board controller for "set-it and forget it" installation
- MERV 8 filter included for improved IAQ



Functional
Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

SMART THERMOSTATS

CONNECTED CONTROLS



LINK360 UX360, SC360 SMART THERMOSTAT & SYSTEM CONTROLLER

- American Standard Link™ Zoning Systems
- Remote wired temperature sensor available through the hub
- Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AWO00MA
- Remote Climate Access with American Standard Home™ app
- American Standard Technician app compatibility allows for easy technician commissioning and servicing
- Compatible with 24V Indoor Equipment
 - 5 heat / 2 cool
 - 3 dry auxiliary contacts***
 - Remote ID, OD sensor connections
- WiFi connectivity
- Control from a smartphone, tablet, or computer
- Customizable home screen
- Runtime history
- 7" diagonal color touchscreen
- 1-Touch Presets - Home, Away, Sleep
- 7 Day programmable with up to four schedules per day
- Smart Continuous Fan
- Adjustable Continuous Airflow (35-100%)
- Five day weather forecast
- Indoor relative humidity display
- Test modes and alert diagnostics
- Over-the-air Software Upgrades
- Color: Designer White

Link™

Home™



ACCULINK™ PLATINUM 1050 AZON1050

- AccuLink™ II communications
- AccuLink™ II zoning
- Compatible with 24 volt systems*
 - 5 heat / 2 cool
 - 3 dry auxiliary contacts***
 - Remote ID, OD sensor connections
- Remote Climate Access with American Standard Home™ App
- Built in Bridge for Z-Wave devices
- American Standard Diagnostics ready
- WiFi connectivity
- Control from a smartphone, tablet, or computer
- 7" diagonal color HD display
- 1-touch presets - Home, Away, Sleep
- 7-day programmable with up to four schedules per day
- Integrated Dehumidification Solution
- Customizable home screen
- Runtime history
- Allergy and quick clean air cycles
- Smart continuous fan
- Adjustable continuous airflow
- Ventilation control*
- Service, filter, humidifier, UV light, air cleaner reminders
- 5-day weather forecast, weather radar, and alerts
- Indoor relative humidity display
- Test modes and alert diagnostics
- Over-the-air Software Upgrades
- BK Terminal for humidity control
- Color: Designer Silver

Home™



AZON1040 AZON1040AC52ZA ZONING COMMUNICATING SENSOR WITH DISPLAY

- For use with AccuLink™ II Zoning Systems (Platinum 1050 required)
- 3-Wire Communicating Zone Sensor
- 4.3" diagonal color touchscreen
- Zone Mode - Auto only
- Fan Mode - Auto/On
- Displays Zone Temperature & Relative Humidity
- Average multiple zone temp sensors
- Displays Outdoor Temperature (American Standard Home™ registration or wired ODT required)
- Clean Screen Function
- 3 Levels of Restricted Access
- Fahrenheit or Celsius
- Adjust zone Setpoint at 1040, 1050, and from the American Standard Home app
- Schedule 1040, 1050, and from the American Standard Home app
- Zone Schedule Override - Permanent Hold
- Enter zone name at 1040 and 1050
- Local software upgrades
- Screen color with backlit options
- Screensaver options
- Color: Designer Silver



ACCULINK™ PLATINUM 850 ACONT850

- Remote Climate Access with American Standard Home™ App
- Built in Bridge for Z-Wave devices
- AccuLink™ II communications
- WiFi connectivity
- American Standard Diagnostics ready
- Compatible with 24 volt systems*
 - 5 heat / 2 cool
- 7-day programmable with up to four schedules per day
- 4.3" diagonal color display
- Dual Fuel Capable
- Filter change reminders
- 5-day weather forecast, weather radar, and alerts
- Integrated Dehumidification Solution
- Allergy and quick clean air cycles
- Ventilation control*
- Maintenance reminders
- Customizable home screen
- Over-the-air Software Upgrades
- Color: Designer Silver

Home™



SILVER 724 ACONT724

- Remote Climate Access included**
- American Standard Diagnostics ready
- 4 heat/2 cool
- 4.3" diagonal LCD touchscreen
- Screen lock out and guest lock out
- Built-in humidity sensor
- 1 aux dry contact*
- Dehumidification setting
- Dual Fuel capable
- Filter, maintenance and humidifier service reminder alerts
- Wi-Fi connectivity**
- Color: Silver

Home™



GOLD 824 ACONT824

- ENERGY STAR® certified
- Remote Climate Access with American Standard Home™ App
- Built in Bridge for Z-Wave devices
- WiFi connectivity
- American Standard Diagnostics ready
- Used with conventional 24 volt systems (non-communicating)
 - 5 heat / 2 cool
 - 2 aux dry contacts***
- 7-day programmable
- 4.3" diagonal color display
- Dual Fuel Capable
- Filter change reminders
- 5-day weather forecast, weather radar, and alerts
- Humidity sensor
- Integrated Dehumidification Solution
- Allergy and quick clean air cycles
- Ventilation control*
- Maintenance reminders
- Customizable home screen
- Over-the-air Software Upgrades
- Color: Designer Silver

Home™

* BAY24VRPAC52DC Relay Panel required.

** Complimentary Service (no monthly service fee) for up to 8 professionally installed American Standard smart thermostats. Complimentary service includes up to 1 lighting or appliance module per thermostat (max 4) installed. Unlimited American Standard Home™ Wi-Fi cameras (live streaming only) is included with complimentary American Standard Home™ remote climate access. Cameras and lighting controls are optional purchase.

*** Auxiliary dry contacts may be configured to control 1) whole house humidifier; 2) dehumidifier; 3) ventilation system.

**** BAC24VRPA252UA Link Relay Panel required

SENSORS



ZZSENSAL 0400 WIRED INDOOR TEMPERATURE SENSOR

- Compatible with American Standard Link™ Zone Panel (ZZON2PNL)
- Indoor sensor for use with AZON1050 ACONT624 ACONT824 ACONT850

Link™



BAYSENS01 WIRED OUTDOOR TEMPERATURE SENSOR

- Outdoor sensor for use with AZON1050 ACONT624 ACONT824 ACONT850

Home™

ZSENS930 INDOOR WIRELESS TEMPERATURE AND HUMIDITY SENSOR

- Z-Wave device
- LINK360 compatible
- Monitor through American Standard Home™ mobile app
- Integrates with built-in Bridge of AZON1050 ACONT850 ACONT824



Functional
Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?

CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

BUILT TO A HIGHER STANDARD

American Standard
HEATING & AIR CONDITIONING

TRADITIONAL THERMOSTATS

7-DAY OR 5/1/1 PROGRAMMABLE



SILVER 303 ACONT303

- 4 heat/2 cool
- Humidity sensor
- Dual fuel capable

COMMON FEATURES

- 5" Interactive touch screen
- Auto changeover
- Real-time clock

SILVER 302 ACONT302

- 4 heat/2 cool
- Dual fuel capable

- Large back lit display
- Armchair programming
- Air filter reminder



SILVER 203 ACONT203

- 4 heat/2 cool
- Dual fuel capable

COMMON FEATURES

- 3.5" Diagonal backlit display
- Simple programming
- Standard wiring terminal block



SILVER 202 ACONT202

- 1 heat/1 cool

- Simultaneous display
- Soft key controls

NON-PROGRAMMABLE



SILVER 103 ACONT103

- 2 heat/1 cool HP only
- Configurable Switchover Valve
- Emergency Heat
- Common required

COMMON FEATURES

- Push button, non-programmable
- 1.9" Diagonal display
- Fahrenheit or Celsius



SILVER 102 ACONT102

- Up to 1 heat/1 cool
- No Common Terminal
- Battery Powered Only

SENSORS



ZZSENSAL0300

WIRED INDOOR TEMPERATURE SENSOR

- Indoor sensor for use with ACONT303 ACONT302

BAYSEN30ATEMPA

WIRED OUTDOOR TEMPERATURE SENSOR

- Outdoor sensor for use with ACONT303 ACONT302



Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?

CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE

PACKAGED

HEAT PUMPS



GOLD 15 5WCZ5

Up to 15.2 SEER2/8.1 HSPF

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- 2-stage Duration™ compressor
- Variable-speed indoor blower motor
- Comfort-R mode
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- AccuClean® Compatible (horizontal only)



GOLD 15 3-PH 5WCZ5

Up to 15.2 SEER2/8.1 HSPF

- 3, 4 and 5 ton
- 3-Phase only (208v/230v & 460v)
- 2-stage Duration™ compressor
- Variable-speed indoor blower motor
- Comfort-R™ mode
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- AccuClean® compatible (horizontal only)

SILVER 14 5WCC4

13.6 SEER2/7.0 HSPF2

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- Duration™ compressor
- Spine Fin™ condenser
- Tough corrosion and UV resistant paint
- Composite Vortica™ blower
- Demand defrost
- AccuClean® compatible (horizontal only)

Silver 14 3-PH 5WCC4

Up to 13.6 SEER2/7.0 HSPF

- 3, 4 and 5 ton
- 3-Phase only (208v/230v & 460v)
- Duration™ compressor
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- AccuClean® compatible (horizontal only)

GAS/ELECTRIC



GOLD 15 5YCZ5

Up to 15.2 SEER2/81% AFUE

- 2, 2.5, 3, 3.5 and 5 ton
- 1-Phase only (208v/230v)
- Duration™ compressor
- 2-stage gas heat
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Ultra quiet
- Tough corrosion and UV resistant paint
- All stainless steel heating system
- AccuClean® compatible (horizontal only)



GOLD 15 3-PH 5YCZ5

Up to 15.2 SEER2/81% AFUE

- 3, 4, and 5 ton
- 3-Phase only (208v/230v & 460v)
- 2-stage Duration™ compressor
- 2-stage gas heat
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Tough corrosion and UV resistant paint
- All stainless steel heating system
- Ultra quiet
- AccuClean® compatible (horizontal only)

SILVER 14 5YCC4

Up to 14.3 SEER2/81% AFUE

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase only (208v/230v)
- Duration™ compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV resistant paint
- AccuClean® compatible (horizontal only)

SILVER 14 3-PH 5YCC4

Up to 14.3 SEER2/81% AFUE

- 3, 4 and 5 ton
- 3-Phase only (208v/230v & 460v)
- Duration™ compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV resistant paint
- AccuClean® compatible (horizontal only)

AIR CONDITIONER



SILVER 14 5TCC4

14.3 SEER2

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase Only (208v/230v)
- Duration™ compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- AccuClean® Compatible (horizontal only)


EarthWise™ Hybrid Comfort System



GOLD 15 5DCZ5

Up to 15.2 SEER2/8.1 HSPF

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase Only (208v/230v)
- 2-stage Duration™ compressor
- Variable-speed indoor blower motor
- Spine Fin™ condenser
- Comfort-R™ mode
- Composite Vortica™ blower
- Heat pump and/or 2-stage gas heat operation
- All stainless steel heating system
- Ultra quiet
- AccuClean® Compatible (horizontal only)



Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

Limited Warranty Term for American Standard Products Installed in Commercial Applications: Coil, Parts – 1 year Limited Warranty; Compressor – 5 years Limited Warranty; Packaged Unit Heat Exchanger – 5 years

Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL AMERICAN STANDARD REPRESENTATIVE