

Hunting - Drill stem specifications and dimensional information.

Hunting - Drill stem specifications and dimensional information.														
	Part Number	Tube Diameter (in) Wall (in)	Tube Diameter (mm) Wall (mm)	Connection (Thread Size)	Tool Joint OD in (mm)	Weight lb (kg)	Length ft (m)	Bend Radius ft (m)	%Slope per rod	Torque Rating ft-lb (Nm)	Fits Drill Model:			
One Piece Forged	HIWS1	HI216490	1.660 / .191	42.2 / 4.9	200	1.875 (47.6)	21 (9.5)	5 (1.5)	95.5 (29.1)	5.2%	1,500 (2034)	TT4X, JT5		
		HI216492	1.660 / .191	42.2 / 4.9	200	1.875 (47.6)	26 (11.8)	6 (1.8)	95.5 (29.1)	6.2%	1,500 (2034)	D9x13, JT10		
		HI230993	1.900 / .240	48.3 / 6.1	250	2.125 (54.0)	55 (24.9)	10 (3.0)	98.7 (30.1)	10.2%	2,300 (3118)	D20x22		
		HI221628	2.063 / .260	52.4 / 6.6	400	2.250 (57.2)	62 (28.1)	10 (3.0)	102 (31.1)	9.8%	2,700 (3661)	D23x30		
		HI222276	2.375 / .254	60.3 / 6.5	600	2.625 (66.7)	76 (34.5)	10 (3.0)	108 (32.9)	9.3%	4,200 (5694)	D24x40, JT30		
		HI296309599*	2.375 / .295	60.3 / 7.5	650	2.750 (69.9)	84 (38.1)	10 (3.0)	108 (32.9)	9.3%	5,500 (7457)	D36x40		
		HI296312531*	2.375 / .295	60.3 / 7.5	650	2.750 (69.9)	115 (52)	15 (4.6)	108 (32.9)	13.9%	5,500 (7457)	D36x40		
		HI296309521	2.625 / .400	66.7 / 10.2	700	3.100 (78.7)	117 (53)	10 (3.0)	145 (44.2)	6.9%	6,000 (8135)	D40x55		
		HI296309522	2.625 / .400	66.7 / 10.2	700	3.100 (78.7)	165 (75)	15 (4.6)	145 (44.2)	10.4%	6,000 (8135)	D40x55, JT40		
		HI222451*	2.875 / .392	73.0 / 10.0	900	3.250 (82.6)	120 (54)	10 (3.0)	169 (51.5)	5.8%	9,300 (12609)	D60x90		
		HI222452	2.875 / .392	73.0 / 10.1	900	3.250 (82.6)	180 (82)	15 (4.6)	169 (51.5)	8.7%	9,300 (12609)	D60x90, JT60		
		HI222454	3.500 / .449	88.9 / 10.4	800	3.625 (92.1)	250 (113)	15 (4.6)	197 (60.1)	7.5%	12,000 (16270)	D80x100		
HI296337977	3.500 / .476	88.9 / 12.1	1000	4.375 (111.1)	265 (120)	15 (4.6)	197 (60.1)	7.5%	15,000 (20337)	D100x140				
HI296309520	3.500 / .476	88.9 / 12.2	1000	4.375 (111.1)	351 (159)	20 (6.1)	197 (60.1)	10.2%	15,000 (20337)	D100x140				
One Piece Forged	HXT™	HI281600*	2.063 / .260	52.4 / 6.6	402	2.500 (63.5)	63 (28.6)	10 (3.0)	102 (31.1)	9.8%	3,300 (4474)	JT2020		
		HI294566	2.375 / .295	60.3 / 7.5	602	2.750 (69.9)	81 (36.7)	10 (3.0)	108 (32.9)	9.3%	5,000 (6779)	DD4045		
		HI284153	2.375 / .295	60.3 / 7.6	602	2.750 (69.9)	115 (52)	15 (4.6)	108 (32.9)	13.9%	5,000 (6779)	D36x44		
		HI294642	2.625 / .400	66.7 / 10.2	602	2.750 (69.9)	160 (73)	15 (4.6)	145 (44.2)	10.4%	5,000 (6779)	D36x50		
		HI276305	2.625 / .400	66.7 / 10.2	702	3.375 (85.7)	164 (74)	14.8 (4.5)	145 (44.2)	10.0%	7,000 (9491)	JT4020M1		
		HI276307*	2.875 / .440	73.0 / 11.2	902	3.875 (98.4)	198 (90)	15 (4.6)	169 (51.5)	8.9%	13,000 (17626)	D55x100		
		HI350802015	3.500 / .449	88.9 / 10.4	802	4.125 (104.8)	260 (118)	15 (4.6)	197 (60.1)	7.5%	18,000 (24405)	JT100		
		HI276376	3.500 / .449	88.9 / 10.4	802	4.125 (104.8)	327 (148)	20 (6.1)	197 (60.1)	10.1%	18,000 (24405)	D100x120		
		HI296100215	3.500 / .476	88.9 / 12.1	1002	4.375 (111.1)	260 (118)	15 (4.6)	197 (60.1)	7.5%	24,000 (32540)			
		HI296100220	3.500 / .476	88.9 / 12.1	1002	4.375 (111.1)	327 (148)	20 (6.1)	197 (60.1)	10.1%	24,000 (32540)			
		One Piece Forged	Ditch Witch®	355-1106	2.060 / .295	52.3 / 7.5	1.94-4	2.625 (66.7)	68 (30.1)	10 (3.0)	109 (32.2)	9.2%	2,000 (2980)	JT20
				355-1244	2.375 / .300	60.3 / 7.6	2.11-4	2.760 (70.1)	81 (36.7)	9.8 (3.0)	123 (37.5)	8.0%	4,000 (5420)	JT25, JT30
359-1211	2.835 / .313			72.0 / 8.0	2.10-4	3.125 (79.4)	140 (63.5)	15 (4.6)	146 (44.5)	10.3%	5,500 (7457)	JT40		
Lined	HI216492L		1.660 / .191	42.2 / 4.9	200	1.875 (47.6)	24 (10.9)	5 (1.5)	95.5 (29.1)	5.2%	1,500 (2034)	TT4X, JT5		
	HI216492L		1.660 / .191	42.2 / 4.9	200	1.875 (47.6)	29 (13.2)	6 (1.8)	95.5 (29.1)	6.2%	1,500 (2034)	D9x13, JT10		
	355-1106L		2.060 / .295	52.3 / 7.5	1.94-4	2.625 (66.7)	73 (33.1)	10 (3.0)	109 (32.2)	9.2%	2,000 (2980)	JT20		
	355-1244L		2.375 / .300	60.3 / 7.6	2.11-4	2.760 (70.1)	86 (39.0)	9.8 (3.0)	123 (37.5)	8.0%	4,000 (5420)	JT25, JT30		
Welded	Advantage®		A216492	1.660 / .191	42.2 / 4.9	200	1.875 (47.6)	26 (11.8)	6 (1.8)	99.0 (30.2)	6.1%	1,500 (2034)	D9x13, JT10	
			A221628	2.063 / .260	52.4 / 6.6	400	2.250 (57.2)	62 (28.1)	10 (3.0)	107 (32.6)	9.4%	2,700 (3661)	D23x30	
			A222276	2.375 / .254	60.3 / 6.5	600	2.625 (66.7)	76 (34.5)	10 (3.0)	123 (37.5)	8.1%	4,200 (5694)	D24x40, JT30	
			A355-1149	1.600 / .190	40.6 / 4.8	1.30-5	2.000 (50.8)	27 (12.3)	6 (1.3)	82 (25.0)	7.3%	1,100 (1491)	JT9, JT10	
		A355-1106	2.060 / .295	52.3 / 7.5	1.94-4	2.625 (66.7)	68 (30.8)	10 (3.0)	107 (32.6)	9.4%	2,200 (2983)	JT20		
		A355-1244	2.375 / .300	60.3 / 7.6	2.11-4	2.760 (70.1)	81 (36.7)	9.8 (3.0)	123 (37.5)	8.0%	4,000 (5420)	JT25, JT30		
		A355-1200	3.500 / .393	89.0 / 10	3.27-4	4.000 (102)	228 (103.4)	14.8 (4.5)	205 (62.5)	7.2%	12,000 (16270)	JT100		
AT	355-1050-500	3.630 / .313	92.2 / 8.0	3.44-4	4.500 (114.3)	302 (137)	14.1 (4.3)	205 (62.5)	6.9%	12,000 (16270)	AT100			