ARI STOCK LIST - February 3rd, 2025



Model	IMM Range	Туре	Vertical Stroke	Traverse Stroke	Strip Stroke	Payload	Location	Qty
MaxA05-800/1000	50 - 280 Tons	3-Axis Single Stage	39.37 in (1,000 mm) 31.49 in (800 mm)	70.86 in (1,800 mm) 55.11 in (1,400 mm)	39.37 in (1,000 mm) 31.49 in (800 mm)	11.0 lbs (5 kg)	MA, On Order	8
MaxAW05-1100	150 - 280 Tons	3-Axis Telescoping	43.3 in (1,100 mm)	70.86 in (1,800 mm)	39.37 in (1,000 mm)	11.0 lbs (5 kg)	MA, On Order	4
MaxBW08-1300	320 - 650 Tons	3-Axis Telescoping	51.18 in (1,300 mm)	78.74 in (2,000 mm)	47.24 in (1,200 mm)	22.0 lbs (10 kg)	MA, On Order, In Transit	8
MaxBW08-1300+AC	320 - 650 Tons	5-Axis Telescoping	51.18 in (1,300 mm)	78.74 in (2,000 mm)	47.24 in (1,200 mm)	22.0 lbs (10 kg)	SC, On Order, In Transit	7
MaxBW10-1500	500 - 800 Tons	3-Axis & 5-Axis Telescoping	59.05 in (1,500 mm)	98.42 in (2,500 mm)	55.11 in (1,400 mm)	22.0 lbs (10 kg)	MA, On Order, In Transit	19
MaxBW15-1700	600 - 1200 Tons	3-Axis & 5-Axis Telescoping	66.92 in (1,700 mm)	98.42 in (2,500 mm)	55.9 in (1,420 mm)	33.0 lbs (15 kg)	On Order	4
MaxCW15-2000	650 - 1300 Tons	3-Axis & 5-Axis Telescoping	78.74 in (2,000 mm)	118.11 in (3,000 mm)	69.29 in (1,760 mm)	33.0 lbs (15 kg)	MA, On Order, In Transit	15
MaxGW25-2500	1400 - 2400 Tons	3-Axis Telescoping	98.42 in (2,500 mm)	157.48 in (4,000 mm)	70.86 in (1,800 mm)	55.1 lbs (25 kg)	MA, On Order	6
X-650 Picker	100 - 180 Tons	Sprue Picker Single Stage	25.59 in (650 mm)	N/A	4.72 in (120 mm)	4.4 lbs (2 kg)	In Transit, On Order	6
XW-800 Picker	120 - 250 Tons	Sprue Picker Telescoping	31.49 in (800 mm)	N/A	7.87 in (200 mm)	6.6 lbs (3 kg)	MA, On Order, In Transit	6
XW-900 Picker	200 - 300 Tons	Sprue Picker Telescoping	35.43 in (900 mm)	N/A	7.87 in (200 mm)	6.6 lbs (3 kg)	MA, In Transit	5
XW-1000 Picker	250 - 380 Tons	Sprue Picker Telescoping	39.37 in (1,000 mm)	N/A	11.81 in (300 mm)	6.6 lbs (3 kg)	MA, In Transit	6