

Stockwell 2.0

Spec Sheet



General Product Specification

Dimensions (H/W/D)	57 Inch / 60 Inch / 24 Inch
Weight	181 Kg (400 lbs)
Power Input	NAMA compliance Dry compartment, technology (PC, Pico device, OptConnect, Cameras) 0.5A 115V AC Refrigerated compartment 1.6A 115V AC Two power outlets are required for this device: one for the technology and dry compartment, and one for the refrigerator compartment.
Connectivity	Optconnect, a dual SIM cellular router. (<i>Stockwell PC and Pico Reader are hard-lined to Optconnect</i>)
Hardware	Actineon Wiisper 10 PC with 12 USB Ports OptConnect Neo mobile router with 2 ethernet ports 1 Pico Payment Terminal Credit Card Device - <i>Device Accepts: ApplePay, GooglePay, Credit/Debit Cards, GMA/Connect & Pay</i>

POS Terminal Specification

CPU / OS	High performance MCU / Android 7.x and later
Display / Touch	5" TFT Color Display (1280 x 720) Capacitive Touch
Contactless Reader	ISO14443 type A/B, ISO 18092 Mifare, Felica VISA PayWave, MasterCard PayPass, AMEX ExpresPay, Discover D-PAS, Inerac Flash, CUP QuickPass, JCB J-speedy
MSR Reader	Vertical Swipe
ICC at bottom	Card insert upward
Front Camera	5 Megapixel
Communication	4G LTE (US band) 4G LTE Band 2,4,5,7,12,13,25,26 Need to meet AT&T criteria
Antenna	4G: External
Audio	Speaker / Microphone / Audio Jack (4 pole)
Barcode Reader	Newland EM2096 300 pixel projects bright red light beam

