

ABSOLUTELY NO ALCOHOL IN THE PITS!!!

Anyone who is found drinking in the pits will be asked to surrender their pit pass and escorted from the pits. Any driver found to be consuming alcohol will be immediately disqualified from competition.

Class is open to all 4 cylinder and fwd 6 cylinder cars. 4 cylinder Awd cars may remain awd. Drivers must be between the ages of 12 & 15 and have notarized minors release, adult rider is encouraged. Cars must remain stock, if you don't see it in the rules below don't do it!! Absolutely no welding anywhere for any reason other than what listed in the rules!! Aftermarket shifters will be permitted.

BUMPER) Any oem car bumper may be used, no loaded or homemade bumpers, a 5x5 1/4" plate may be welded to the end of the frame

and bumper may be welded to plate. You may trim the front frame rails to square them off to mount plate but core support must remain in place. DO NOT GET CARRIED AWAY, YOU WILL BE LOADED.

SUSPENSION) All suspension components must remain stock. A 1 1/2" bolt may be welded to the strut rod for bumper height, NO other welding or reinforcing of suspension or steering components will be permitted.

CAGE) All cars must have a spreader bar running from post to post behind the front seat, 2" min to 4" max diameter tubing, or a simple 4 point cage. Cage must have 5" of clearance from highest part of the floor. Side bars of cage may not be butted tight to firewall and may extend no further back than the kick panel. Gas tank may be mounted off

of the cage but must maintain the same 5" of clearance from the floor as well as the package tray/ speaker deck area.

GAS TANKS) You can run the factory tank in the factory location but it must be wired or chained in place (that is in addition to the factory tank straps). If you choose to move the tank to the back seat area you must use a metal tank or fuel cell. Tank must be bolted securely, no self tapping screws, bungee cords, ratchet straps. Factory tank can not be relocated, if you're not using the factory tank it must either be removed completely or have a large/ multiple holes drilled in it.

Battery) 1 battery per car. Battery can be moved into the front passenger side floor board, or mounted to cage, and must be safely secured to the floor board using a metal battery box or to the cage to accommodate the rider.

Tires) Any air filled tire will be permitted. Tires may be tubed and/or doubled. A simple valve stem protector will be allowed. No solid tires permitted.

Hood/trunk/doors) hood and trunk can be secured 4 places each using 9 wire(2 wraps per location) or no bigger than 3/8 chain. Doors may be wired or chained in 2 locations per door. Drivers/riders doors only may be welded using no more than 4 4x4 1/4 thick plates. Trunk lid may have a simple tuck, can not be attached to trunk floor pan. Quarter panels must remain vertical, no dishing or canoeing the trunk. No creasing or enhancing of body lines. You may have 2 windshield bars, sheet metal to sheet metal only, Bars may be bolted or welded in place.

