

## Bumper swap compact

Class is open to all 4 cylinder and fwd 6 cylinder cars. Awd cars may remain awd. Cars must remain stock, if you don't see it in the rules below don't do it!! Absolutely no welding anywhere for any reason other than what listed in the rules!! No aftermarket shifters , steering columns, or pedals will be permitted!!

BUMPER) Any oem car bumper may be used, no loaded or homemade bumpers, a 5x5 1/4" plate may be welded to the end of the frame and bumper may be welded to plate. You may trim the front frame rails to square them off to mount plate but core support must remain in place. DO NOT GET CARRIED AWAY, YOU WILL BE LOADED.

SUSPENSION) All suspension components

must remain stock. The single exception being you may use a u bolt style cable clamp on the strut rod to gain bumper height, this is the only approved method to adjust bumper height. A max height of 14" from ground to bottom of bumper will be allowed. Do not weld!!

CAGE) All cars must have a spreader bar running from post to post behind the front seat, 2" min to 4" max diameter tubing, or a simple 4 point cage. Cage must have 5" of clearance from highest part of the floor. Side bars of cage may not be butted tight to firewall and may extend no further back than the kick panel. Gas tank may be mounted off of the cage but must maintain the same 5" of clearance from the floor as well as the package tray/ speaker deck area.

GAS TANKS ) You can run the factory tank in the factory location but it must be wired or chained in place ( that is in addition to the factory tank straps). If you choose to move the tank to the back seat area you must use a metal tank or fuel cell. Tank must be bolted securely, no self tapping screws, bungee cords, ratchet straps. Factory tank can not be relocated, if you're not using the factory tank it must either be removed completely or have a large/ multiple holes drilled in it.

Battery) 1 battery per car. Battery can be moved into the front passenger side floor board and must be safely secured to the floor board using a metal battery box.

Tires) DOT stamped street tires only! Tires may be tubed and/or doubled. A simple valve stem protector will be allowed. No skid steer, ag, or solid tires permitted.

Hood/trunk/doors) hood and trunk can be secured 4 places each using 9 wire(2 wraps per location) or no bigger than 3/8 chain. Doors may be wired or chained in 2 locations per door. Drivers door only may be welded using no more than 4 4x4 1/4 thick plates. Trunk lid may have a simple, can not be attached to trunk floor pan. Quarter panels must remain vertical, no dishing or canoeing the trunk. No creasing or enhancing of body lines.