

Features

- 16 Channel Video Recorder H.265/H.265+
- Support HD-TVI / AHD/ ANALOG / CVI / IP input (5-in-1)
- 1-4 Channel support up to 3MP HD-TVI input
- Up to 2-Ch 4MP IP Cameras input
- Support Live View, Storage, Playback up to 16 HD-TVI/Analog Cameras + 2 IP Cameras
- Up to 4K (3840X2160) HDMI Video Output
- CVBS Output
- 2 SATA up to 16TB HDD
- 1 USB 2.0, 1 USB3.0
- 1080P@30fps with LTS efficient mode on



Specifications

Model Name	TVI-DVR8516K-ET
Video Compression	H.265+
Audio Compression	G.711u
IP Video Input	2-ch, Up to 4 MP resolution, supports H.265+/H.265/H.264 Zip+/H.264 IP cameras
HD-TVI Input	3 MP, 1080p30,1080p25, 720p60, 720p50,720p30,720p25 Note: The 3 MP signal input is only available for channel 1/2/3/4
Support	HDCVI, AHD, 1080p25, 1080p30, 720p25, 720p30
CVBS Input	Support
Simultaneous Playback	16CH
Audio Input	1-ch, RCA (2.0 Vp-p, 1 Kohm)
HDMI VGA Output	VGA: 1-ch, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz HDMI: 1-ch, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60Hz, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
Encoding Resolution	When 1080p Lite mode not enabled: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF; When 1080p Lite mode enabled: 3 MP/1080p lite/720p lite/VGA/WD1/4CIF/CIF

CVBS Output	1-ch, BNC (1.0 Vp-p, 75 kohm), resolution: PAL: 704 x 576, NTSC: 704 x 480
USB interface	Front panel: 1 xUSB 2.0, Rear panel: 1 xUSB 3.0
Two Way Audio Input	1-ch, RCA (2.0 Vp-p, 1 Kohm) (using the1st audio input)
Capacity	2 SATA/ Up to 8TB capacity for each disk
Casing	1U
Power supply	12 VDC
Consumption	<= 25W
Operating Temperature	-10 deg.C ~ +55 deg.C(14deg.F - 131deg.F)
Product Dimension	380 x 320 x 48 mm (15.0 x 12.6 x 1.9 inch)
Product Weight	<=2 kg (4.4 lb)