



## BPR CODE QUIZ

November 2025

1. Per Section 422.4 of the 2022 California Plumbing Code, required toilet facilities for employees and customers located in shopping malls or centers shall be permitted to be met by providing a centrally located toilet facility accessible to several stores. The maximum travel distance from entry to any store to the toilet facility shall not exceed \_\_\_\_ feet). Required toilet facilities for employees and customers in other than shopping malls or centers shall have a maximum travel distance not to exceed \_\_\_\_ feet.
  - a. 300 / 500
  - b. 300 / 250
  - c. 500 / 500
  - d. 300 / 300
2. Per Section 401.4 of the 2022 California Residential Code, where quantifiable data created by accepted soil science methodologies indicate \_\_\_\_, \_\_\_\_, \_\_\_\_ or other questionable soil characteristics are likely to be present, the building official shall determine whether to require a soil test to determine the soil's characteristics at a particular location. This test shall be done by an approved agency using an approved method.
  - a. Expansive soils, compressible soils, shifting soils
  - b. Stable rock, coarse-grained soils, organic soils
  - c. Coarse-grained soils, fine-grained soils, compressible soils
3. Per Section 1102.2 of the 2022 California Existing Building Code, an addition shall not increase the area of an existing building beyond that permitted under the applicable provisions of Chapter 5 of the California Building Code for new buildings unless fire separation as required by the California Building Code is provided.
  - a. True
  - b. False
4. Per Section 2407.1.2 of the 2022 California Building Code, guards with structural glass balusters, whether vertical posts, columns or panels, shall be installed with an attached top rail or handrail. The top rail or handrails shall be supported by not fewer than \_\_\_\_ glass balusters, or shall be otherwise supported to remain in place should one glass baluster fail.
  - a. Two
  - b. Three
  - c. Four
  - d. Five
5. Per Section 410.3 of the 2022 California Building Code, permanent platforms shall be constructed of materials as required for the type of construction of the building in which the permanent platform is located. Permanent platforms are permitted to be constructed of fire-retardant-treated wood for Types I, II and IV construction where the platforms are not more than \_\_\_\_ inches above the main floors, and not more than \_\_\_\_ of the room floor area and not more than \_\_\_\_ square feet in area.
  - a. 24, one-half, 2,000
  - b. 36, two-thirds, 1,000
  - c. 30, one-third, 3,000

*Answer Key: 1: a 2: a 3: a 4: b 5: c*

Please contact Ron Beehler by email at [rbeehler@bpr-grp.com](mailto:rbeehler@bpr-grp.com) to discuss any questions.