



## CODE QUIZ

November 2024

1. Per the 2022 CA Building Code Table 506.2 footnote k, Group R-2 of Type VA construction equipped throughout with an approved automatic sprinkler system in accordance with Section 903.3.1.1, S (sprinkler) area increase is permitted in addition to the height and story increase provided the height shall not exceed 60 feet and 4 stories.
  - a. True
  - b. False
2. Per the 2022 CA Building Code Section 706.8, each opening through a fire wall shall be protected in accordance with Section 716 and shall not exceed \_\_\_\_ sq. ft. The aggregate width of openings at any floor level shall not exceed \_\_\_\_% of the length of the wall.
  - a. 120 sq. ft. & 10%
  - b. 156 sq. ft. & 25%
  - c. 100 sq. ft. & 50%
  - d. 150 sq. ft. & 30%
3. Per 2022 CA Residential Code R310.1, basements with a ceiling height of more than 80" shall not be required to have emergency escape and rescue openings.
  - a. True
  - b. False
4. Per the 2022 CA Electrical Code 400.10, flexible cords and flexible cables shall be used for all of the following except:
  - a. Where concealed by walls, floors, or ceilings or located above suspended or dropped ceilings
  - b. Elevator cables
  - c. Connection of moving parts
  - d. Wiring of cranes and hoists
5. Per the 2022 CA Historical Code Section 8-201, the act or process of depicting, by means of new construction, the form, features and detailing of a non-surviving site, landscape, building, property or object for the purpose of replicating its appearance at a specific period of time is the definition of:
  - a. Rehabilitation
  - b. Reconstruction
  - c. Restoration



*Answer Key: 1: a 2: b 3: b 4: a 5: b*

Please contact Ron Beehler by email at [rbeehler@bpr-grp.com](mailto:rbeehler@bpr-grp.com) to discuss any questions.